



Garmin International, Inc.
1200 East 151st Street
Olathe, Kansas 66062
P: 913-397-8200 F: 913-397-8282

16-Feb-26

Manufacturer: Garmin International, Inc.

Address: 1200 E. 151st St.
Olathe, KS 66062-3426
U.S.A.

Chile Representative: Matías Rodríguez Correa
Rosario Norte 660 piso 24, Las Condes Santiago
Province CP 7550083, Chile

Contact Email: matias.rodriguez@garmin.com


Subject: SUBTEL, Chile (Resolution 737) Certification Compliance 2026

Commercial Name: EchoMap UHD2 7Xsv, EchoMap UHD2 6Xsv

	Información (Information)
Tipo de equipo (Equipment type)	Digital Transmission System Transceiver
Marca (Brand)	Garmin 
Modelo (Model)	A04266, B04266
Tecnología o modulación (Technology or modulation)	ANT (GFSK), BLE (GMSK), WiFi 2.4GHz (802.11 b/g/n)
Frecuencias (Frequencies)	ANT (2402MHz-2480MHz), BLE (2402MHz- 2480MHz), WiFi 2.4GHz (2412MHz – 2462MHz)
Ganancia de antena (dBi) (Antenna gain (dBi))	ANT PIFA (5.24 dBi), BLE PIFA (5.24 dBi), WiFi 2.4GHz PIFA (5.24 dBi)
P.i.r.e. (E.I R P.)	ANT (-1.95 dBm, 0.63 mW), BLE (11.58 dBm, 14.38 mW), WiFi 2.4GHz (14.13 dBm, 25.88 mW)
Módulos (Modules)	ANT , BLE, WiFi 2.4GHz

Declaration of Conformity Statement: the equipment previously identified complies with the provisions established in the Technical Standard for Small Range Equipment, approved by Exempt Resolution No.1,985 of 2017, of the Undersecretary of Telecommunications.

Declaración de conformidad: El equipo anteriormente identificado cumple con las disposiciones establecidas en la Norma Técnica para Equipos de Corto Alcance, aprobada mediante la Resolución Exenta N° 1.985 de 2017, de la Subsecretaría de Telecomunicaciones.



ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

47CFR, PART 15C - Intentional Radiators
47CFR Paragraph 15.247, Industry Canada
RSS-247 Issue 2, and RSS-GEN Issue 5
Application For Grant of Certification

Models: A04266, B04266

2402-2480 MHz (DTS)
Broadband Digital Transmission System

FCC ID: IPH-04266

IC: 1792A-04266

Garmin International, Inc.

1200 East 151st Street
Olathe, KS 66062

FCC Designation: US5305
ISED Registration: 3041A

Test Report Number: 220830

Test Date: August 30, 2022

Authorized Signatory: *Scot D Rogers*
Scot D. Rogers

This report shall not be reproduced except in full, without the written approval of the laboratory.
This report must not be used by the client to claim product certification, approval, or
endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: 47CFR 15C, RSS-Gen RSS-247
File: 04266 DTS TstRpt 220830

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: November 28, 2022
Page 1 of 58

Table of Contents

TABLE OF CONTENTS.....	2
REVISIONS.....	4
EXECUTIVE SUMMARY	5
OPINION / INTERPRETATION OF RESULTS	6
EQUIPMENT TESTED.....	8
Equipment Operational Modes.....	8
Equipment Function	9
Equipment Configuration.....	9
APPLICATION FOR CERTIFICATION.....	10
APPLICABLE STANDARDS & TEST PROCEDURES	11
TESTING PROCEDURES	11
AC Line Conducted Emission Test Procedure	11
Radiated Emission Test Procedure.....	11
Antenna Port Conducted Emission Test Procedure.....	11
Diagram 1 Test arrangement for radiated emissions of tabletop equipment.....	12
Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)	13
Diagram 3 Test arrangement for Antenna Port Conducted emissions	13
TEST SITE LOCATIONS	14
UNITS OF MEASUREMENTS	14
ENVIRONMENTAL CONDITIONS.....	15
STATEMENT OF MODIFICATIONS AND DEVIATIONS	15
INTENTIONAL RADIATORS.....	15
Antenna Requirements	15

Restricted Bands of Operation	15
Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 2 BLE.....	16
Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 3 802.11b	17
Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 4 802.11g	18
Table 4 Radiated Emissions in Restricted Frequency Bands Data Mode 5 802.11n	19
Summary of Results for Radiated Emissions in Restricted Bands	19
General Radiated Emissions Procedure	20
Table 4 General Radiated Emissions Data	21
Summary of Results for General Radiated Emissions	21
Operation in the Band 2400 – 2483.5 MHz	22
Figure 1 Plot of Transmitter Operation in 2402-2480 MHz Mode 2 BLE	23
Figure 2 Plot of Transmitter Operation in 2412-2462 MHz Mode 3 802.11b	24
Figure 3 Plot of Transmitter Operation in 2412-2462 MHz Mode 4 802.11g	25
Figure 4 Plot of Transmitter Operation in 2412-2462 MHz Mode 5 802.11n	26
Figure 5 Plot of Transmitter Emissions Low Band Edge Mode 2 BLE.....	27
Figure 6 Plot of Transmitter Emissions Low Band Edge Mode 3 802.11b	28
Figure 7 Plot of Transmitter Emissions Low Band Edge Mode 4 802.11g	29
Figure 8 Plot of Transmitter Emissions Low Band Edge Mode 5 802.11n	30
Figure 9 Plot of Transmitter Emissions High Band Edge Mode 2 BLE	31
Figure 10 Plot of Transmitter Emissions High Band Edge Mode 3 802.11b.....	32
Figure 11 Plot of Transmitter Emissions High Band Edge Mode 4 802.11g.....	33
Figure 12 Plot of Transmitter Emissions High Band Edge Mode 5 802.11n.....	34
Figure 13 Plot of 6-dB Occupied Bandwidth Mode 2 BLE.....	35
Figure 14 Plot of 99% Occupied Bandwidth Mode 2 BLE	36
Figure 15 Plot of 6-dB Occupied Bandwidth Mode 3 802.11b	37
Figure 16 Plot of 99% Occupied Bandwidth Mode 3 802.11b	38
Figure 17 Plot of 6-dB Occupied Bandwidth Mode 4 802.11g	39
Figure 18 Plot of 99% Occupied Bandwidth Mode 4 802.11g	40
Figure 19 Plot of 6-dB Occupied Bandwidth Mode 5 802.11n	41
Figure 20 Plot of 99% Occupied Bandwidth Mode 5 802.11n	42
Figure 21 Plot of Transmitter Power Spectral Density Mode 2 BLE	43
Figure 22 Plot of Transmitter Power Spectral Density Mode 3 802.11b.....	44
Figure 23 Plot of Transmitter Power Spectral Density Mode 4 802.11g.....	45

Figure 24 Plot of Transmitter Power Spectral Density Mode 5 802.11n	46
Transmitter Emissions Data	47
Table 5 Transmitter Radiated Emissions Mode 2 BLE	47
Table 6 Transmitter Radiated Emissions Mode 3 802.11b	48
Table 6 Transmitter Radiated Emissions Mode 4 802.11g	49
Table 7 Transmitter Radiated Emissions Mode 5 802.11n	50
Table 8 Transmitter Antenna Port Conducted Data modes 2, 3, 4, and 5	51
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator	52
ANNEX	53
Annex A Measurement Uncertainty Calculations	54
Annex B Test Equipment	55
Annex C Rogers Qualifications	57
Annex D Laboratory Certificate of Accreditation	58

Revisions

Revision 1 Issued November 28, 2022

Executive Summary

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under Code of Federal Regulations Title 47 (47CFR) Part 15C paragraph 15.247, Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5, operation in the 2400 – 2483.5 MHz band.

Name of Applicant: Garmin International, Inc.
 1200 East 151st Street
 Olathe, KS 66062

HVIN's: A04266, B04266

FCC ID: IPH-04266 IC: 1792A-04266

Frequency Range: operation in the 2402-2480 MHz band

Operational communication modes 2, 3, 4, and 5

Mode	Power (Watts)	99% OBW (kHz)	6-dB OBW (kHz)
Mode 2 BLE	0.010	1,053.8	720
Mode 3 802.11b	0.012	11,175.0	8,430
Mode 4 802.11g	0.017	16,777.5	16,349.6
Mode 5 802.11n	0.018	17,970.0	16,867.5

This report addresses EUT Operations as Digital Transmission System using transmitter modulations in modes 2 through 5. Note, the production device utilizes integral antenna system.

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions 15.205, RSS-GEN, RSS-247	-5.9	Complies
Emissions as per 47CFR 15.207, RSS-GEN 8.8	N/A	Complies
Radiated Emissions 47 CFR 15.209, RSS-GEN 8.9	-2.4	Complies
Harmonic Emissions per 47CFR 15.247, RSS-247	-2.2	Complies
Power Spectral Density per 47CFR 15.247, RSS-247	-12.7	Complies

Tests performed include

47CFR

15.247 (a) (2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one-Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in

accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Issue 2

5.2 Digital transmission systems

DTS's include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz

a) The minimum 6 dB bandwidth shall be 500 kHz.

b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e., the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.4 Transmitter output power and equivalent isotropically radiated power (e.i.r.p.) requirements

d) For DTS's employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

5.5 Unwanted emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Equipment Tested

Models: A04266, B04266

Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT	A04266	3425814614
EUT (Ant Port)	A04266	3425814607
DC power Cable	Garmin 4-pin	N/A
Garmin Transducer	011-04943-00	637051630
Garmin Network device	011-03208-00	5JW000066
5-pin NMEA 2000 Cable	Garmin NMEA Cable	N/A
Garmin Sensor	011-04314-01	N/A
Garmin Network Cable (6m)	320-00372-03	N/A
DC power Cable (2.3m)	Garmin 2-pin	N/A
DC Power Supply	BK 1745	209C13

Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

Software: 29.44

Antenna: 2.4 GHz PIFA (1.6 dBi)


Equipment Operational Modes

Mode	Transmitter Operation
1	ANT (GFSK)
2	BT BLE (GMSK)
3	802.11b
4	802.11g
5	802.11n

Equipment Function

The EUT is a mapping display and interface system providing interface options for use with compatible equipment. The design incorporates transmitter with operation capability in the 2,400-2,483.5 MHz frequency band. The GPS design offers use as a marine mounted mobile configuration for use in navigational aid applications. The transmitter design is provided in two display sizes, 7-inch HVIN: A04266, or 6-inch HVIN: B04266. The transmitter is electrically identical in both versions. Two samples were supplied for testing, one production design and the other modified for testing purposes replacing integral antenna with RF connection port. Both samples were provided with test software enabling testing personnel the ability to test operational functions. The antenna modification offered testing facility ability to connect test equipment directly to the transmitter output. The EUT was arranged in a testing configuration emulating user equipment for testing purposes. The design offers no other interface connections than those in the configuration diagrams shown below. The EUT operates from externally supplied direct current power. The EUT was powered through the manufacturer supplied power cable operating at 12 Vdc from a DC power supply for testing purposes. Test results in this report relate only to the products described in this report.

Equipment Configuration



Application for Certification

- (1) Manufacturer: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062
- (2) Identification: HVIN's: A04266, B04266
FCC ID: IPH-04266 IC: 1792A-04266
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from external direct current power provided from marine installation power sources. The EUT provides interface ports for associated marine accessories and power as presented in this filing.
- (9) Transition Provisions of 47CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards & Test Procedures

The following information is submitted in accordance with the eCFR Code of Federal Regulations Title 47 (47CFR), dated August 30, 2022: Part 2, Subpart J, Part 15C Paragraph 15.247, Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations as Digital Transmission Systems operation.

Testing Procedures

AC Line Conducted Emission Test Procedure

The EUT operates on direct current power only provided by the vehicle installation. Therefore, no AC line conducted emission testing was required or performed.


Radiated Emission Test Procedure

Radiated emissions testing was performed as required in 47CFR 15C, RSS-247 Issue 2, RSS-GEN and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. The frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions during preliminary investigation. Refer to diagrams one and two showing typical test setup. Refer to photographs in the test setup exhibits for specific EUT placement during testing.

Antenna Port Conducted Emission Test Procedure

The EUT was assembled as required for operation and placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed as presented in this document and specified in ANSI C63.10-2013. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Diagram 1 Test arrangement for radiated emissions of tabletop equipment



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).

1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).

4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)





Diagram 3 Test arrangement for Antenna Port Conducted emissions



Test Site Locations

Conducted EMI	AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Antenna port	Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096	
NVLAP Accreditation	Lab code 200087-0

Units of Measurements

Conducted EMI	Data presented in dB μ V; dB referenced to one microvolt
Antenna port Conducted	Data is in dBm; dB referenced to one milliwatt
Radiated EMI	Data presented in dB μ V/m; dB referenced to one microvolt per meter

Note: Radiated limit may be expressed for measurement in dB μ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters. Sample calculation demonstrates corrected field strength reading for Open Area Test Site using the measurement reading and correcting for receive antenna factor, cable losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

$RFS \text{ (dB}\mu\text{V/m @ 3m)} = FSM \text{ (dB}\mu\text{V)} + A.F. \text{ (dB/m)} + \text{Losses (dB)} - \text{Gain (dB)}$

Rogers Labs, Inc.	Garmin International, Inc.	SN's: 3425814614, 3425814607
4405 West 259 th Terrace	HVIN's: A04266, B04266	FCC ID: IPH-04266
Louisburg, KS 66053	Test: 220830	IC: 1792A-04266
Phone/Fax: (913) 837-3214	Test to: 47CFR 15C, RSS-Gen RSS-247	Date: November 28, 2022
Revision 1	File: 04266 DTS TstRpt 220830	Page 14 of 58

Environmental Conditions

Ambient Temperature	24.8° C
Relative Humidity	41 %
Atmospheric Pressure	1020.6 mb

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with 47CFR Part 15C, RSS-247 Issue 2, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

Intentional Radiators

The following information is submitted supporting demonstration of compliance with the requirements of 47CFR, Paragraph 15 Subpart C, paragraph 15.247, Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5.

Antenna Requirements

The EUT incorporates integral Planer Inverted F Antenna (PIFA) system. Production equipment offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values

consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 2 BLE

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	44.7	30.9	43.3	30.5	54.0	-23.1	-23.5
2483.5	45.0	31.1	44.5	31.0	54.0	-22.9	-23.0
4804.0	50.1	36.5	49.4	36.5	54.0	-17.5	-17.5
4880.0	49.5	36.6	49.5	36.6	54.0	-17.4	-17.4
4960.0	49.4	36.0	49.2	36.0	54.0	-18.0	-18.0
7206.0	53.9	40.4	53.3	40.5	54.0	-13.6	-13.5
7320.0	53.3	40.4	53.5	40.6	54.0	-13.6	-13.4
7440.0	53.3	40.4	53.5	40.4	54.0	-13.6	-13.6
12010.0	59.3	46.3	59.0	46.2	54.0	-7.7	-7.8
12200.0	60.0	47.4	60.2	47.4	54.0	-6.6	-6.6
12400.0	60.1	47.5	61.0	47.6	54.0	-6.5	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 3 802.11b

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	45.3	31.2	49.3	32.7	54.0	-22.8	-21.3
2483.5	45.2	31.3	47.3	32.2	54.0	-22.7	-21.8
4824.0	49.1	36.4	49.3	36.3	54.0	-17.6	-17.7
4874.0	49.3	36.4	49.5	36.4	54.0	-17.6	-17.6
4924.0	49.6	36.6	49.8	36.6	54.0	-17.4	-17.4
7236.0	53.1	40.1	52.9	40.1	54.0	-13.9	-13.9
7311.0	53.0	40.3	53.0	40.3	54.0	-13.7	-13.7
7386.0	53.2	40.3	53.0	40.3	54.0	-13.7	-13.7
12060.0	58.8	46.3	59.0	46.2	54.0	-7.7	-7.8
12185.0	60.7	47.6	60.3	47.2	54.0	-6.4	-6.8
12310.0	61.0	47.8	60.5	47.8	54.0	-6.2	-6.2

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 4 802.11g

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	48.7	33.4	52.8	37.0	54.0	-20.6	-17.0
2483.5	45.9	32.5	47.1	33.5	54.0	-21.5	-20.5
4824.0	49.4	36.2	49.5	36.2	54.0	-17.8	-17.8
4874.0	49.2	36.3	49.5	36.3	54.0	-17.7	-17.7
4924.0	50.0	36.4	49.2	36.4	54.0	-17.6	-17.6
7236.0	53.0	40.1	52.9	40.0	54.0	-13.9	-14.0
7311.0	52.5	40.2	53.2	40.3	54.0	-13.8	-13.7
7386.0	53.2	40.2	53.3	40.2	54.0	-13.8	-13.8
12060.0	59.8	47.0	59.5	47.0	54.0	-7.0	-7.0
12185.0	59.8	47.2	61.0	47.8	54.0	-6.8	-6.2
12310.0	61.4	47.7	60.9	48.1	54.0	-6.3	-5.9

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 4 Radiated Emissions in Restricted Frequency Bands Data Mode 5 802.11n

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	46.1	32.5	50.6	35.5	54.0	-21.5	-18.5
2483.5	45.9	32.3	48.1	33.2	54.0	-21.7	-20.8
4824.0	49.6	36.2	49.1	36.2	54.0	-17.8	-17.8
4874.0	49.2	36.4	49.3	36.4	54.0	-17.6	-17.6
4924.0	49.4	36.6	49.3	36.5	54.0	-17.4	-17.5
7236.0	52.9	40.1	52.8	40.1	54.0	-13.9	-13.9
7311.0	54.3	40.4	53.0	40.4	54.0	-13.6	-13.6
7386.0	52.9	40.3	52.9	40.2	54.0	-13.7	-13.8
12060.0	59.5	46.4	59.9	46.6	54.0	-7.6	-7.4
12185.0	60.7	48.0	60.5	47.2	54.0	-6.0	-6.8
12310.0	61.2	47.7	60.6	47.6	54.0	-6.3	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Paragraph 15, Subpart 15C, RSS-247 Issue 2, and RSS-GEN Issue 5 emission requirements. The EUT worst-case operations demonstrated a minimum radiated emission margin of -5.9 dB below the requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available mode during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Requirement, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. Attenuation below the general limits specified in 47CFR 15.209 are not required. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Table 4 General Radiated Emissions Data

Frequency (MHz)	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
63.6	40.4	29.7	35.7	28.9	40.0	-10.3	-11.1
111.6	35.7	30.7	37.2	29.5	40.0	-9.3	-10.5
122.2	33.7	27.1	30.1	23.3	40.0	-12.9	-16.7
151.5	39.4	30.4	33.7	26.8	40.0	-9.6	-13.2
155.6	38.3	28.0	28.2	21.7	40.0	-12.0	-18.3
170.1	37.2	31.2	37.8	32.6	40.0	-8.8	-7.4
180.7	35.5	30.3	30.7	24.8	40.0	-9.7	-15.2
199.2	42.4	37.6	35.1	30.0	40.0	-2.4	-10.0
438.5	42.2	40.8	38.5	37.1	47.0	-6.2	-9.9

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Paragraph 15.209, RSS-247 Issue 2 and RSS-GEN Issue 5 emission requirements. The EUT demonstrated a minimum margin of -2.4 dB below the requirement. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 2400 – 2483.5 MHz

Test procedures of ANSI C63.10-2013 paragraph 6, and KDB 558074 v05r02 were used during transmitter testing. Test sample #2 was provided for testing antenna port conducted emissions. This sample was modified by replacing the internal antenna with a 50-ohm antenna port connector and attenuator for testing purposes. The transmitter peak and average power was measured at the antenna port using a wideband RF power meter as described in ANSI C63.10-2013 and KDB 558074. Average power measured did not include any time intervals during which the transmitter was off or transmitting at a reduced power level. The Power Spectral Density (PSD) was measured as required in ANSI C63.10-2013 and KDB 558074. DTS Emission bandwidth was measured as required in ANSI C63.10-2013 and KDB 558074. The amplitude of each harmonic and general radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna (radiated emission testing was performed on sample #1 representative of production equipment with integral antenna). The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 25,000 MHz. Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dBμV/m @ 3 meters. Plots were taken of transmitter performance (using sample #2) for reference in this and other documentation displaying compliance with the specifications.

Figure 1 Plot of Transmitter Operation in 2402-2480 MHz Mode 2 BLE




Figure 2 Plot of Transmitter Operation in 2412-2462 MHz Mode 3 802.11b




Figure 3 Plot of Transmitter Operation in 2412-2462 MHz Mode 4 802.11g




Figure 4 Plot of Transmitter Operation in 2412-2462 MHz Mode 5 802.11n




Figure 5 Plot of Transmitter Emissions Low Band Edge Mode 2 BLE




Figure 6 Plot of Transmitter Emissions Low Band Edge Mode 3 802.11b




Figure 7 Plot of Transmitter Emissions Low Band Edge Mode 4 802.11g




Figure 8 Plot of Transmitter Emissions Low Band Edge Mode 5 802.11n




Figure 9 Plot of Transmitter Emissions High Band Edge Mode 2 BLE




Figure 10 Plot of Transmitter Emissions High Band Edge Mode 3 802.11b




Figure 11 Plot of Transmitter Emissions High Band Edge Mode 4 802.11g




Figure12 Plot of Transmitter Emissions High Band Edge Mode 5 802.11n




Figure 13 Plot of 6-dB Occupied Bandwidth Mode 2 BLE




Figure 14 Plot of 99% Occupied Bandwidth Mode 2 BLE




Figure 15 Plot of 6-dB Occupied Bandwidth Mode 3 802.11b




Figure 16 Plot of 99% Occupied Bandwidth Mode 3 802.11b




Figure 17 Plot of 6-dB Occupied Bandwidth Mode 4 802.11g




Figure 18 Plot of 99% Occupied Bandwidth Mode 4 802.11g




Figure 19 Plot of 6-dB Occupied Bandwidth Mode 5 802.11n




Figure 20 Plot of 99% Occupied Bandwidth Mode 5 802.11n




Figure 21 Plot of Transmitter Power Spectral Density Mode 2 BLE




Figure 22 Plot of Transmitter Power Spectral Density Mode 3 802.11b




Figure 23 Plot of Transmitter Power Spectral Density Mode 4 802.11g





Figure 24 Plot of Transmitter Power Spectral Density Mode 5 802.11n



Transmitter Emissions Data

Table 5 Transmitter Radiated Emissions Mode 2 BLE

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	--	--	--	--	--	--	--
4804.0	50.1	36.5	49.4	36.5	54.0	-17.5	-17.5
7206.0	53.9	40.4	53.3	40.5	54.0	-13.6	-13.5
9608.0	57.0	43.7	56.7	43.8	54.0	-10.3	-10.2
12010.0	59.3	46.3	59.0	46.2	54.0	-7.7	-7.8
14412.0	60.9	48.0	61.2	47.9	54.0	-6.0	-6.1
16814.0	63.2	51.1	64.2	51.1	54.0	-2.9	-2.9
2440.0	--	--	--	--	--	--	--
4880.0	49.5	36.6	49.5	36.6	54.0	-17.4	-17.4
7320.0	53.3	40.4	53.5	40.6	54.0	-13.6	-13.4
9760.0	57.1	44.0	57.1	44.0	54.0	-10.0	-10.0
12200.0	60.0	47.4	60.2	47.4	54.0	-6.6	-6.6
14640.0	61.3	48.5	61.3	48.5	54.0	-5.5	-5.5
17080.0	64.1	51.0	63.8	51.0	54.0	-3.0	-3.0
2480.0	--	--	--	--	--	--	--
4960.0	49.4	36.0	49.2	36.0	54.0	-18.0	-18.0
7440.0	53.3	40.4	53.5	40.4	54.0	-13.6	-13.6
9920.0	56.6	43.3	57.1	44.0	54.0	-10.7	-10.0
12400.0	60.1	47.5	61.0	47.6	54.0	-6.5	-6.4
14880.0	61.5	48.6	61.3	48.5	54.0	-5.4	-5.5
17360.0	64.5	51.1	63.7	51.1	54.0	-2.9	-2.9

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 6 Transmitter Radiated Emissions Mode 3 802.11b

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2412.0	--	--	--	--	--	--	--
4824.0	49.1	36.4	49.3	36.3	54.0	-17.6	-17.7
7236.0	53.1	40.1	52.9	40.1	54.0	-13.9	-13.9
9648.0	56.8	44.0	57.2	44.6	54.0	-10.0	-9.4
12060.0	58.8	46.3	59.0	46.2	54.0	-7.7	-7.8
14472.0	61.0	47.9	61.2	47.9	54.0	-6.1	-6.1
16884.0	63.5	51.0	64.3	51.0	54.0	-3.0	-3.0
2437.0	--	--	--	--	--	--	--
4874.0	49.3	36.4	49.5	36.4	54.0	-17.6	-17.6
7311.0	53.0	40.3	53.0	40.3	54.0	-13.7	-13.7
9748.0	56.2	43.8	57.4	44.6	54.0	-10.2	-9.4
12185.0	60.7	47.6	60.3	47.2	54.0	-6.4	-6.8
14622.0	61.3	48.6	61.2	48.7	54.0	-5.4	-5.3
17059.0	64.0	51.0	64.0	51.0	54.0	-3.0	-3.0
2462.0	--	--	--	--	--	--	--
4924.0	49.6	36.6	49.8	36.6	54.0	-17.4	-17.4
7386.0	53.2	40.3	53.0	40.3	54.0	-13.7	-13.7
9848.0	57.2	44.4	57.4	44.9	54.0	-9.6	-9.1
12310.0	61.0	47.8	60.5	47.8	54.0	-6.2	-6.2
14772.0	61.3	48.9	61.4	48.9	54.0	-5.1	-5.1
17234.0	62.9	50.3	63.1	50.2	54.0	-3.7	-3.8

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 6 Transmitter Radiated Emissions Mode 4 802.11g

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2412.0	--	--	--	--	--	--	--
4824.0	49.4	36.2	49.5	36.2	54.0	-17.8	-17.8
7236.0	53.0	40.1	52.9	40.0	54.0	-13.9	-14.0
9648.0	56.5	44.2	57.0	44.2	54.0	-9.8	-9.8
12060.0	59.8	47.0	59.5	47.0	54.0	-7.0	-7.0
14472.0	60.5	47.7	60.3	47.6	54.0	-6.3	-6.4
16884.0	64.4	51.1	63.8	51.0	54.0	-2.9	-3.0
2437.0	--	--	--	--	--	--	--
4874.0	49.2	36.3	49.5	36.3	54.0	-17.7	-17.7
7311.0	52.5	40.2	53.2	40.3	54.0	-13.8	-13.7
9748.0	56.6	43.8	56.7	43.9	54.0	-10.2	-10.1
12185.0	59.8	47.2	61.0	47.8	54.0	-6.8	-6.2
14622.0	61.5	48.4	61.3	48.4	54.0	-5.6	-5.6
17059.0	64.1	51.8	65.4	51.8	54.0	-2.2	-2.2
2462.0	--	--	--	--	--	--	--
4924.0	50.0	36.4	49.2	36.4	54.0	-17.6	-17.6
7386.0	53.2	40.2	53.3	40.2	54.0	-13.8	-13.8
9848.0	57.1	44.1	57.0	44.3	54.0	-9.9	-9.7
12310.0	61.4	47.7	60.9	48.1	54.0	-6.3	-5.9
14772.0	61.5	48.7	61.5	48.7	54.0	-5.3	-5.3
17234.0	63.4	50.6	64.0	50.5	54.0	-3.4	-3.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 7 Transmitter Radiated Emissions Mode 5 802.11n

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2412.0	--	--	--	--	--	--	--
4824.0	49.6	36.2	49.1	36.2	54.0	-17.8	-17.8
7236.0	52.9	40.1	52.8	40.1	54.0	-13.9	-13.9
9648.0	57.4	44.1	57.3	44.3	54.0	-9.9	-9.7
12060.0	59.5	46.4	59.9	46.6	54.0	-7.6	-7.4
14472.0	60.2	47.7	60.5	47.7	54.0	-6.3	-6.3
16884.0	63.9	51.1	64.0	51.1	54.0	-2.9	-2.9
2437.0	--	--	--	--	--	--	--
4874.0	49.2	36.4	49.3	36.4	54.0	-17.6	-17.6
7311.0	54.3	40.4	53.0	40.4	54.0	-13.6	-13.6
9748.0	56.9	43.9	57.3	43.9	54.0	-10.1	-10.1
12185.0	60.7	48.0	60.5	47.2	54.0	-6.0	-6.8
14622.0	61.5	48.5	61.7	48.6	54.0	-5.5	-5.4
17059.0	64.7	51.8	64.4	51.6	54.0	-2.2	-2.4
2462.0	--	--	--	--	--	--	--
4924.0	49.4	36.6	49.3	36.5	54.0	-17.4	-17.5
7386.0	52.9	40.3	52.9	40.2	54.0	-13.7	-13.8
9848.0	57.3	44.5	57.0	44.5	54.0	-9.5	-9.5
12310.0	61.2	47.7	60.6	47.6	54.0	-6.3	-6.4
14772.0	61.7	48.8	61.4	48.8	54.0	-5.2	-5.2
17234.0	63.3	50.2	63.5	50.3	54.0	-3.8	-3.7

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 8 Transmitter Antenna Port Conducted Data modes 2, 3, 4, and 5

Frequency MHz	Antenna Port Average Output Power (Watts)	99% Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm)
Mode 2 BLE				
2402.0	0.009	1,053.0	712.1	-5.2
2440.0	0.010	1,053.0	712.5	-4.7
2480.0	0.007	1,053.8	720.0	-6.6
Mode 3 802.11b				
2412.0	0.011	11,032.5	8,295.0	-12.8
2437.0	0.012	11,145.0	8,430.0	-11.4
2462.0	0.012	11,175.0	8,260.0	-11.7
Mode 4 802.11g				
2412.0	0.006	16,582.5	16,257.5	-15.6
2437.0	0.017	16,740.0	16,349.6	-11.1
2462.0	0.006	16,777.5	16,265.0	-15.4
Mode 5 802.11n				
2412.0	0.004	17,850.0	15,920.6	-16.8
2437.0	0.018	17,940.0	16,867.5	-11.2
2462.0	0.005	17,970.0	16,097.7	-16.2

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated and conducted emission requirements of 47CFR Subpart 15C Paragraph 15.247, RSS-247 Issue 2 and RSS-GEN Issue 5 emission requirements for Digital Transmission Systems. Highest average output power measured at the antenna port was 0.018 Watts. The highest peak power spectral density measured at the antenna port presented a minimum margin of -12.7 dB below the requirements. The EUT demonstrated a minimum margin of -2.2 dB below the radiated harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Rogers Qualifications
- Annex D Rogers Labs Certificate of Accreditation

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16–4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Test Equipment

Equipment	Manufacturer	Model (SN)	Band	Cal Date(m/d/y)	Due
☐ LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/29/2022	3/29/2023
☐ LISN: Fischer Custom Communications Model:		FCC-LISN-50-16-2-08		3/29/2022	3/29/2023
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	10/14/2021	10/14/2022
☐ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	10/14/2021	10/14/2022
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303070)	9kHz-40 GHz	10/14/2021	10/14/2022
☐ Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/14/2021	10/14/2022
☐ Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/14/2021	10/14/2022
☒ Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/14/2021	10/14/2022
☐ Antenna:	EMCO	6509	.001-30 MHz	10/14/2020	10/14/2022
☐ Antenna	ARA	BCD-235-B (169)	20-350MHz	10/14/2021	10/14/2022
☐ Antenna:	Schwarzbeck Model	VHBB 9124 (1468)	30-200MHz	10/14/2020	10/14/2022
☒ Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/14/2021	10/14/2022
☐ Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	10/14/2020	10/14/2022
☐ Antenna:	Schwarzbeck Model:	VULP 9118 (A-534)	200-1000MHz	10/14/2020	10/14/2022
☒ Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	3/29/2022	3/29/2024
☐ Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/14/2020	10/14/2022
☒ Antenna	Com Power	AH-840 (101046)	18-40 GHz	4/6/2021	4/6/2023
☒ Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	3/9/2022	3/9/2023
☒ Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/18/2022	1/18/2023
☐ Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
☒ Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/14/2021	10/14/2022
☒ Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/14/2021	10/14/2022
☒ Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/14/2021	10/14/2022
☒ Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/14/2021	10/14/2022
☒ Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	3/29/2022	3/29/2023
☐ Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	3/29/2022	3/29/2023
☐ Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/29/2022	3/29/2023
☐ RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	4/6/2021	4/6/2023
☒ RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ Attenuator	Fairview	SA6NFFNF100W-40 (1625)	30-18000 MHz	3/29/2022	3/29/2023
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	3/29/2022	3/29/2023
☒ Weather station	Davis	6312 (A81120N075)		11/4/2021	11/4/2022

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: 47CFR 15C, RSS-Gen RSS-247
File: 04266 DTS TstRpt 220830

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: November 28, 2022
Page 55 of 58

List of Test Equipment

Calibration Date (m/d/y) Due

☐	Antenna:	Schwarzbeck Model VHBB 9124 (01468)	10/14/2020	10/14/2022
☐	Antenna:	Schwarzbeck Model: VULP 9118 A (VULP 9118 A-856)	10/14/2020	10/14/2022
☐	Frequency Counter:	Leader LDC-825 (8060153)	3/29/2022	4/6/2023
☐	ISN: Com-Power Model	ISN T-8	3/29/2022	3/29/2023
☐	LISN	Compliance Design FCC-LISN-2.Mod.cd,(126) .15-30MHz	10/14/2021	10/14/2022
☐	LISN: Com-Power Model	LI-220A	10/14/2020	10/14/2022
☐	LISN: Com-Power Model	LI-550C	10/14/2020	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(1.5M)(303072) 9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(L1M)(281183) 9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(L4M)(281184) 9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(L10M)(317546)9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Time Microwave 4M-750HF290-750 (4M) 9kHz-24 GHz	10/14/2021	10/14/2022
☐	RF Filter	Micro-Tronics BRC17663 (001) 9.3-9.5 notch 30-1800 MHz	4/6/2021	4/6/2023
☐	RF Filter	Micro-Tronics BRC19565 (001) 9.2-9.6 notch 30-1800 MHz	10/14/2021	10/14/2023
☐	Analyzer	HP 8562A (3051A05950) 9kHz-125GHz	3/29/2022	3/29/2023
☐	Wave Form Generator	Keysight 33512B (MY57400128)	3/29/2022	3/29/2023
☐	Antenna:	Solar 9229-1 & 9230-1	2/22/2022	2/22/2023
☐	CDN: Com-Power Model	CDN325E	10/14/2021	10/14/2022
☐	Injection Clamp	Luthi Model EM101	10/14/2021	10/14/2022
☐	Oscilloscope Scope:	Tektronix MDO 4104	2/22/2022	2/22/2023
☐	EMC Transient Generator	HVT TR 3000	2/22/2022	2/22/2023
☐	AC Power Source (Ametech, California Instruments)		2/22/2022	2/22/2023
☐	Field Intensity Meter:	EFM-018	2/22/2022	2/22/2023
☐	ESD Simulator:	MZ-15	2/22/2022	2/22/2023
☐	R.F. Power Amp	ACS 230-50W	not required	
☐	R.F. Power Amp	EIN Model: A301	not required	
☐	R.F. Power Amp	A.R. Model: 10W 1010M7	not required	
☐	R.F. Power Amp	A.R. Model: 50U1000	not required	
☐	Temperature Chamber		not required	
☒	Shielded Room		not required	

Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has over 35 years' experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held:

Systems Engineer: A/C Controls Mfg. Co., Inc.

Electrical Engineer: Rogers Consulting Labs, Inc.

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background:

Bachelor of Science Degree in Electrical Engineering from Kansas State University

Bachelor of Science Degree in Business Administration Kansas State University

Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming

Annex D Laboratory Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, Inc.
Louisburg, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2022-03-22 through 2023-03-31

Effective Dates




[Signature]
For the National Voluntary Laboratory Accreditation Program

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: 47CFR 15C, RSS-Gen RSS-247
File: 04266 DTS TstRpt 220830

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: November 28, 2022
Page 58 of 58



ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

47CFR, PART 15C - Intentional Radiators 47CFR Paragraph 15.249 and Industry Canada RSS-GEN Issue 5 and RSS-210 Issue 10 Application For Grant of Certification

Model: A04266, B04266

2402-2480 MHz

Low Power Digital Transmitter (DXX))

FCC ID: IPH-04266

IC: 1792A-04266

Garmin International, Inc.


1200 East 151st Street
Olathe, KS 66062

FCC Designation: US5305

ISED Registration: 3041A

Test Report Number: 220830

Test Date: August 30, 2022

Authorized Signatory: 
Scot D. Rogers

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: 47CFR 15C, RSS-Gen RSS-210
File: 04266 DXX TstRpt 220830

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: November 28, 2022
Page 1 of 28

Table of Contents

TABLE OF CONTENTS.....	2
REVISIONS.....	3
EXECUTIVE SUMMARY	4
OPINION / INTERPRETATION OF RESULTS	4
EQUIPMENT TESTED.....	5
Equipment Operational Modes.....	5
Equipment Function	6
Equipment Configuration.....	6
APPLICATION FOR CERTIFICATION.....	7
APPLICABLE STANDARDS.....	8
EQUIPMENT TESTING PROCEDURES	8
AC Line Conducted Emission Test Procedure	8
Radiated Emission Test Procedure.....	8
Antenna Port Conducted Emission Test Procedure.....	8
Diagram 1 Test arrangement for radiated emissions of tabletop equipment.....	9
Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS).....	10
Diagram 3 Test arrangement for Antenna Port Conducted emissions	10
TEST SITE LOCATIONS	11
UNITS OF MEASUREMENTS	11
ENVIRONMENTAL CONDITIONS.....	12
STATEMENT OF MODIFICATIONS AND DEVIATIONS	12
INTENTIONAL RADIATORS.....	12
Antenna Requirements	12

Restricted Bands of Operation	12
Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1 ANT (GFSK)	13
Summary of Results for Radiated Emissions in Restricted Bands	13
General Radiated Emissions Procedure	14
Table 2 General Radiated Emissions Data	15
Summary of Results for General Radiated Emissions	15
Operation in the Band 2400 – 2483.5 MHz	16
Figure 1 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 1 ANT (GFSK).....	17
Figure 2 Plot of Transmitter Emissions Low Band Edge Mode 1 ANT (GFSK)	18
Figure 3 Plot of Transmitter Emissions High Band Edge Mode 1 ANT (GFSK)	19
Figure 4 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 1 ANT (GFSK)	20
Transmitter Emissions Data.....	21
Table 3 Transmitter Radiated Emissions Mode 1 ANT (GFSK).....	21
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....	22
ANNEX.....	23
Annex A Measurement Uncertainty Calculations	24
Annex B Test Equipment.....	25
Annex C Rogers Qualifications	27
Annex D Laboratory Certificate of Accreditation.....	28

Revisions

Revision 1 Issued November 28, 2022

Executive Summary

License Exempt Digital Transmission System Intentional Radiator operating under Title 47 Code of Federal Regulations (47 CFR) Paragraph 15.249 and Industry Canada RSS-210 Issue 10 and RSS-GEN Issue 5, low power (DXX) digital device transmitter operations in the 2400 – 2483.5 MHz frequency band.

Name of Applicant: Garmin International, Inc.
 1200 East 151st Street
 Olathe, KS 66062

M/N's: A04266, B04266 HVIN's: A04266, B04266
 FCC ID: IPH-04266 IC: 1792A-04266
 Operating Frequency Range: 2402-2480 MHz

Operational communication mode 1

Mode	Peak Power (dBμV/m@3m)	Average power (dBμV/m@3m)	99% OBW (kHz)
ANT (GFSK)	93.3	87.6	1,044

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Bands 47 CFR 15.205, RSS-210 4.1	-6.6	Complies
Radiated Emissions 47 CFR 15.209, RSS-GEN 8.9	-2.4	Complies
Harmonic Emissions per 47 CFR 15.249, RSS-210 B.10	-3.0	Complies

Equipment Tested

Models: A04266, B04266

Garmin International, Inc.
 1200 East 151st Street
 Olathe, KS 66062

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT	A04266	3425814614
EUT (Ant Port)	A04266	3425814607
DC power Cable	Garmin 4-pin	N/A
Garmin Transducer	011-04943-00	637051630
Garmin Network device	011-03208-00	5JW000066
5-pin NMEA 2000 Cable	Garmin NMEA Cable	N/A
Garmin Sensor	011-04314-01	N/A
Garmin Network Cable (6m)	320-00372-03	N/A
DC power Cable (2.3m)	Garmin 2-pin	N/A
DC Power Supply	BK 1745	209C13

Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

Software: 29.44

Antenna: 2.4 GHz PIFA (1.6 dBi)


Equipment Operational Modes

Mode	Transmitter Operation
1	ANT (GFSK)
2	BT BLE (GMSK)
3	802.11b
4	802.11g
5	802.11n

Equipment Function

The EUT is a mapping display and interface system providing interface options for use with compatible equipment. The design incorporates transmitter with operation capability in the 2,400-2,483.5 MHz frequency band. The GPS design offers use as a marine mounted mobile configuration for use in navigational aid applications. The transmitter design is provided in two display sizes, 7-inch HVIN: A04266, or 6-inch HVIN: B04266. The transmitter is electrically identical in both versions. Two samples were supplied for testing, one production design and the other modified for testing purposes replacing integral antenna with RF connection port. Both samples were provided with test software enabling testing personnel the ability to test operational functions. The antenna modification offered testing facility ability to connect test equipment directly to the transmitter output. The EUT was arranged in a testing configuration emulating user equipment for testing purposes. The design offers no other interface connections than those in the configuration diagrams shown below. The EUT operates from externally supplied direct current power. The EUT was powered through the manufacturer supplied power cable operating at 12 Vdc from a DC power supply for testing purposes. Test results in this report relate only to the products described in this report.

Equipment Configuration



Application for Certification

- (1) Manufacturer: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062
- (2) Identification: HVIN: A04266, B04266
FCC ID: IPH-04266 IC: 1792A-04266
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from external direct current power provided from marine installation power sources. The EUT provides interface ports for associated marine accessories and power as presented in this filing.
- (9) Transition Provisions of 47 CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards

The following information is submitted in accordance with the eCFR Title 47 Code of Federal Regulations (47CFR), dated August 30, 2022: Part 2, Subpart J, Part 15C Paragraph 15.249, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations as Low Power Transmitter (DXX).

Equipment Testing Procedures

AC Line Conducted Emission Test Procedure

The EUT operates on direct current power only provided by the vehicle installation. Therefore, no AC line conducted emission testing was required or performed.


Radiated Emission Test Procedure

Radiated emissions testing was performed as required in 47 CFR 15C, RSS-210 Issue 10, and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. The frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions during preliminary investigation. Refer to diagrams two and three showing typical test setup. Refer to photographs in the test setup exhibits for specific EUT placement during testing.

Antenna Port Conducted Emission Test Procedure

The EUT was assembled as required for operation placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed presented in the regulations and specified in ANSI C63.10-2013. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram four showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Diagram 1 Test arrangement for radiated emissions of tabletop equipment



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).

1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).

4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)





Diagram 3 Test arrangement for Antenna Port Conducted emissions



Test Site Locations

Conducted EMI	AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Antenna port	Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096	
NVLAP Accreditation	Lab code 200087-0

Units of Measurements

Conducted EMI	Data presented in dB μ V; dB referenced to one microvolt
Antenna port Conducted	Data is in dBm; dB referenced to one milliwatt
Radiated EMI	Data presented in dB μ V/m; dB referenced to one microvolt per meter

Note: Radiated limit may be expressed for measurement in dB μ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters. Sample calculation demonstrates corrected field strength reading for Open Area Test Site using the measurement reading and correcting for receive antenna factor, cable losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

$RFS (dB\mu V/m @ 3m) = FSM (dB\mu V) + A.F. (dB/m) + Losses (dB) - Gain (dB)$

Environmental Conditions

Ambient Temperature	24.8° C
Relative Humidity	41 %
Atmospheric Pressure	1020.6 mb

Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with the 47 CFR Part 15C, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

Intentional Radiators

The following information is submitted supporting demonstration of compliance with the requirements of 47CFR, Subpart C, paragraph 15.249, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5.

Antenna Requirements

The EUT incorporates integral Planer Inverted F Antenna (PIFA) system. Production equipment offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and receiver / spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation.

Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1 ANT (GFSK)

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	44.1	30.8	43.6	30.7	54.0	-23.2	-23.3
2483.5	45.2	31.3	44.1	31.3	54.0	-22.7	-22.7
4804.0	49.2	36.4	49.4	36.4	54.0	-17.6	-17.6
4914.0	49.3	36.5	49.4	36.4	54.0	-17.5	-17.6
4960.0	49.6	36.5	49.3	36.5	54.0	-17.5	-17.5
7206.0	52.8	40.4	53.6	40.4	54.0	-13.6	-13.6
7371.0	53.1	40.2	53.2	40.2	54.0	-13.8	-13.8
7440.0	53.4	40.4	53.6	40.6	54.0	-13.6	-13.4
12010.0	59.2	46.2	59.3	46.2	54.0	-7.8	-7.8
12285.0	60.5	47.4	61.0	47.4	54.0	-6.6	-6.6
12400.0	60.3	47.0	60.1	47.0	54.0	-7.0	-7.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C and RSS-210 Issue 10 Intentional Radiator requirements. The EUT demonstrated a worst-case minimum margin of -6.6 dB below the emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

General Radiated Emissions Procedure

The EUT was arranged in a manufacturer defined equipment configuration and operated with both transmitter active during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Table 2 General Radiated Emissions Data

Frequency (MHz)	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
63.6	40.4	29.7	35.7	28.9	40.0	-10.3	-11.1
111.6	35.7	30.7	37.2	29.5	40.0	-9.3	-10.5
122.2	33.7	27.1	30.1	23.3	40.0	-12.9	-16.7
151.5	39.4	30.4	33.7	26.8	40.0	-9.6	-13.2
155.6	38.3	28.0	28.2	21.7	40.0	-12.0	-18.3
170.1	37.2	31.2	37.8	32.6	40.0	-8.8	-7.4
180.7	35.5	30.3	30.7	24.8	40.0	-9.7	-15.2
199.2	42.4	37.6	35.1	30.0	40.0	-2.4	-10.0
438.5	42.2	40.8	38.5	37.1	47.0	-6.2	-9.9

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C paragraph 15.209, RSS-210 Issue 10, and RSS-GEN Issue 5 Intentional Radiators. The EUT configuration demonstrated a minimum margin of -2.4 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 2400 – 2483.5 MHz

The transmitter output power, harmonic, and general emissions were measured on an Open Area Test Site (OATS) @ 3 meters. The amplitude of radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna (radiated emission testing was performed on sample #1) representative of production equipment with integral antennas. The EUT was placed on a turntable elevated as required above the ground plane and at a distance of 3 meters from the FSM antenna. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. The amplitude of each emission was then recorded from the analyzer display. Emissions radiated outside of the specified bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits, whichever is the lesser attenuation. Antenna port emission plots were taken of transmitter performance for reference in this and other documentation using test sample #4. The amplitude of each radiated emission was maximized by equipment orientation and placement on the turn table, raising and lowering the FSM (Field Strength Measuring) antenna, changing the FSM antenna polarization, and by rotating the turntable. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Emissions were measured in dB μ V/m @ 3 meters.

Refer to figures one through four plots of mode 1 taken of the 2402-2480 MHz transmitter operation displaying compliance with the specifications.

Figure 1 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 1 ANT (GFSK)




Figure 2 Plot of Transmitter Emissions Low Band Edge Mode 1 ANT (GFSK)




Figure 3 Plot of Transmitter Emissions High Band Edge Mode 1 ANT (GFSK)





Figure 4 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 1 ANT (GFSK)



Transmitter Emissions Data

Table 3 Transmitter Radiated Emissions Mode 1 ANT (GFSK)

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	88.8	82.5	93.3	87.6	94.0	-11.5	-6.4
4804.0	49.2	36.4	49.4	36.4	54.0	-17.6	-17.6
7206.0	52.8	40.4	53.6	40.4	54.0	-13.6	-13.6
9608.0	56.7	43.6	56.8	43.7	54.0	-10.4	-10.3
12010.0	59.2	46.2	59.3	46.2	54.0	-7.8	-7.8
14412.0	60.7	47.9	61.5	48.0	54.0	-6.1	-6.0
16814.0	64.6	51.0	65.4	51.0	54.0	-3.0	-3.0
2457.0	91.0	85.9	92.6	87.5	94.0	-8.1	-6.5
4914.0	49.3	36.5	49.4	36.4	54.0	-17.5	-17.6
7371.0	53.1	40.2	53.2	40.2	54.0	-13.8	-13.8
9828.0	57.5	44.3	57.2	44.1	54.0	-9.7	-9.9
12285.0	60.5	47.4	61.0	47.4	54.0	-6.6	-6.6
14742.0	61.9	48.6	61.3	48.5	54.0	-5.4	-5.5
17199.0	64.4	51.0	64.2	51.0	54.0	-3.0	-3.0
2480.0	87.9	82.7	91.4	86.2	94.0	-11.3	-7.8
4960.0	49.6	36.5	49.3	36.5	54.0	-17.5	-17.5
7440.0	53.4	40.4	53.6	40.6	54.0	-13.6	-13.4
9920.0	56.8	43.9	56.7	43.9	54.0	-10.1	-10.1
12400.0	60.3	47.0	60.1	47.0	54.0	-7.0	-7.0
14880.0	61.1	48.1	61.5	48.0	54.0	-5.9	-6.0
17360.0	63.5	50.9	64.4	50.8	54.0	-3.1	-3.2

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15.249, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5 Intentional Radiator regulations. The EUT worst-case test sample configuration demonstrated minimum average margin of -6.4 dB below the average emission limit for the fundamental. The EUT worst-case configuration demonstrated minimum radiated harmonic emission margin of -3.0 dB below the limit. No other radiated emissions were found in the restricted bands less than 20 dB below limits than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the limits.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Rogers Qualifications
- Annex D Laboratory Certificate of Accreditation

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16–4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Test Equipment

Equipment	Manufacturer	Model (SN)	Band	Cal Date(m/d/y)	Due
☐ LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/29/2022	3/29/2023
☐ LISN: Fischer Custom Communications Model:	FCC-LISN-50-16-2-08			3/29/2022	3/29/2023
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	10/14/2021	10/14/2022
☐ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	10/14/2021	10/14/2022
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303070)	9kHz-40 GHz	10/14/2021	10/14/2022
☐ Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/14/2021	10/14/2022
☐ Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/14/2021	10/14/2022
☒ Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/14/2021	10/14/2022
☐ Antenna:	EMCO	6509	.001-30 MHz	10/14/2020	10/14/2022
☐ Antenna	ARA	BCD-235-B (169)	20-350MHz	10/14/2021	10/14/2022
☐ Antenna:	Schwarzbeck Model	VHBB 9124 (1468)	30-200MHz	10/14/2020	10/14/2022
☒ Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/14/2021	10/14/2022
☐ Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	10/14/2020	10/14/2022
☐ Antenna:	Schwarzbeck Model:	VULP 9118 (A-534)	200-1000MHz	10/14/2020	10/14/2022
☒ Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	3/29/2022	3/29/2024
☐ Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/14/2020	10/14/2022
☒ Antenna	Com Power	AH-840 (101046)	18-40 GHz	4/6/2021	4/6/2023
☒ Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	3/9/2022	3/9/2023
☒ Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/18/2022	1/18/2023
☐ Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
☒ Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/14/2021	10/14/2022
☒ Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/14/2021	10/14/2022
☒ Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/14/2021	10/14/2022
☒ Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/14/2021	10/14/2022
☐ Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	3/29/2022	3/29/2023
☐ Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	3/29/2022	3/29/2023
☐ Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/29/2022	3/29/2023
☐ RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	4/6/2021	4/6/2023
☒ RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	4/6/2021	4/6/2023
☐ Attenuator	Fairview	SA6NFN100W-40 (1625)	30-18000 MHz	3/29/2022	3/29/2023
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/29/2022	3/29/2023
☐ Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	3/29/2022	3/29/2023
☒ Weather station	Davis	6312 (A81120N075)		11/4/2021	11/4/2022

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: 47CFR 15C, RSS-Gen RSS-210
File: 04266 DXX TstRpt 220830

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: November 28, 2022
Page 25 of 28

List of Test Equipment

Calibration Date (m/d/y) Due

☐	Antenna:	Schwarzbeck Model VHBB 9124 (01468)	10/14/2020	10/14/2022
☐	Antenna:	Schwarzbeck Model: VULP 9118 A (VULP 9118 A-856)	10/14/2020	10/14/2022
☐	Frequency Counter:	Leader LDC-825 (8060153)	3/29/2022	4/6/2023
☐	ISN: Com-Power Model	ISN T-8	3/29/2022	3/29/2023
☐	LISN	Compliance Design FCC-LISN-2.Mod.cd,(126) .15-30MHz	10/14/2021	10/14/2022
☐	LISN: Com-Power Model	LI-220A	10/14/2020	10/14/2022
☐	LISN: Com-Power Model	LI-550C	10/14/2020	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(1.5M)(303072) 9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(L1M)(281183) 9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(L4M)(281184) 9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Huber & Suhner Inc. Sucoflex102ea(L10M)(317546)9kHz-40 GHz	10/14/2021	10/14/2022
☐	Cable	Time Microwave 4M-750HF290-750 (4M) 9kHz-24 GHz	10/14/2021	10/14/2022
☐	RF Filter	Micro-Tronics BRC17663 (001) 9.3-9.5 notch 30-1800 MHz	4/6/2021	4/6/2023
☐	RF Filter	Micro-Tronics BRC19565 (001) 9.2-9.6 notch 30-1800 MHz	10/14/2021	10/14/2023
☐	Analyzer	HP 8562A (3051A05950) 9kHz-125GHz	3/29/2022	3/29/2023
☐	Wave Form Generator	Keysight 33512B (MY57400128)	3/29/2022	3/29/2023
☐	Antenna:	Solar 9229-1 & 9230-1	2/22/2022	2/22/2023
☐	CDN: Com-Power Model	CDN325E	10/14/2021	10/14/2022
☐	Injection Clamp	Luthi Model EM101	10/14/2021	10/14/2022
☐	Oscilloscope Scope:	Tektronix MDO 4104	2/22/2022	2/22/2023
☐	EMC Transient Generator	HVT TR 3000	2/22/2022	2/22/2023
☐	AC Power Source (Ametech, California Instruments)		2/22/2022	2/22/2023
☐	Field Intensity Meter:	EFM-018	2/22/2022	2/22/2023
☐	ESD Simulator:	MZ-15	2/22/2022	2/22/2023
☐	R.F. Power Amp	ACS 230-50W	not required	
☐	R.F. Power Amp	EIN Model: A301	not required	
☐	R.F. Power Amp	A.R. Model: 10W 1010M7	not required	
☐	R.F. Power Amp	A.R. Model: 50U1000	not required	
☐	Temperature Chamber		not required	
☒	Shielded Room		not required	

Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 35 years' experience in the field of electronics. Working experience includes six years working in the automated controls industry and 6 years working with the design, development and testing of radio communications and electronic equipment.

Positions Held:

Systems Engineer: A/C Controls Mfg. Co., Inc.

Electrical Engineer: Rogers Consulting Labs, Inc.

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background:

Bachelor of Science Degree in Electrical Engineering from Kansas State University

Bachelor of Science Degree in Business Administration Kansas State University

Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming

Annex D Laboratory Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, Inc.
Louisburg, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2022-03-22 through 2023-03-31
Effective Dates




For the National Voluntary Laboratory Accreditation Program

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: 47CFR 15C, RSS-Gen RSS-210
File: 04266 DXX TstRpt 220830

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: November 28, 2022
Page 28 of 28



Antenna Gain Information: A04266/B04266

Equipment Description:

This report contains the antenna gain information for the Wi-Fi /ANT/BLE antenna(s) for Garmin Model AXXXXX. The operational frequency of these technologies is approximately 2400-2480 MHz, and the maximum gain within the frequency band is reported.


Reported Data:

Maximum Gain for Wi-Fi/ BLE/ANT (Antenna 1): **1.58 dBi @ XXXX MHz**

Procedure:

Garmin uses an ETS-Lindgren AMS-8500 3D Fully Anechoic Automated Antenna Measurement System. The measurement chamber is fully anechoic and contains both the Equipment Under Test (EUT) and the measurement antenna. The EUT is mounted on a Multi-Axis Positioner, which can orient the antenna in all orientations relative to the measurement antenna. The measurement antenna is dual-polarized and measures both horizontal and vertical polarization simultaneously. The other equipment includes a Vector Signal Generator, a multi-channel Vector Network Analyzer, and a control PC. Data is taken and analyzed using EMQuest Data Acquisition and Analysis Software. The output includes the maximum 3D antenna gain within the frequency band.

Setup:



Equipment List:

3D Chamber PC interfaced to Test Equipment
EMQuest Software w/ Required Drivers for Equipment Installed
AMS-8500 Anechoic Wireless Test Chamber
Dual Polarization Measurement Antenna (ETS 3164)
Multi-Axis Positioning System (MAPS)
Multi-Axis Positioning Controller (ETS EMCO Model 2090)
Network Analyzer (Agilent E5017C)
Automated RF Switch Controller (Agilent)

Additional Information:

- Photos of the antenna are provided in a separate exhibit: A04266 B04266 Internal Photos
- The Photos include a scale for dimensions

Signature:

Jeffrey Hailey
Staff Compliance Engineer
Garmin International.

		HVIN: A04266, B04266		Test Number: 220830			
MPE Calculator		RF Exposure uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi. dBi = dB gain compared to an isotropic radiator. S = power density in mW/cm²2					
		Transmitter Output power (mW)		17.7			
		Transmitter Output power (W)		0.018			
Output Power for % duty Cycle operation (Watts)		100		0.018		Antenna Gain (dBi) 1.6	
Output Power for 100% duty Cycle operation (Watts)				0.018		Antenna Gain (Numeric) 1.45	
Tx Frequency (MHz)		2437		Calculation power (Watts) 0.018		dBd + 2.17 = dBi dBi to dBd 2.17	
						Antenna Gain (dBd) -0.57	
Cable Loss (dB)		0.0		Adjusted Power (dBm) 12.48		Antenna minus cable (dBi) 1.60	
						Antenna Gain (Numeric) 1.45	
		Calculated ERP (mw) 15.524				EIRP = Po(dBm) + Gain (dB)	
		Calculated EIRP (mw) 25.586				Radiated (EIRP) dBm 14.080	
						ERP = EIRP - 2.17 dB	
						Radiated (ERP) dBm 11.910	
		Power density (S) mW/cm² = $\frac{\text{EIRP}}{4 \pi r^2}$ r (cm) EIRP (mW)					

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
HVIN's: A04266, B04266
Test: 220830
Test to: CFR47 15C, RSS-210, RSS-247
File: 04266 RFExp

SN's: 3425814614, 3425814607
FCC ID: IPH-04266
IC: 1792A-04266
Date: September 20, 2022
Page 1 of 1