



FCC PART 15C REPORT FOR CERTIFICATION On Behalf of

BYD Auto Industry Company Limited

Central Computing Platform

Model Number: MTED01

FCC ID: SD4-MTED01

Applicant:	BYD Auto Industry Company Limited
Address:	No.3001, 3007, Hengping Road, Pingshan, Shenzhen, Guangdong, P.R.China
Prepared By:	EST Technology Co., Ltd. Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R2512202
Date of Test:	Nov. 11, 2025~ Dec. 15, 2025
Date of Report:	Dec. 31, 2025

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
1.2. Antenna Information.....	5
1.3. Information of RF Cable.....	5
2. SUMMARY OF TEST.....	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Measurement uncertainty.....	8
2.4. Assistant equipment used for test.....	8
2.5. Block Diagram.....	8
2.6. Test Mode.....	9
2.7. Power Setting of Test Software.....	11
2.8. Duty Cycle.....	11
2.9. Channel List.....	12
2.10. Test Equipment List.....	13
3. 6DB BANDWIDTH.....	15
3.1. Limit.....	15
3.2. Test Setup.....	15
3.3. Spectrum Analyzer Setting.....	15
3.4. Test Procedure.....	15
3.5. Test Result.....	15
4. MAXIMUM PEAK OUTPUT POWER.....	16
4.1. Limit.....	16
4.2. Test Setup.....	16
4.3. Spectrum Analyzer Setting.....	16
4.4. Test Procedure.....	16
4.5. Test Result.....	16
5. POWER SPECTRAL DENSITY.....	17
5.1. Limit.....	17
5.2. Test Setup.....	17
5.3. Spectrum Analyzer Setting.....	17
5.4. Test Procedure.....	17
5.5. Test Result.....	17
6. CONDUCTED BAND EDGE.....	18
6.1. Limit.....	18
6.2. Test Setup.....	18
6.3. Spectrum Analyzer Setting.....	18
6.4. Test Procedure.....	18
6.5. Test Result.....	18
7. CONDUCTED SPURIOUS EMISSIONS.....	19
7.1. Limit.....	19



7.2. Test Setup.....	19
7.3. Spectrum Analyzer Setting.....	19
7.4. Test Procedure.....	19
7.5. Test Result.....	19
8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE	20
8.1. Limit.....	20
8.2. Test Setup.....	21
8.3. Spectrum Analyzer Setting.....	22
8.4. Test Procedure.....	23
8.5. Test Result.....	24
9. ANTENNA REQUIREMENTS.....	36
9.1. Limit.....	36
9.2. Test Result.....	36
10. TEST SETUP PHOTO	37
11. EUT PHOTO	39

Applicant: BYD Auto Industry Company Limited
Address: No.3001, 3007, Hengping Road, Pingshan, Shenzhen, Guangdong, P.R.China

Manufacturer: BYD Auto Industry Company Limited
Address: No.3001, 3007, Hengping Road, Pingshan, Shenzhen, Guangdong, P.R.China

E.U.T: Central Computing Platform

Model Number: MTED01

Power Supply: DC 12V From Battery

Trade Name: BYD **Sample No.:** EST-250411014-002

Date of Receipt: Nov. 11, 2025 **Date of Test:** Nov. 11, 2025~
 Dec. 15, 2025

Test Specification: FCC Part 15 Subpart C (15.247)
 ANSI C63.10:2020
 FCC KDB 558074 D01 15.247 Meas Guidance v05r02

Test Result: The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.

Date: Jan. 12, 2026

Prepared by:

Reviewed by:

Approved by:

Ring Yang / Assistant

Seven Wang / Engineer

Iceman Hu / Manager



Other Aspects:
 None.

Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd. The statement of compliance in this report is based on the limit in the test standard, the measurement uncertainty is not considered.

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	Central Computing Platform
Model Number	:	MTED01
Software Version	:	N/A
Hardware Version	:	HW0.0.5
Operation frequency	:	IEEE 802.11b/g/n/ax/be HT20:2412MHz~2462MHz
Number of channel	:	IEEE 802.11b/g/n/ax/be HT20: 11 Channels
Max Output Power (PEAK)	:	IEEE 802.11b: 16.51dBm IEEE 802.11g: 18.89dBm IEEE 802.11n HT20: 18.70dBm IEEE 802.11ax HE20: 20.09dBm IEEE 802.11be EHT20: 20.00dBm
Modulation Type	:	DSSS OFDM OFDMA
Sample Type	:	Prototype production
Note: The product information is provided by the manufacturer. The laboratory is not responsible for this data.		

1.2. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	External	-	2.93
Note: 1.The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain. 2.The test results of this report only apply to the sample as received.					

1.3. Information of RF Cable

Cable Loss(dB)	Provided by
1.0	BYD Auto Industry Company Limited
Note: 1.The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received. 2.The laboratory is not responsible for the accuracy of the cable loss.	

2.SUMMARY OF TEST

2.1.Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	6dB Bandwidth	15.247(a)(2)	PASS
2	Maximum Peak Output Power	15.247(b)(3)	PASS
3	Power Spectral Density	15.247(e)	PASS
4	Conducted Band Edge	15.247(d)	PASS
5	Conducted Spurious Emissions	15.247(d)	PASS
6	Radiated Spurious Emissions and Band Edge	15.205 15.209 15.247(d)	PASS
7	AC Power Line Conducted Emissions	15.207	PASS
8	Antenna Requirement	15.203	PASS

Note:“N/A” denotes test is not applicable in this test report.

2.2. Test Facilities

EMC Lab : Accredited by CNAS, CHINA
Registration No.: L5288
This Accreditation is valid until: November 12, 2029

Recognized by FCC, USA
Designation Number: CN1215
This Recognition is valid until: January 31, 2026

Accredited by A2LA, USA
Registration No.: 4366.01
This Accreditation is valid until: January 31, 2026

Recognized by Industry Canada
CAB identifier No.: CN0035
This Recognition is valid until: January 31, 2026

Recognized by VCCI, Japan
Registration No.: C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2020
This Recognition is valid until: Apr. 19, 2026

Recognized by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Recognized by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
Guangdong, China

2.3.Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	0.26dB
Uncertainty for spurious emissions test (30MHz-1GHz)	±4.76dB
Uncertainty for spurious emissions test (1GHz to 25GHz)	±5.32dB
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


2.4.Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	2.0m	DC Line

2.5.Block Diagram

For radiated emissions test: EUT was placed on a turntable, which is 0.8 (or 1.5) meter high above ground. The EUT was set into 2.4G Wi-Fi test mode by software prior to testing.



(EUT: Central Computing Platform)

2.6. Test Mode

The test mode was selected for the final test as listed below.

Test Item	Mode	Date Rate	Test Channel
6dB Bandwidth	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Maximum Peak Output Power	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Power Spectral Density	IEEE 802.11b	MCS0	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Conducted Band Edge	IEEE 802.11b	1Mbps	Low/ High
	IEEE 802.11g	6Mbps	Low/ High
	IEEE 802.11n HT20	MCS0	Low/ High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Conducted Spurious Emissions	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Radiated Spurious Emissions(Below 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Radiated Spurious Emissions(Above 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High
Radiated Band Edge	IEEE 802.11b	1Mbps	Low/High
	IEEE 802.11g	6Mbps	Low/High
	IEEE 802.11n HT20	MCS0	Low/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High

AC Power Line Conducted Emissions	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11ax HE20	MCS0	Low/Middle/High
	IEEE 802.11be EHT20	MCS0	Low/Middle/High

Note: In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7. Power Setting of Test Software

Software Name	AP META TOOL		
Frequency(MHz)	2412	2437	2462
IEEE 802.11b Setting	18	18	18
IEEE 802.11g Setting	15	15	15
IEEE 802.11n HT20 Setting	15	15	15
IEEE 802.11ax HE20 Setting	15	15	15
IEEE 802.11be EHT20 Setting	15	15	15

Note: This information is provided by the applicant.

2.8. Duty Cycle

Refer to Appendix H of Appendix FCC ID 2.4G Wi-Fi (the test data).

Note:

1. If duty cycle $< 98\%$, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle $\geq 98\%$, the EUT is consider to be transmitting continuously, the conducted average output power and average power spectral density no need to add duty factor (consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. The on-time time is transmission duration(T).

2.9.Channel List

IEEE 802.11b/802.11g/802.11n HT20/802.11ax HE20/802.11be EHT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442		
3	2422	8	2447		
4	2427	9	2452		
5	2432	10	2457		

2.10. Test Equipment List

For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESRP3	EST-E070	LISAI	June 11,25	June 10,26
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E048	LISAI	June 11,25	June 10,26
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emission test(9kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 11,25	June 10,26
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	EST-E054	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 11,25	June 10,26
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA9120D	EST-E144	LISAI	June 11,25	June 10,26
Horn Antenna	Com-Power	AHA-840	EST-E133	LISAI	June 11,25	June 10,26
Low Noise Amplifier	RF	TRLA-010180 G45N	EST-E142	LISAI	June 11,25	June 10,26
Spectrum Analyzer	Rohde & Schwarz	FSV40	EST-E069	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

For connect EUT antenna terminal test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
TS 1120	Tonscend	/	/	/	/	/
Test Software	Tonscend	JS1120-3	3.5.39	/	/	/
RF Control Unit	Tonscend	JS0806-2	EST-E134	LISAI	June 11,25	June 10,26
Signal and Spectrum Analyzer	Keysight	N9010B	EST-E141	LISAI	June 11,25	June 10,26

3.6DB BANDWIDTH

3.1.Limit

Systems using digital modulation techniques operate in the 2400-2483.5 MHz,the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2.Test Setup



3.3.Spectrum Analyzer Setting

6dB Bandwidth

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode)/ 80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth

Spectrum Parameters	Setting
RBW	300KHz(20MHz Bandwidth mode)/ 1MHz(40MHz Bandwidth mode)
VBW	1MHz(20MHz Bandwidth mode)/3MHz(40MHz Bandwidth mode)
Span	40MHz(20MHz Bandwidth mode)/ 80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4.Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 3.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

3.5.Test Result

Refer to Appendix A of Appendix FCC ID 2.4G Wi-Fi (the test data).

4. MAXIMUM PEAK OUTPUT POWER

4.1. Limit

For systems using digital modulation in 2400-2483.5MHz, the maximum peak output power is 1 Watt(30dBm).

4.2. Test Setup



4.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

4.4. Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 4.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

4.5. Test Result

Refer to Appendix B of Appendix FCC ID 2.4G Wi-Fi (the test data).

5. POWER SPECTRAL DENSITY

5.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	3KHz
VBW	10KHz
Span	30MHz(20MHz Bandwidth mode)/60MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

5.4. Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 5.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

5.5. Test Result


Refer to Appendix C of Appendix FCC ID 2.4G Wi-Fi (the test data).

6. CONDUCTED BAND EDGE

6.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2. Test Setup



6.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	100MHz(20MHz Bandwidth mode)/ 200MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.4. Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 6.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report

6.5. Test Result


Refer to Appendix D & E of Appendix FCC ID 2.4G Wi-Fi (the test data).

7. CONDUCTED SPURIOUS EMISSIONS

7.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.2. Test Setup



7.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	26.5GHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

7.4. Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 7.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

7.5. Test Result

Refer to Appendix D & F of Appendix FCC ID 2.4G Wi-Fi (the test data).

8.RADIATED SPURIOUS EMISSIONS AND BAND EDGE

8.1.Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


Frequency (MHz)	Field Strength($\mu\text{V}/\text{m}$)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:


- (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$.
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Test Setup


9kHz~30MHz



30~1000MHz



Above 1GHz



8.3.Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting
RBW	1MHz
VBW	PEAK Measurement
	AVG Measurement
	3MHz
	Duty cycle \geq 98%,VBW=10Hz
	Duty cycle $<$ 98%,VBW \geq 1/T
Start frequency	1GHz
Stop frequency	25GHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

Note :T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

8.4. Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 8.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

Note:

1. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2412MHz/2422MHz/2437MHz/2452MHz/2462MHz are fundamental frequency, which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.
3. IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ax HE20, IEEE 802.11be EHT20 all have been tested, only worst case 802.11be EHT20 is recorded.


8.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 61 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01-30-1000.EM6 (66) Date: 2025-12-02



Site no. : 5# 966 Chamber Data no. : 61
 Dis. / Ant. : 3m 54681 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C(3M)
 Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
 Engineer : Aron
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : TX Mode
 Sample No : EST-250411014-002


	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	53.28	8.20	1.25	11.40	20.85	40.00	19.15	QP
2	64.92	6.00	1.37	10.38	17.75	40.00	22.25	QP
3	605.21	19.55	4.50	2.07	26.12	46.00	19.88	QP
4	791.45	21.98	5.22	1.61	28.81	46.00	17.19	QP
5	862.26	22.77	5.46	1.70	29.93	46.00	16.07	QP
6	932.10	23.18	5.70	1.99	30.87	46.00	15.13	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 62 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01-30-1000.EM6 (66) Date: 2025-12-02



Site no. : 5# 966 Chamber Data no. : 62
 Dis. / Ant. : 3m 54681 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C(3M)
 Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
 Engineer : Aron
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : TX Mode
 Sample No : EST-250411014-002

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	588.72	19.14	4.43	2.27	25.84	46.00	20.16	QP
2	642.07	20.22	4.64	2.21	27.07	46.00	18.93	QP
3	713.85	20.54	4.92	2.50	27.96	46.00	18.04	QP
4	778.84	21.86	5.17	1.75	28.78	46.00	17.22	QP
5	859.35	22.80	5.45	1.76	30.01	46.00	15.99	QP
6	913.67	22.89	5.64	1.75	30.28	46.00	15.72	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:


1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.

Radiated Emissions Above 1G

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 107 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144) Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 107
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2412MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5488.00	33.53	5.63	43.30	45.60	41.46	74.00	32.54	Peak
2	7239.00	36.80	6.71	43.35	44.02	44.18	74.00	29.82	Peak
3	8650.00	38.25	7.02	43.07	42.78	44.98	74.00	29.02	Peak
4	9823.00	39.72	7.93	42.75	42.03	46.93	74.00	27.07	Peak
5	12254.00	40.15	9.05	40.62	39.88	48.46	74.00	25.54	Peak
6	14005.00	42.10	10.22	39.90	37.56	49.98	74.00	24.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 108

File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144)

Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 108
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2412MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4791.00	31.87	5.28	43.24	49.09	43.00	74.00	31.00	Peak
2	7443.00	36.85	6.77	43.31	42.99	43.30	74.00	30.70	Peak
3	9687.00	40.25	7.78	42.79	41.06	46.30	74.00	27.70	Peak
4	11982.00	40.09	8.92	41.02	39.44	47.43	74.00	26.57	Peak
5	13614.00	41.40	9.91	39.74	38.40	49.97	74.00	24.03	Peak
6	15314.00	39.28	11.22	42.36	40.04	48.18	74.00	25.82	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 109

File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144)

Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 109
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2437MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5182.00	32.58	5.48	43.24	45.41	40.23	74.00	33.77	Peak
2	7273.00	36.50	6.72	43.35	44.52	44.39	74.00	29.61	Peak
3	8718.00	38.73	7.03	43.06	41.82	44.52	74.00	29.48	Peak
4	9687.00	40.25	7.78	42.79	41.64	46.88	74.00	27.12	Peak
5	11727.00	39.91	8.88	41.27	39.00	46.52	74.00	27.48	Peak
6	13971.00	42.04	10.19	39.89	36.93	49.27	74.00	24.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 110

File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144)

Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 110
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2437MHz
 Sample No : EST-250411014-002


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5199.00	32.60	5.49	43.24	45.64	40.49	74.00	33.51	Peak
2	6661.00	35.43	6.38	43.40	44.85	43.26	74.00	30.74	Peak
3	8021.00	38.10	6.94	43.20	42.97	44.81	74.00	29.19	Peak
4	9993.00	39.60	8.11	42.70	41.84	46.85	74.00	27.15	Peak
5	11863.00	40.01	8.90	41.14	39.95	47.72	74.00	26.28	Peak
6	14056.00	41.97	10.26	40.02	37.35	49.56	74.00	24.44	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 111 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144)



Date: 2025-11-27

Site no. : 5# 966 Chamber Data no. : 111
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2462MHz
 Sample No : EST-250411014-002


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5148.00	32.55	5.46	43.23	46.16	40.94	74.00	33.06	Peak
2	7239.00	36.80	6.71	43.35	43.33	43.49	74.00	30.51	Peak
3	9279.00	38.92	7.35	42.92	42.03	45.38	74.00	28.62	Peak
4	10945.00	39.41	8.74	42.04	41.19	47.30	74.00	26.70	Peak
5	12373.00	40.17	9.11	40.44	38.34	47.18	74.00	26.82	Peak
6	13954.00	42.01	10.18	39.88	37.29	49.60	74.00	24.40	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: **112** File: \\EMC-966-5\Test Data2\2025\RF\B\Bi Ya Di\MTED01.EM6 (144) Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 112
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2462MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4264.00	30.93	5.00	43.35	54.69	47.27	74.00	26.73	Peak
2	6848.00	35.45	6.52	43.40	44.59	43.16	74.00	30.84	Peak
3	8888.00	38.90	7.05	43.02	41.69	44.62	74.00	29.38	Peak
4	10843.00	39.43	8.67	42.11	41.29	47.28	74.00	26.72	Peak
5	12407.00	40.18	9.13	40.39	38.82	47.74	74.00	26.26	Peak
6	13563.00	41.31	9.87	39.72	37.38	48.84	74.00	25.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


Note:

- The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Radiated Band Edge

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 5# 966 Chamber Data no. : 103
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2412MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.60	3.49	44.13	56.26	43.22	54.00	10.78	Average
2	2390.00	27.60	3.49	44.13	65.60	52.56	74.00	21.44	Peak
3	2404.65	27.67	3.51	44.11	110.31	97.38	74.00	-23.38	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 104 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144)

Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 104
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2412MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.60	3.49	44.13	58.41	45.37	74.00	28.63	Peak
2	2408.94	27.67	3.51	44.11	104.92	91.99	74.00	-17.99	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 105 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144)

Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 105
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2462MHz
 Sample No : EST-250411014-002


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2459.66	27.87	3.55	44.05	109.51	96.88	74.00	-22.88	Peak
2	2483.50	27.93	3.57	44.03	55.26	42.73	54.00	11.27	Average
3	2483.50	27.93	3.57	44.03	64.97	52.44	74.00	21.56	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 106 File: \\EMC-966-5\Test Data2\2025\RF\Bibi Ya Di\MTED01.EM6 (144) Date: 2025-11-27



Site no. : 5# 966 Chamber Data no. : 106
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.3°C;Humi:48%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Central Computing Platform
 Power : DC 12V From Battery
 M/N : MTED01
 Test Mode : IEEE 802.11be EHT20 TX 2462MHz
 Sample No : EST-250411014-002

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2460.92	27.87	3.55	44.05	105.91	93.28	74.00	-19.28	Peak
2	2483.50	27.93	3.57	44.03	58.23	45.70	74.00	28.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. All channels had been pre-test, only of the worst case channels were reported.

9. ANTENNA REQUIREMENTS

9.1. Limit


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2. Test Result

The antennas used for this product is Internal antenna, so compliance with antenna requirements. (Please refer to the EUT photo for details)

10. TEST SETUP PHOTO

Radiated Test (Below 1GHz)



Radiated Test (Above 1GHz)



Radio Spectrum Testing



11.EUT PHOTO

Refer to report no. ESTE-R2512200

End of Test Report





Appendix A: DTS Bandwidth


Test Result

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.040	2408.000	2416.040	0.5	PASS
11B	Ant1	2437	8.040	2433.000	2441.040	0.5	PASS
11B	Ant1	2462	7.520	2458.000	2465.520	0.5	PASS
11G	Ant1	2412	15.600	2404.200	2419.800	0.5	PASS
11G	Ant1	2437	16.280	2428.880	2445.160	0.5	PASS
11G	Ant1	2462	15.760	2454.160	2469.920	0.5	PASS
11N20SISO	Ant1	2412	15.680	2404.480	2420.160	0.5	PASS
11N20SISO	Ant1	2437	16.760	2428.640	2445.400	0.5	PASS
11N20SISO	Ant1	2462	15.160	2454.440	2469.600	0.5	PASS
11AX20SISO	Ant1	2412	16.920	2403.880	2420.800	0.5	PASS
11AX20SISO	Ant1	2437	18.040	2428.000	2446.040	0.5	PASS
11AX20SISO	Ant1	2462	17.320	2453.160	2470.480	0.5	PASS
11BE20SISO	Ant1	2412	17.560	2403.520	2421.080	0.5	PASS
11BE20SISO	Ant1	2437	17.840	2427.960	2445.800	0.5	PASS
11BE20SISO	Ant1	2462	16.960	2452.840	2469.800	0.5	PASS

Test Graphs



11B-Ant1-2462-PASS





11G-Ant1-2462-PASS



11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2437-PASS




11N20SISO-Ant1-2462-PASS



11AX20SISO-Ant1-2412-PASS



11AX20SISO-Ant1-2437-PASS




11AX20SISO-Ant1-2462-PASS



11BE20SISO-Ant1-2412-PASS



11BE20SISO-Ant1-2437-PASS



11BE20SISO-Ant1-2462-PASS





Appendix B: Maximum conducted output power


Test Result Peak

TestMode	Antenna	Frequency[MHz]	Peak Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	16.51	≤30.00	PASS
11B	Ant1	2437	16.39	≤30.00	PASS
11B	Ant1	2462	16.38	≤30.00	PASS
11G	Ant1	2412	18.63	≤30.00	PASS
11G	Ant1	2437	18.89	≤30.00	PASS
11G	Ant1	2462	18.77	≤30.00	PASS
11N20SISO	Ant1	2412	18.24	≤30.00	PASS
11N20SISO	Ant1	2437	18.70	≤30.00	PASS
11N20SISO	Ant1	2462	18.26	≤30.00	PASS
11AX20SISO	Ant1	2412	19.88	≤30.00	PASS
11AX20SISO	Ant1	2437	20.09	≤30.00	PASS
11AX20SISO	Ant1	2462	19.65	≤30.00	PASS
11BE20SISO	Ant1	2412	19.67	≤30.00	PASS
11BE20SISO	Ant1	2437	20.00	≤30.00	PASS
11BE20SISO	Ant1	2462	19.66	≤30.00	PASS


Test Graphs Peak



11B-Ant1-2462-PASS




11G-Ant1-2412-PASS



11G-Ant1-2437-PASS




11G-Ant1-2462-PASS




11N20SISO-Ant1-2412-PASS




11N20SISO-Ant1-2437-PASS




11N20SISO-Ant1-2462-PASS



11AX20SISO-Ant1-2412-PASS




11AX20SISO-Ant1-2437-PASS




11AX20SISO-Ant1-2462-PASS



11BE20SISO-Ant1-2412-PASS



11BE20SISO-Ant1-2437-PASS



11BE20SISO-Ant1-2462-PASS

