

# Emissions Test Report

**EUT Name:** Vibration Meter

**Model No.:** 805FC

CFR 47 Part 15.247:2013 and RSS 210:2010

*Prepared for:*

Graham Don T  
Fluke Corporation.  
6920 Seaway Blvd.  
Everett, WA 98203 U.S.A.  
Tel: (425) 446-5928

*Prepared by:*

TUV Rheinland of North America, Inc.  
1279 Quarry Lane, Ste. A  
Pleasanton, CA 94566 U.S.A.  
Tel: (925) 249-9123  
Fax: (925) 249-9124  
<http://www.tuv.com/>

*Report/Issue Date:* February 19, 2015  
*Report Number:* 31460300.001  
*Project Number:* 0000125067  
*Revision Number:* 0

## Revisions

| Revision No. | Date MM/DD/YYYY | Reason for Change | Author |
|--------------|-----------------|-------------------|--------|
| 0            | 02/19/2015      | Original Document | N/A    |
|              |                 |                   |        |
|              |                 |                   |        |
|              |                 |                   |        |
|              |                 |                   |        |
|              |                 |                   |        |
|              |                 |                   |        |

# Statement of Compliance

*Manufacturer:* Fluke Corporation.  
6920 Seaway Blvd.  
Everett, WA 98203 U.S.A.  
(425) 446-5928

*Requester / Applicant:* Graham Don T

*Name of Equipment:* Vibration Meter

*Model No.* 805FC

*Type of Equipment:* Intentional Radiator

*Application of Regulations:* CFR 47 Part 15.247:2013 and RSS 210:2010

*Test Dates:* Oct 30 – Nov 7, 2014

*Guidance Document:*

Emissions: ANSI C63.10:2009; ANSI C63.10:2013

*Test Methods:*


Emissions: ANSI C63.10:2009; ANSI C63.10:2013

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA. This report contains data that are not covered by A2LA accreditation. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.



Suresh Kondapalli      February 19, 2015  
Test Engineer      Date



Conan Boyle      February 23, 2015  
Laboratory Signatory      Date



**Testing Certificate**  
**#3331.02**



**US5254**

**INDUSTRY**  
**CANADA**

**2932M-1**

|          |                                                            |           |
|----------|------------------------------------------------------------|-----------|
| <b>1</b> | <b>Executive Summary</b>                                   | <b>7</b>  |
| 1.1      | Scope                                                      | 7         |
| 1.2      | Purpose                                                    | 7         |
|          | Summary of Test Results                                    | 7         |
| 1.3      | Special Accessories                                        | 8         |
| 1.4      | Equipment Modifications                                    | 8         |
| <b>2</b> | <b>Laboratory Information</b>                              | <b>9</b>  |
| 2.1      | Accreditations & Endorsements                              | 9         |
| 2.1.1    | US Federal Communications Commission                       | 9         |
| 2.1.2    | NIST / A2LA                                                | 9         |
| 2.1.3    | Canada – Industry Canada                                   | 9         |
| 2.1.4    | Japan – VCCI                                               | 9         |
| 2.1.5    | Acceptance by Mutual Recognition Arrangement               | 10        |
| 2.2      | Test Facilities                                            | 10        |
| 2.2.1    | Emission Test Facility                                     | 10        |
| 2.2.2    | Immunity Test Facility                                     | 10        |
| 2.3      | Measurement Uncertainty                                    | 11        |
| 2.3.1    | Sample Calculation – radiated & conducted emissions        | 11        |
| 2.3.2    | Measurement Uncertainty                                    | 11        |
| 2.4      | Calibration Traceability                                   | 12        |
| <b>3</b> | <b>Product Information</b>                                 | <b>13</b> |
| 3.1      | Product Description                                        | 13        |
| 3.2      | Equipment Configuration                                    | 13        |
| 3.3      | Operating Mode                                             | 13        |
| 3.4      | Duty Cycle:                                                | 13        |
| 3.5      | Unique Antenna Connector                                   | 14        |
| 3.5.1    | Results                                                    | 14        |
| <b>4</b> | <b>Emission Requirements – 2400 MHz to 2483.5 MHz Band</b> | <b>15</b> |
| 4.1      | Output Power Requirements                                  | 15        |
| 4.1.1    | Test Method                                                | 15        |
| 4.1.2    | Results                                                    | 16        |
| 4.2      | Occupied Bandwidth                                         | 20        |
| 4.2.1    | Test Method                                                | 20        |
| 4.2.2    | Results                                                    | 21        |
| 4.3      | Hopping Frequency Requirements                             | 25        |
| 4.3.1    | Results                                                    | 25        |
| 4.4      | Out of Band Emission requirements                          | 34        |
| 4.4.1    | Results                                                    | 34        |
| 4.5      | Maximum RF Exposure                                        | 42        |

## Index of Tables

|            |                                                          |           |
|------------|----------------------------------------------------------|-----------|
| 4.5.1      | Test Methodology                                         | 42        |
| 4.5.2      | FCC KDB 447498 D01 – General SAR Test Exclusion Guidance | 42        |
| 4.5.3      | EUT Operating Condition                                  | 43        |
| 4.5.4      | Classification                                           | 43        |
| 4.5.5      | SAR Test Exclusion Threshold                             | 43        |
| <b>4.6</b> | <b>Transmitter Spurious Emissions</b>                    | <b>44</b> |
| 4.6.1      | Test Methodology                                         | 44        |
| 4.6.2      | Transmitter Spurious Emission Limit                      | 45        |
| 4.6.3      | Test Results                                             | 45        |
| 4.6.4      | Sample Calculation                                       | 61        |
| <b>4.7</b> | <b>AC Conducted Emissions</b>                            | <b>62</b> |
| 4.7.1      | Test Methodology                                         | 62        |
| 4.7.2      | Deviations                                               | 62        |
| 4.7.3      | Test Results                                             | 62        |
| <b>5</b>   | <b>Test Equipment Use List</b>                           | <b>63</b> |
| 5.1        | Equipment List                                           | 63        |
| <b>6</b>   | <b>EMC Test Plan</b>                                     | <b>64</b> |
| 6.1        | Introduction                                             | 64        |
| 6.2        | Customer                                                 | 64        |
| 6.3        | Product Specification                                    | 65        |
| 6.4        | Configuration (s)                                        | 66        |
| 6.5        | Test Specifications                                      | 67        |

## Index of Tables

|                                                                                       |    |
|---------------------------------------------------------------------------------------|----|
| <b>Table 1:</b> Summary of Test Results.....                                          | 7  |
| <b>Table 2:</b> RF Output Power at the Antenna Port – Test Results.....               | 16 |
| <b>Table 3:</b> Occupied Bandwidth – Test Results .....                               | 21 |
| <b>Table 4:</b> Frequency Hopping Requirements .....                                  | 25 |
| <b>Table 5:</b> Band Edge Requirements – Test Results .....                           | 34 |
| <b>Table 6:</b> Transmit Spurious Emission at Restricted Band Edge Requirements ..... | 46 |
| <b>Table 7:</b> Customer Information.....                                             | 64 |
| <b>Table 8:</b> Technical Contact Information .....                                   | 64 |
| <b>Table 9:</b> EUT Specifications .....                                              | 65 |
| Table 10: Description of Sample used for Testing.....                                 | 66 |
| Table 11: Description of Test Configuration used for Radiated Measurement. ....       | 67 |
| <b>Table 12:</b> Test Specifications .....                                            | 67 |

# 1 Executive Summary

## 1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.247:2013 and RSS 210:2010 based on the results of testing performed from Oct 30 to Nov 7, 2014 on the Vibration Meter Model 805FC manufactured by Fluke Corporation. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

## 1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

## Summary of Test Results

**Table 1:** Summary of Test Results

| Test                                  | Test Method<br>ANSI C63.4              | Test<br>Parameters | Measured Value                            | Result          |
|---------------------------------------|----------------------------------------|--------------------|-------------------------------------------|-----------------|
| <b>2400 MHz to 2483.5 MHz Band</b>    |                                        |                    |                                           |                 |
| Spurious Emission in Transmitted Mode | CFR47 15.209, RSS-GEN Sect.7.2.3       | Class B            | 47.49dBuV/m at 4883.41MHz Margin - 6.22dB | <b>Complied</b> |
| Restricted Bands of Operation         | CFR47 15.205, RSS-210 Sect.2.6         | Class B            |                                           | <b>Complied</b> |
| AC Power Conducted Emission           | CFR47 15.207, RSS-GEN Sect.7.2.2       | N/A                | Na.                                       | <b>N/A</b>      |
| Occupied Bandwidth                    | CFR 47 15.247(a1), RSS Gen Sect. 4.4.1 | N/A                | 1210kHz (20dB BW)<br>1108kHz (99% BW)     | <b>Complied</b> |
| Channel Separation                    | CFR47 15.247 (a1), RSS-210 Sect. A.8.1 | >25 kHz            | 1968.6 KHz                                | <b>Complied</b> |
| Number of Hopping Channels            | CFR47 15.247 (a1), RSS-210 Sect. A.8.1 | >15                | 40 Channels                               | <b>Complied</b> |
| Average time occupancy of Channel     | CFR47 15.247 (a1), RSS-210 Sect. A.8.1 | < 0.4 sec          | 25.12mS                                   | <b>Complied</b> |
| Maximum Transmitted Power             | CFR47 15.247 (b1), RSS-210 Sect. A.8.1 | <125 mWatts        | 0.60mW                                    | <b>Complied</b> |
| Out of Band Emission                  | CFR47 15.247 (d), RSS-210 Sect. A.8.5  | < -20 dBr          | See plots 13-16                           | <b>Complied</b> |

Note: Since EUT is portable device where the end user will have the direct contact as handheld device, RF Exposure/SAR requirements are calculated for human extremity parts, and EUT met FCC KDB 447498 SAR exclusion. See Section 4.5 of this report

### **1.3 Special Accessories**

No special accessories were necessary in order to achieve compliance.

### **1.4 Equipment Modifications**

None

## 2 Laboratory Information

### 2.1 Accreditations & Endorsements

#### 2.1.1 US Federal Communications Commission



TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 is recognized by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (US5254). The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, and 90. The accreditation is updated every 3 years.

#### 2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:2005 and ISO 9002 (Lab Code Testing Certificate #3331.02). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

#### 2.1.3 Canada – Industry Canada



TUV Rheinland of North America at the 1279 Quarry Ln, Pleasanton, CA 94566 address is accredited by Industry Canada for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by Industry Canada (File Number 2932M). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

#### 2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0031

VCCI Registration No. for Santa Clara: A-0032

### 2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member country.

## 2.2 Test Facilities

All of the test facilities are located at 1279 Quarry Lane, Pleasanton, California 94566, USA. The 2305 Mission College, Santa Clara, 95054, USA location is considered a Pleasanton annex.

### 2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2009, at a test distance of 3 and 5 meters. The site is listed with the FCC and accredited by A2LA (Lab Code Testing Certificate #3331.02). The 3/5-meter semi-anechoic chamber used to collect the radiated data has been verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2009, at a test distance of 3 meter and 5 meters. A report detailing this site can be obtained from TUV Rheinland of North America.

### 2.2.2 Immunity Test Facility

ESD, EFT, Surge, PQF: These tests are performed in an environmentally controlled room with a 3.7 m x 4.8 m x 3.175 mm thick aluminum floor connected to PE ground.

For ESD testing, tabletop equipment is placed on an insulated mat with a surface resistivity of  $10^9$  Ohms/square on a 1.6 m x 0.8 m x 0.8 m high non-conductive table with a 3.175 mm aluminum top (Horizontal Coupling Plane). The HCP is connected to the main ground plane via a low impedance ground strap through two 470-k $\Omega$  resistors. The Vertical Coupling Plane consists of an aluminum plate 50 cm x 50 cm x 3.175 mm thick. The VCP is connected to the main ground plane via a low impedance ground strap through two 470-k $\Omega$  resistors.

For EFT, Surge, PQF, the HCP and VCP are removed.

RF Field Immunity testing is performed in a 7.3m x 4.3m x 4.1m anechoic chamber.

RF Conducted and Magnetic Field Immunity testing is performed on a 4.8m x 3.7m x 3.175mm thick aluminum ground plane.

All test areas allow a minimum distance of 1 meter from the EUT to walls or conducting objects.

## 2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1<sup>st</sup> Edition, 1995.

*The Combined Standard Uncertainty* is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

### 2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dBμV)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V} / \text{m}}{20}}$$

#### Sample radiated emissions calculation @ 30 MHz

**Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)**

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

### 2.3.2 Measurement Uncertainty

| Per CISPR 16-4-2                               | U <sub>lab</sub> | U <sub>cispr</sub> |
|------------------------------------------------|------------------|--------------------|
| <b>Radiated Disturbance @ 10 meters</b>        |                  |                    |
| 30 – 1,000 MHz                                 | 2.25 dB          | 4.51 dB            |
| <b>Radiated Disturbance @ 3 meters</b>         |                  |                    |
| 30 – 1,000 MHz                                 | 2.26 dB          | 4.52 dB            |
| 1 – 6 GHz                                      | 2.12 dB          | 4.25 dB            |
| 6 – 18 GHz                                     | 2.47 dB          | 4.93 dB            |
| <b>Conducted Disturbance @ Mains Terminals</b> |                  |                    |
| 150 kHz – 30 MHz                               | 1.09 dB          | 2.18 dB            |

|                          |         |        |
|--------------------------|---------|--------|
| <b>Disturbance Power</b> |         |        |
| 30 MHz – 300 MHz         | 3.92 dB | 4.3 dB |

### Voltech PM6000A

|                                                                                                            |                          |
|------------------------------------------------------------------------------------------------------------|--------------------------|
| The estimated combined standard uncertainty for harmonic current and flicker measurements is $\pm 5.0\%$ . | Per CISPR 16-4-2 Methods |
|------------------------------------------------------------------------------------------------------------|--------------------------|

### Measurement Uncertainty Immunity

|                                                                                                           |                   |
|-----------------------------------------------------------------------------------------------------------|-------------------|
| The estimated combined standard uncertainty for ESD immunity measurements is $\pm 8.2\%$ .                | Per IEC 61000-4-2 |
| The estimated combined standard uncertainty for radiated immunity measurements is $\pm 4.10$ dB.          | Per IEC 61000-4-3 |
| The estimated combined standard uncertainty for conducted immunity measurements with CDN is $\pm 3.66$ dB | Per IEC 61000-4-6 |
| The estimated combined standard uncertainty for power frequency magnetic field immunity is $\pm 11.6\%$ . | Per IEC 61000-4-8 |

### Thermo KeyTek EMC Pro

|                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------|
| The estimated combined standard uncertainty for EFT fast transient immunity measurements is $\pm 5.84\%$ .        |
| The estimated combined standard uncertainty for surge immunity measurements is $\pm 5.84\%$ .                     |
| The estimated combined standard uncertainty for voltage variation and interruption measurements is $\pm 3.48\%$ . |

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

## 2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

## **3 Product Information**

### **3.1 Product Description**

805FC Vibration meter measures vibration in acceleration, velocity, displacement and crest factor. Crest factor is a special algorithm to detect bearing failures. Nose of unit has accelerometer to measure vibration and IR sensor to measure temperature. Connections include USB and external sensor. USB is only for downloading data after a measurement and external sensor is for customer accelerometer. Fluke does not provide an external sensor as an accessory. After a measurement, data is transmitted wireless when the data is saved to the instrument.

The 805 FC uses low-power 802.15.1 wireless technology to communicate with FC Series wireless module meters.

### **3.2 Equipment Configuration**

A description of the equipment configuration is given in the Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with test standards. The EUT was programed to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

### **3.3 Operating Mode**

A description of the operation mode is given in the Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

EUT was programed to operate at > 99% duty for the purpose of testing. This operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

### **3.4 Duty Cycle:**

Duty Cycle description is provided under test plan in section 11.

---

### **3.5 Unique Antenna Connector**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

#### **3.5.1 Results**

The Vibration Meter has one internal antenna. The antenna is integral part of main PCB.

Antenna Specification:

Manufacturer - Johanson Technology

Part Number – 2450AT42B100

Type - Ceramic Chip

Antenna Gain – 0.0 dBi

## 4 Emission Requirements – 2400 MHz to 2483.5 MHz Band

Testing was performed in accordance with CFR 47 Part 15.247: 2013 and RSS 210 Annex 8: 2010. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in Section 8 of the standard were used.

### 4.1 Output Power Requirements

*The maximum output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.*


*The maximum output power and harmonics shall not exceed CFR47 Part 15.247 (b1) and RSS-210 A.8.1: 2010*

*Frequency hopping systems in the 2400-2483.5 MHz band: 0.001 watts.*

#### 4.1.1 Test Method

The conducted method was used to measure the channel power output according to ANSI C63.10:2009 Section 6.10.3.1. The measurement was performed with modulation per CFR47 Part 15.247 (b 1):2013 and RSS-210 A.8.1. This test was conducted on 3 channels. The worst mode results are indicated below.

Test Setup:



#### 4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

**Table 2: RF Output Power at the Antenna Port – Test Results**

|                                                                                                                                                                                                           |                    |                    |                                  |                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--------------------|----------------------------------|--------------------|
| <b>Test Conditions:</b> Conducted Measurement, Normal Temperature                                                                                                                                         |                    |                    |                                  |                    |
| <b>Antenna Type:</b> Chip Antenna                                                                                                                                                                         |                    |                    | <b>Power Setting:</b> Fixed.     |                    |
| <b>Max. Antenna Gain:</b> 0 dBi                                                                                                                                                                           |                    |                    | <b>Signal State:</b> Modulated   |                    |
| <b>Duty Cycle:</b> 100 %                                                                                                                                                                                  |                    |                    | <b>Data Rate:</b> see below      |                    |
| <b>Ambient Temp.:</b> 23° C                                                                                                                                                                               |                    |                    | <b>Relative Humidity:</b> 35 %RH |                    |
| 802.15.4 Mode                                                                                                                                                                                             |                    |                    |                                  |                    |
| <b>Operating Channel</b>                                                                                                                                                                                  | <b>Limit [dBm]</b> | <b>Power [dBm]</b> | <b>Power [mWatts]</b>            | <b>Margin [dB]</b> |
| 2402 MHz                                                                                                                                                                                                  | +20.96             | -2.18              | 0.60                             | -23.14             |
| 2442 MHz                                                                                                                                                                                                  | +20.96             | -2.40              | 0.57                             | -23.36             |
| 2480 MHz                                                                                                                                                                                                  | +20.96             | -2.60              | 0.55                             | -23.56             |
| <b>Note:</b> EUT has a low duty cycle. EUT was modified to transmit continuously for test purpose. The normal data rate is 1 Mbps. The above measurements did not apply any duty cycle correction factor. |                    |                    |                                  |                    |




Figure 1: Maximum Transmitted Power, 2402 MHz




Figure 2: Maximum Transmitted Power, 2440 MHz




Figure 3: Maximum Transmitted Power, 2480 MHz

## 4.2 Occupied Bandwidth

*The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.*


*The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.*

*20 dB bandwidth was performed by coupling the output of the EUT to the input of a spectrum analyzer.*

### 4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth. The measurement was performed with modulation per CFR47 15.247(a) (1) 2013 and RSS Gen Sect. 4.4.1:2010. This test was conducted on 3 channels on 805FC, SN: FC2. The worst sample result indicated below.

Test Setup:



## 4.2.2 Results

These measurements were used for information only

**Table 3:** Occupied Bandwidth – Test Results

|                                                                                    |                               |                                  |
|------------------------------------------------------------------------------------|-------------------------------|----------------------------------|
| <b>Test Conditions:</b> Conducted Measurement, Normal Temperature and Voltage only |                               |                                  |
| <b>Antenna Type:</b> Chip Antenna                                                  |                               | <b>Power Setting:</b> Fixed.     |
| <b>Max. Antenna Gain:</b> 0 dBi                                                    |                               | <b>Signal State:</b> Modulated   |
| <b>Duty Cycle:</b> 100 %                                                           |                               | <b>Data Rate:</b> see below      |
| <b>Ambient Temp.:</b> 23° C                                                        |                               | <b>Relative Humidity:</b> 35 %RH |
| <b>Bandwidth (MHz)</b>                                                             |                               |                                  |
| <b>Freq. (MHz)</b>                                                                 | <b>20dB Bandwidth<br/>MHz</b> | <b>99% Bandwidth<br/>MHz</b>     |
| 2402                                                                               | 1.192                         | 1.095                            |
| 2440                                                                               | 1.210                         | 1.108                            |
| 2480                                                                               | 1.181                         | 1.103                            |
| Notes: EUT operated at 1 Mbps.                                                     |                               |                                  |




Figure 4: Occupied Bandwidth at 2402 MHz




Figure 5: Occupied Bandwidth at 2440 MHz




Figure 6: Occupied Bandwidth at 2480 MHz

### 4.3 Hopping Frequency Requirements

*The Frequency Hopping Requirements are applicable to the equipment using Frequency Hopping Spread Spectrum (FHSS) modulation.*

*Per CFR47 15.247 (a1), RSS-210 Sect.A.8.1.2, frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.*

*Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.*

The setup was identical to RF output power measurement.

#### 4.3.1 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

**Table 4:** Frequency Hopping Requirements

|                                                                                                                                                                                                                                                                                       |                     |                                  |           |        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|----------------------------------|-----------|--------|
| <b>Test Conditions:</b> Conducted Measurement, Normal Temperature and Voltage only                                                                                                                                                                                                    |                     |                                  |           |        |
| <b>Antenna Type:</b> Chip Antenna                                                                                                                                                                                                                                                     |                     | <b>Power Setting:</b> Fixed.     |           |        |
| <b>Max. Antenna Gain:</b> 0 dBi                                                                                                                                                                                                                                                       |                     | <b>Signal State:</b> Modulated   |           |        |
| <b>Duty Cycle:</b> 100 %                                                                                                                                                                                                                                                              |                     | <b>Data Rate:</b> see below      |           |        |
| <b>Ambient Temp.:</b> 23° C                                                                                                                                                                                                                                                           |                     | <b>Relative Humidity:</b> 35 %RH |           |        |
| Average Occupancy Time                                                                                                                                                                                                                                                                |                     |                                  |           |        |
| Pulse Width (ms)                                                                                                                                                                                                                                                                      | # of Pulses in 1.6s | Ave. Time (ms)                   | Limit (s) | Result |
| 0.3925                                                                                                                                                                                                                                                                                | 64                  | 25.12                            | < 0.4     | Pass   |
| <b>Comment:</b> Since the dwell time in each channel must less than 0.4 seconds. The total time for dwell all 40 channels is 16 seconds. To determine the average dwell time, the frequency 2440MHz was sampled in 1.6 second, 1/10 <sup>th</sup> of the total 40 channel dwell time. |                     |                                  |           |        |

| Minimum Channel Separation                                        |                          |                                         |        |
|-------------------------------------------------------------------|--------------------------|-----------------------------------------|--------|
| Operating Channel (MHz)                                           | Hopping Separation (kHz) | Two-Third of 20dB Bandwidth Limit (kHz) | Result |
| 2402                                                              | 1986.10                  | > 612kHz                                | Pass   |
| 2440                                                              | 2023.35                  | > 612kHz                                | Pass   |
| 2480                                                              | 1968.60                  | > 612kHz                                | Pass   |
| <b>Comment:</b> Two-Third of the highest 20dB bandwidth was used. |                          |                                         |        |
| Minimum Number of Channels                                        |                          |                                         |        |
| Range (2402MHz -2480MHz)                                          | Min. Channel Limit       | Result                                  |        |
| 40                                                                | 15                       | Pass                                    |        |




Figure 7: Number of Operating Channels 40




Figure 8: Pulse Width – Channel 2440MHz





Figure 9: Pulse Width – Channel 2440MHz



**Figure 10:** Number Pulses in 500ms, 20

Note: There are 64 pulse in 1.6 seconds.

$$\begin{aligned} \text{Dwell time in 1.6 seconds} &= 64 \times \text{Average pulse width} \\ &= 64 \times (390.1 + 394.4) / 2 \\ &= 25.12 \text{ ms} \end{aligned}$$



Figure 11: Channel Separation at 2402MHz




Figure 12: Channel Separation at 2440MHz



Figure 13: Channel Separation at 2480MHz

#### 4.4 Out of Band Emission requirements

The setup was identical to RF output power measurement. Intentional radiators operating under the alternative provisions to the general emission limits, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If the frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

*Any frequency outside the band of 2400 MHz to 2483.5 MHz, the power output level must be below 20 dB from the in-band transmitting signal; CFR 47 Part 15.215, 15.247(d) and RSS-210 A8.5*

The setup was identical to RF output power measurement.

This test was conducted on 3 channels on 805FC, SN: FC2

##### 4.4.1 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

**Table 5: Band Edge Requirements – Test Results**

|                                                                                                  |       |             |                           |        |
|--------------------------------------------------------------------------------------------------|-------|-------------|---------------------------|--------|
| Test Conditions: Conducted Measurement, Normal Temperature and Voltage only                      |       |             |                           |        |
| Antenna Type: Chip Antenna                                                                       |       |             | Power Setting: Fixed.     |        |
| Max. Antenna Gain: 0 dBi                                                                         |       |             | Signal State: Modulated   |        |
| Duty Cycle: 100 %                                                                                |       |             | Data Rate: see below      |        |
| Ambient Temp.: 23° C                                                                             |       |             | Relative Humidity: 35 %RH |        |
| -20 dBr Band Edge Results                                                                        |       |             |                           |        |
| Operating Freq.                                                                                  | Mode  | Limit (dBm) | Measured Value (dBm)      | Result |
| 2402 MHz                                                                                         | 1Mbps | -22.18      | -53.17                    | Pass   |
| 2442 MHz                                                                                         | 1Mbps | -22.40      | -63.03                    | Pass   |
| 2480 MHz                                                                                         | 1Mbps | -22.60      | -55.84                    | Pass   |
| Note: The stated limits for 20 dBr are relative to each individual output per KDB 662911 Method. |       |             |                           |        |

| Out of Band Emission                                                                         |       |             |                      |        |
|----------------------------------------------------------------------------------------------|-------|-------------|----------------------|--------|
| Operating Freq.                                                                              | Mode  | Limit (dBm) | Measured Value (dBm) | Result |
| 2402 MHz                                                                                     | 1Mbps | -22.18      | -41.66               | Pass   |
| 2442 MHz                                                                                     | 1Mbps | -22.40      | -44.42               | Pass   |
| 2480 MHz                                                                                     | 1Mbps | -22.60      | -46.15               | Pass   |
| <b>Note:</b> The stated limits are relative to each individual output per KDB 662911 Method. |       |             |                      |        |




Figure 14: Band Edge Requirements at 2402 MHz





Figure 15: Band Edge Requirements at 2440 MHz






Figure 17: Out of Band Emission Requirements at 2402 MHz




Figure 18: Out of Band Emission Requirements at 2440 MHz




Figure 19: Out of Band Emission Requirements at 2480 MHz

## 4.5 Maximum RF Exposure

### 4.5.1 Test Methodology

In this section, we try to prove the safety of radiation harmfulness to the human body for our product. The KDB 447498 D01 General RF Exposure Guidance is followed. The Gain of the antenna used in this calculation is declared by the manufacturer, and the maximum average power input to the antenna is measured. Using the general SAR test exclusion guidance in Section 4.3 of KDB 447498, we show the device meeting the SAR exclusion threshold.

Note: Per RSS 102:2010 Section 2.5.1, the EUT is exempted since the measured power is less than 20mW.

### 4.5.2 FCC KDB 447498 D01 – General SAR Test Exclusion Guidance

The SAR exclusion threshold conditions are listed:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

☐  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

☐ Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:<sup>18</sup>

a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)  $\cdot$  ( $f(\text{MHz})/150$ )] mW, at 100 MHz to 1500 MHz

b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)  $\cdot$  10] mW at  $> 1500$  MHz and  $\leq 6$  GHz

- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion, and as illustrated in Appendix C:<sup>19</sup>

a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm

b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

### 4.5.3 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

### 4.5.4 Classification

The antenna of the product, under normal use condition, is less than 20cm away from the body of the user. This device is classified as a **Portable Device**.

### 4.5.5 SAR Test Exclusion Threshold

#### 4.5.5.1 Antenna Gain

The transmitting antenna was integrated. The directional antenna gain was 3.0 dBi.

#### 4.5.5.2 SAR Exclusion Threshold Calculation

| Mode                                                                                                                                                                                                                    | Max. Power (dBm) | EIRP (dBm) | Min. Separation Distance (mm) | Cal. Excl. Threshold | 1-g SAR Limit | 10-g extremity SAR Limit | Result   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|------------|-------------------------------|----------------------|---------------|--------------------------|----------|
| BLE                                                                                                                                                                                                                     | -2.18            | -2.18      | 5                             | 2.633                | $\leq 3.0$    | $\leq 7.5$               | Exempted |
| Note:<br>1. Since EUT can operate at distance less than 50 mm, the minimum distance, 5 mm, was used for calculation per condition #1 of SAR Exclusion Threshold.<br>2. The maximum output power was taken from Table 2. |                  |            |                               |                      |               |                          |          |

## **4.6 Transmitter Spurious Emissions**

*Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmitting mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS-210 Sect. A.8.5*

### **4.6.1 Test Methodology**

#### **4.6.1.1 Preliminary Test**

A test program that controls instrumentation and data logging was used to automate the preliminary RF emission test procedure. The frequency range of interest was divided into sub-ranges to yield a frequency resolution of approximately 120 kHz and provide a reading at each frequency for no more than 12° of turntable rotation. For each frequency sub-range the turntable was rotated 360° while peak emission data was recorded and plotted over the frequency range of interest in horizontal and vertical antenna polarization's.

Preliminary emission profile testing was performed inside the anechoic chamber. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm above the floor. The EUT was positioned as shown in the setup photographs. The receiving antenna was placed at a distance of 3m at a fixed height of 1m. Measurement equipment was located outside of the chamber. A video camera was placed inside the chamber to view the EUT.

#### **4.6.1.2 Final Test**

For each frequency measured, the peak emission was maximized by manipulating the receiving antenna from 1 to 4 meters above the ground plane and placing it at the position that produced the maximum signal strength reading. The turntable was then rotated through 360° while observing the peak signal and placing the EUT at the position that produced maximum radiation. The six highest emissions relative to the limit were measured unless such emissions were more than 20 dB below the limit. If less than six emissions are within 20 dB of the limit, then the noise level of the receiver is measured at frequencies where emissions are expected. Multiples of all oscillator and microprocessor frequencies were also checked.

Final testing was performed on an NSA compliant test site. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane. The placement of EUT and cables were the same as for preliminary testing and is shown in the setup photographs.

The final scans performed on the worst axis, X-Axis, for three operating channels: 2402 MHz, 2440 MHz, and 2480 MHz at 1 Mbit/s.

#### **4.6.1.3 Deviations**

None.

#### 4.6.2 Transmitter Spurious Emission Limit

The spurious emissions of the transmitter shall not exceed the values in CFR47 Part 15.205, 15.209:2013 and RSS-210 A1.1.2 2010.

| Frequency (MHz)  | Field strength<br>(microvolts/meter) | Measurement<br>distance<br>(meters) |
|------------------|--------------------------------------|-------------------------------------|
| 0.009-0.490..... | 2400/F (kHz)                         | 300                                 |
| 0.490-1.705..... | 24000/F (kHz)                        | 30                                  |
| 1.705-30.0.....  | 30                                   | 30                                  |
| 30-88.....       | 100 **                               | 3                                   |
| 88-216.....      | 150 **                               | 3                                   |
| 216-960.....     | 200 **                               | 3                                   |
| Above 960.....   | 500                                  | 3                                   |

All harmonics and spurious emission which are outside of the restricted band shall be 20 dB below the in-band emission.


#### 4.6.3 Test Results

The final measurement data was taken under the worst case operating modes, configurations, and/or cable positions. It also reflects the results including any modifications and/or special accessories listed in Sections 1.4 and Test Plan.


As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

**Table 6:** Transmit Spurious Emission at Restricted Band Edge Requirements


|                                                   |            |      |               |        |                           |         |        |                       |
|---------------------------------------------------|------------|------|---------------|--------|---------------------------|---------|--------|-----------------------|
| Test Conditions: Radiated Measurement at 3 meters |            |      |               |        |                           |         |        |                       |
| Antenna Type: Chip Antenna                        |            |      |               |        | Power Setting: Fixed.     |         |        |                       |
| Max. Antenna Gain: 0 dBi                          |            |      |               |        | Signal State: Modulated   |         |        |                       |
| Duty Cycle: 100 %                                 |            |      |               |        | Data Rate: see below      |         |        |                       |
| Ambient Temp.: 23° C                              |            |      |               |        | Relative Humidity: 38 %RH |         |        |                       |
| Band Edge Results                                 |            |      |               |        |                           |         |        |                       |
| Freq.                                             | Level      | Pol. | 15.209/15.247 |        | Detector                  | Azimuth | Height | Comments              |
| MHz                                               | dBuV/<br>m | V/H  | Limit         | Margin | Pk/QP/Avg                 | degrees | meters |                       |
| 2390                                              | 36.78      | V    | 74.00         | -37.22 | Pk                        | 207     | 342    | TX at 2402 MHz, 1Mbps |
| 2390                                              | 25.85      | V    | 54.00         | -28.15 | Ave                       | 207     | 342    | TX at 2402 MHz, 1Mbps |
| 2390                                              | 35.98      | H    | 74.00         | -38.02 | Pk                        | 185     | 100    | TX at 2402 MHz, 1Mbps |
| 2390                                              | 26.43      | H    | 54.00         | -27.57 | Ave                       | 185     | 100    | TX at 2402 MHz, 1Mbps |
| 2483.5                                            | 37.64      | V    | 74.00         | -36.36 | Pk                        | 133     | 328    | TX at 2480 MHz, 1Mbps |
| 2483.5                                            | 28.40      | V    | 54.00         | -25.60 | Ave                       | 133     | 328    | TX at 2480 MHz, 1Mbps |
| 2483.5                                            | 42.57      | H    | 74.00         | -31.43 | Pk                        | 184     | 137    | TX at 2480 MHz, 1Mbps |
| 2483.5                                            | 36.24      | H    | 54.00         | -17.76 | Ave                       | 184     | 137    | TX at 2480 MHz, 1Mbps |




**Figure 20:** Radiated Emission at the Edge for Channel 2402 MHz at 1Mbps – Vertical (Peak)




**Figure 21:** Radiated Emission at the Edge for Channel 2402 MHz at 1Mbps – Vertical (Avg)




**Figure 22:** Radiated Emission at the Edge for Channel 2402 MHz at 1Mbps – Horizontal (Pk)






**Figure 24: Radiated Emission at the Edge for Channel 2480 MHz at 1Mbps – Vertical (Pk)**



**Figure 25:** Radiated Emission at the Edge for Channel 2480 MHz at 1Mbps – Vertical (Avg)



**Figure 26:** Radiated Emission at the Edge for Channel 2480 MHz at 1Mbps – Horizontal (Pk)




|                                                                                                                 |                              |       |        |        |          |     |                                     |                   |       |        |        |
|-----------------------------------------------------------------------------------------------------------------|------------------------------|-------|--------|--------|----------|-----|-------------------------------------|-------------------|-------|--------|--------|
| SOP 1 Radiated Emissions                                                                                        |                              |       |        |        |          |     | Tracking # 31460300.001 Page 1 of 6 |                   |       |        |        |
| EUT Name                                                                                                        | Vibration Meter              |       |        |        |          |     | Date                                | 06 Nov, 2014      |       |        |        |
| EUT Model                                                                                                       | 805FC                        |       |        |        |          |     | Temp / Hum in                       | 23°C / 38%rh      |       |        |        |
| EUT Serial                                                                                                      | FC2                          |       |        |        |          |     | Temp / Hum out                      | N/A               |       |        |        |
| EUT Comfit.                                                                                                     | Integrated Antenna on X-Axis |       |        |        |          |     | Line AC / Freq                      | 3.0 V(batteries)  |       |        |        |
| Standard                                                                                                        | CFR47 Part 15 Subpart C      |       |        |        |          |     | RBW / VBW                           | 120KHz/300KHz     |       |        |        |
| Dist/Ant Used                                                                                                   | 3m /JB3                      |       |        |        |          |     | Performed by                        | Suresh Kondapalli |       |        |        |
| 30 -1000 MHz radiated emission at 2440 MHz This table combines test data of 3 channels                          |                              |       |        |        |          |     |                                     |                   |       |        |        |
| Freq                                                                                                            | Raw                          | Cable | AF     | Level  | Detector | Pol | Hgt                                 | Azt               | Limit | Margin | Result |
| MHz                                                                                                             | dBuV/m                       | dB    | dB     | dBuV/m | QP       | -   | cm                                  | Deg               | dBuV  | dB     |        |
| 30.68                                                                                                           | 21.23                        | 1.27  | -5.29  | 17.22  | QP       | H   | 338                                 | 28                | 40.00 | -22.79 | Pass   |
| 450.18                                                                                                          | 20.95                        | 2.24  | -9.95  | 13.25  | QP       | H   | 167                                 | 177               | 46.00 | -32.76 | Pass   |
| 649.81                                                                                                          | 21.67                        | 2.54  | -7.08  | 17.13  | QP       | H   | 216                                 | 32                | 46.00 | -28.87 | Pass   |
| 649.98                                                                                                          | 21.62                        | 2.54  | -7.08  | 17.08  | QP       | H   | 355                                 | 198               | 46.00 | -28.92 | Pass   |
| 749.75                                                                                                          | 21.26                        | 2.67  | -5.86  | 18.07  | QP       | H   | 392                                 | 76                | 46.00 | -27.93 | Pass   |
| 54.71                                                                                                           | 27.30                        | 1.37  | -18.94 | 9.74   | QP       | V   | 106                                 | 4                 | 40.00 | -30.26 | Pass   |
| Spec Margin = Level – Limit, Level = Raw + Cable + AF ± Uncertainty<br>AF= Amp Gain + ANT Factor                |                              |       |        |        |          |     |                                     |                   |       |        |        |
| Combined Standard Uncertainty $u_c(y)$ = ± 3.2 dB Expanded Uncertainty $U = ku_c(y)$ $k = 2$ for 95% confidence |                              |       |        |        |          |     |                                     |                   |       |        |        |
| Note 1. Pre-scan performed on 3 orientations, and the worst case was observed on X-Axis .                       |                              |       |        |        |          |     |                                     |                   |       |        |        |

**SOP 1 Radiated Emissions**

Tracking # 31460300.001 Page 2 of 6

|                      |                              |                       |                   |
|----------------------|------------------------------|-----------------------|-------------------|
| <b>EUT Name</b>      | Vibration Meter              | <b>Date</b>           | Nov 06, 2014      |
| <b>EUT Model</b>     | 805FC                        | <b>Temp / Hum in</b>  | 23°C / 38%rh      |
| <b>EUT Serial</b>    | FC2                          | <b>Temp / Hum out</b> | N/A               |
| <b>EUT Comfit.</b>   | Integrated Antenna on X-Axis | <b>Line AC / Freq</b> | 3.0 V(batteries)  |
| <b>Standard</b>      | CFR47 Part 15 Subpart C      | <b>RBW / VBW</b>      | 120KHz/300KHz     |
| <b>Dist/Ant Used</b> | 3m /JB3                      | <b>Performed by</b>   | Suresh Kondapalli |

30 to 1000 MHz Plots for Transmit Mode at 2402 MHz, 1Mbit/s



Note: Plot was scanned in the peak mode.

|                                 |                                   |  |  |                                     |                   |  |  |
|---------------------------------|-----------------------------------|--|--|-------------------------------------|-------------------|--|--|
| <b>SOP 1 Radiated Emissions</b> |                                   |  |  | Tracking # 31460300.001 Page 3 of 6 |                   |  |  |
| <b>EUT Name</b>                 | Vibration Meter                   |  |  | <b>Date</b>                         | Nov 06, 2014      |  |  |
| <b>EUT Model</b>                | 805FC                             |  |  | <b>Temp / Hum in</b>                | 22°C / 31%rh      |  |  |
| <b>EUT Serial</b>               | FC2                               |  |  | <b>Temp / Hum out</b>               | N/A               |  |  |
| <b>EUT Comfit.</b>              | Integrated Antenna on X-Axis      |  |  | <b>Line AC / Freq</b>               | 3.0 V(batteries)  |  |  |
| <b>Standard</b>                 | CFR47 Part 15 Subpart C           |  |  | <b>RBW / VBW</b>                    | 120KHz/300KHz     |  |  |
| <b>Dist/Ant Used</b>            | 3m – DRH-118 / 1m - RA42-K-F-4B-C |  |  | <b>Performed by</b>                 | Suresh Kondapalli |  |  |

Above 1GHz Radiated Emission at 2402 MHz, 1 Mbps

| Frequency | Raw    | Cable Loss | AF     | Level  | Detector | Polarity | Height | Azimuth | Limit  | Margin | Result | Comments |
|-----------|--------|------------|--------|--------|----------|----------|--------|---------|--------|--------|--------|----------|
| MHz       | dBuV/m | dB         | dB     | dBuV/m |          | H/V      | cm     | deg     | dBuV/m | dB     |        |          |
| 1049.81   | 56.30  | 0.75       | -26.25 | 30.80  | Avg      | H        | 160    | 40      | 54.00  | -23.20 | Pass   | Spur     |
| 1150.01   | 59.12  | 0.79       | -25.78 | 34.13  | Avg      | H        | 146    | 32      | 54.00  | -19.87 | Pass   | Spur     |
| 1250.00   | 59.29  | 0.82       | -25.50 | 34.61  | Avg      | H        | 126    | 144     | 54.00  | -19.39 | Pass   | Spur     |
| 1350.01   | 58.71  | 0.86       | -25.52 | 34.05  | Avg      | H        | 194    | 238     | 54.00  | -19.95 | Pass   | Spur     |
| 2050.01   | 54.03  | 1.06       | -23.42 | 31.68  | Avg      | H        | 106    | 114     | 54.00  | -22.33 | Pass   | Spur     |
| 4804.36   | 62.20  | 1.65       | -16.37 | 47.49  | Avg      | V        | 134    | 70      | 54.00  | -6.51  | Pass   | Har      |

Above 1GHz Radiated Emission at 2440 MHz, 1 Mbps

|         |       |      |        |       |     |   |     |     |       |        |      |      |
|---------|-------|------|--------|-------|-----|---|-----|-----|-------|--------|------|------|
| 1049.73 | 54.65 | 0.75 | -26.25 | 29.15 | Avg | H | 174 | 24  | 54.00 | -24.85 | Pass | Spur |
| 1149.92 | 59.39 | 0.79 | -25.78 | 34.40 | Avg | H | 144 | 30  | 54.00 | -19.60 | Pass | Spur |
| 1250.09 | 58.25 | 0.82 | -25.50 | 33.58 | Avg | H | 136 | 128 | 54.00 | -20.42 | Pass | Spur |
| 1449.90 | 57.59 | 0.89 | -25.56 | 32.92 | Avg | H | 170 | 40  | 54.00 | -21.08 | Pass | Spur |
| 1550.50 | 48.12 | 0.92 | -25.45 | 23.59 | Avg | H | 156 | 220 | 54.00 | -30.41 | Pass | Spur |
| 4883.41 | 62.43 | 1.67 | -16.32 | 47.78 | Avg | V | 154 | 68  | 54.00 | -6.22  | Pass | Har  |

Above 1GHz Radiated Emission at 2480 MHz, 1 Mbps

|         |       |      |        |       |     |   |     |     |       |        |      |      |
|---------|-------|------|--------|-------|-----|---|-----|-----|-------|--------|------|------|
| 1149.86 | 59.29 | 0.79 | -25.78 | 34.30 | Avg | H | 144 | 32  | 54.00 | -19.70 | Pass | Spur |
| 1250.08 | 59.22 | 0.82 | -25.50 | 34.54 | Avg | H | 129 | 144 | 54.00 | -19.46 | Pass | Spur |
| 1350.02 | 58.67 | 0.86 | -25.52 | 34.02 | Avg | H | 196 | 224 | 54.00 | -19.99 | Pass | Spur |
| 1550.51 | 45.87 | 0.92 | -25.45 | 21.35 | Avg | H | 159 | 28  | 54.00 | -32.66 | Pass | Spur |
| 1049.76 | 54.11 | 0.75 | -26.25 | 28.61 | Avg | V | 116 | 286 | 54.00 | -25.39 | Pass | Spur |
| 4959.34 | 58.12 | 1.68 | -16.38 | 43.42 | Avg | V | 170 | 74  | 54.00 | -10.58 | Pass | Har  |


|                                                                                                                    |                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Spec Margin = Level – Limit, Level = Raw + Cable + AF ± Uncertainty<br>AF= Amp Gain + ANT Factor                   |                                                                                                                                                                                                                                                                                                      |
| Combined Standard Uncertainty $u_c(y) = \pm 3.2$ dB Expanded Uncertainty $U = k u_c(y)$ $k = 2$ for 95% confidence |                                                                                                                                                                                                                                                                                                      |
| Note                                                                                                               | 1. Pre-scan performed on 3 orientations, and the worst case was observed on X-Axis .<br>2. EUT has operating maximum duty cycle less than 0.13%.<br>3. Since EUT has low duty cycle, maximum reduction of 20 dB was applied to the peak measurements.<br>4. All emissions met restricted band limit. |

## SOP 1 Radiated Emissions

Tracking # 31460300.001 Page 4 of 6

|               |                                   |                |                   |
|---------------|-----------------------------------|----------------|-------------------|
| EUT Name      | Vibration Meter                   | Date           | Nov 06, 2014      |
| EUT Model     | 805FC                             | Temp / Hum in  | 23°C / 31%rh      |
| EUT Serial    | DEM0003                           | Temp / Hum out | N/A               |
| EUT Config.   | Integrated Antenna on X-Axis      | Line AC        | 3.0 V(batteries)  |
| Standard      | CFR47 Part 15 Subpart C           | RBW / VBW      | 1 MHz/ 3 MHz      |
| Dist/Ant Used | 3m – DRH-118 / 1m - RA42-K-F-4B-C | Performed by   | Suresh Kondapalli |

Above 1 GHz Radiated Emission Plot for Transmit Mode at 2402 MHz, 1Mbit/s




Notes: 18 GHz – 25 GHz was scanned at 1m distance. No emissions were found 18-25GHz range

**SOP 1 Radiated Emissions**

Tracking # 31460300.001 Page 5 of 6

|                      |                                   |                       |                   |
|----------------------|-----------------------------------|-----------------------|-------------------|
| <b>EUT Name</b>      | Vibration Meter                   | <b>Date</b>           | Nov 06, 2014      |
| <b>EUT Model</b>     | 805FC                             | <b>Temp / Hum in</b>  | 23°C / 31%rh      |
| <b>EUT Serial</b>    | DEM0003                           | <b>Temp / Hum out</b> | N/A               |
| <b>EUT Config.</b>   | Integrated Antenna on X-Axis      | <b>Line AC</b>        | 3.0 V(batteries)  |
| <b>Standard</b>      | CFR47 Part 15 Subpart C           | <b>RBW / VBW</b>      | 1 MHz/ 3 MHz      |
| <b>Dist/Ant Used</b> | 3m – DRH-118 / 1m - RA42-K-F-4B-C | <b>Performed by</b>   | Suresh Kondapalli |

Above 1 GHz Radiated Emission Plot for Transmit Mode at 2440 MHz, 1Mbit/s




Notes: 18 GHz – 25 GHz was scanned at 1m distance. No emissions were found 18-25GHz range

**SOP 1 Radiated Emissions**

Tracking # 31460300.001 Page 6 of 6

|                      |                                   |                       |                   |
|----------------------|-----------------------------------|-----------------------|-------------------|
| <b>EUT Name</b>      | Vibration Meter                   | <b>Date</b>           | Nov 06, 2014      |
| <b>EUT Model</b>     | 805FC                             | <b>Temp / Hum in</b>  | 23°C / 31%rh      |
| <b>EUT Serial</b>    | DEM0003                           | <b>Temp / Hum out</b> | N/A               |
| <b>EUT Config.</b>   | Integrated Antenna on X-Axis      | <b>Line AC</b>        | 3.0 V(batteries)  |
| <b>Standard</b>      | CFR47 Part 15 Subpart C           | <b>RBW / VBW</b>      | 1 MHz/ 3 MHz      |
| <b>Dist/Ant Used</b> | 3m – DRH-118 / 1m - RA42-K-F-4B-C | <b>Performed by</b>   | Suresh Kondapalli |

Above 1 GHz Plots for Transmit Mode at 2480 MHz 1Mbit/s



Notes: 18 GHz – 25 GHz was scanned at 1m distance. No emissions were found 18-25GHz range

#### 4.6.4 Sample Calculation

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{FIM} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where:

FIM = Field Intensity Meter (dB $\mu$ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V} / \text{m}}{20}}$$

---

## **4.7 AC Conducted Emissions**

Testing was performed in accordance with ANSI C63.4: 2009. These test methods are listed under the laboratory's A2LA Scope of Accreditation.

This test measures the levels emanating from the EUT's AC input port, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

The AC conducted emissions of equipment under test shall not exceed the values in CFR47 Part 15.207: 2013 and RSS-210: 2010.

### **4.7.1 Test Methodology**

A test program that controls instrumentation and data logging was used to automate the AC Power Line Conducted emission test procedure. The frequency range of interest was divided into sub-ranges such as to yield a frequency resolution of 9 kHz. Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a set of 50 $\mu$ H / 50 $\Omega$  LISNs.

Testing is either performed in Lab 5. The setup photographs clearly identify which site was used. The vertical ground plane used in the semi-anechoic chamber is a 2m x 2m solid aluminum frame and panel, and it is bonded to the horizontal ground plane.

In the case of tabletop equipment, the EUT is placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane and 40cm from a vertical ground reference plane. The rear of the EUT was positioned flush with the backside of the table and directly over the LISNs. The power and I/O cables were routed over the edge of the table and bundled approximately 40cm from the ground plane. Support equipment was powered from a separate LISN.

### **4.7.2 Deviations**

There were no deviations from this test methodology.

### **4.7.3 Test Results**

This Test is not applicable since EUT is powered alkaline battery.

## 5 Test Equipment Use List

### 5.1 Equipment List

| Equipment         | Manufacturer    | Model #       | Serial/Inst # | Last Cal<br>mm/dd/yy | Next Cal<br>mm/dd/yy |
|-------------------|-----------------|---------------|---------------|----------------------|----------------------|
| Bilog Antenna     | Sunol Sciences  | JB3           | A020502       | 04/02/2014           | 04/02/2015           |
| Horn Antenna      | EMCO            | 3115          | 9211-3969     | 03/18/2013           | 03/18/2015           |
| Horn Antenna      | CMT             | RA42-K-F-4B-C | 020131-004    | 06/19/2014           | 06/19/2015           |
| Spectrum Analyzer | Agilent         | N9038A        | MY52260210    | 01/08/2014           | 02/08/2015           |
| Spectrum Analyzer | Rohde Schwarz   | ESIB          | 832427/002    | 01/08/2014           | 02/08/2015           |
| Amplifier         | Hewlett Packard | 8447D         | 2944A07996    | 01/07/2014           | 02/07/2015           |
| Amplifier         | Miteq           | TTA1800-30-4G | 1842452       | 01/08/2014           | 02/08/2015           |
| Amplifier         | Rhode&Schwarz   | TS-PR26       | 100011        | 03/05/2014           | 03/05/2015           |
| Power Meter       | Agilent         | E4418B        | MY45103902    | 01/09/2014           | 02/09/2015           |
| Power Sensor      | Hewlett Packard | 8482A         | 55-5131       | 01/09/2014           | 02/09/2015           |
| Notch Filter      | Micro-Tronics   | BRM50702      | 37            | 07/18/2014           | 07/18/2015           |

\* Calibration of equipment past due for re-calibration will be performed expeditiously. If any equipment is found to be out of tolerance at that time, affected customers will be notified accordingly.

## 6 EMC Test Plan

### 6.1 Introduction

This section provides a description of the Equipment Under Test (EUT), configurations, operating conditions, and performance acceptance criteria. It is an overview of information provided by the manufacturer so that the test laboratory may perform the requested testing.

### 6.2 Customer

**Table 7:** Customer Information

|                         |                    |
|-------------------------|--------------------|
| <b>Company Name</b>     | Fluke Corporation. |
| <b>Address</b>          | 6920 Seaway Blvd.  |
| <b>City, State, Zip</b> | Everett, WA 98203  |
| <b>Country</b>          | U.S.A.             |
| <b>Phone</b>            | (425) 446-5518     |

**Table 8:** Technical Contact Information

|               |                      |
|---------------|----------------------|
| <b>Name</b>   | Graham Don T         |
| <b>E-mail</b> | don.graham@fluke.com |
| <b>Phone</b>  | (425) 446-5518       |
| <b>Fax</b>    | (425) 446-4703       |

### 6.3 Product Specification

**Table 9:** EUT Specifications

| EUT Specification            |                                                                                                                                                                                     |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions                   | 24.5 cm x 7.4 cm x 4.8 cm                                                                                                                                                           |
| Power                        | EUT is Battery Operated<br>Input Voltage: 3.0 V ( 2 AA batteries)                                                                                                                   |
| Environment                  | Indoor and Outdoor                                                                                                                                                                  |
| Operating Temperature Range: | -10 to +50 degrees C                                                                                                                                                                |
| Multiple Feeds:              | <input type="checkbox"/> Yes and how many<br><input checked="" type="checkbox"/> No                                                                                                 |
| Hardware Version             | NA                                                                                                                                                                                  |
| Part Number                  | NA                                                                                                                                                                                  |
| RF Software Version          | None                                                                                                                                                                                |
| Operating Mode               | 802.15.1 - Bluetooth Radio                                                                                                                                                          |
| Transmitter Frequency Band   | 2.402 GHz to 2.480 GHz                                                                                                                                                              |
| Max. Rated Power Output      | 1 dBm                                                                                                                                                                               |
| Antenna Type                 | 0 dBi integrated chip antenna                                                                                                                                                       |
| Modulation Type              | <input type="checkbox"/> AM <input type="checkbox"/> FM <input type="checkbox"/> DSSS <input type="checkbox"/> OFDM<br><input checked="" type="checkbox"/> Other describe: GFSK     |
| Data Rate                    | 1 Mbps                                                                                                                                                                              |
| TX/RX Chain (s)              | 1                                                                                                                                                                                   |
| Directional Gain Type        | <input checked="" type="checkbox"/> Uncorrelated <input checked="" type="checkbox"/> No Beam-Forming<br><input type="checkbox"/> Other describe:                                    |
| Type of Equipment            | <input type="checkbox"/> Table Top <input type="checkbox"/> Wall-mount <input type="checkbox"/> Floor standing cabinet<br><input checked="" type="checkbox"/> Other <i>Portable</i> |

## 6.4 Configuration (s)




Figure 28 - Block Diagram of EUT Setup

**Note:** The wireless vibration meter was in stand-alone. There was no support device.

Table 10: Description of Sample used for Testing

| Device | Serial | RF Connection  | CFR 47 Part 15.247                                         |
|--------|--------|----------------|------------------------------------------------------------|
| 805FC  | FC2    | Chip Antenna   | TX Spurious Emission<br>Hopping Parameters                 |
|        | FC1    | Direct via SMA | Output Power<br>Occupied Bandwidth<br>Out of Band Emission |

Table 11: Description of Test Configuration used for Radiated Measurement.

| Device                                                                                 | Antenna    | Mode     | Setup Photo (X-Axis)                                                               | Setup Photo (Y-Axis)                                                                | Setup Photo (Z-Axis)                                                                |
|----------------------------------------------------------------------------------------|------------|----------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 805FC                                                                                  | Integrated | Transmit |  |  |  |
| <b>Note:</b> Pre-scans were performed in 3 orthogonal axis, and X-Axis was worst-case. |            |          |                                                                                    |                                                                                     |                                                                                     |

## 6.5 Test Specifications

Testing requirements

Table 12: Test Specifications

| Emissions and Immunity  |             |
|-------------------------|-------------|
| Standard                | Requirement |
| CFR 47 Part 15.247:2013 | All         |
| RSS-210 Issue 8, 2010   | All         |



**END OF REPORT**