



TEST REPORT
ETSI EN 301 893 V2.2.1 (2024-11)

Report Reference No.: **HK241217001-1ER**

Compiled by

(position+printed name+signature)...: Testing engineer Bella Huang

Bella Huang

Supervised by

(position+printed name+signature)...: Technique principal Sliver Wan

Sliver Wan

Approved by

(position+printed name+signature)...: Manager Jason Zhou

Jason Zhou

Date of issue: 2025/01/07

Representative Laboratory Name.....: Shenzhen HUAK Testing Technology Co., Ltd.

Address.....: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park,
Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong,
China

Applicant's name: ViewSonic Corporation

Address.....: 10 Pointe Dr. Suite 200. Brea, CA 92821, USA

Test specification :

Standard: **ETSI EN 301 893 V2.2.1 (2024-11)**

TRF Originator: Shenzhen HUAK Testing Technology Co., Ltd.

Master TRF: Dated 2014-12

Shenzhen HUAK Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Product Name : WPD-900

Trade Mark: ViewSonic

Product Model.....: VS20455

Serial Model.....: WPD-900-TX

Hardware version.....: V3

Software version.....: V2.0

Operation Frequency.....: From 5180MHz-5240MHz

Ratings.....: DC 5V From Type-C

Result.....: **PASS**



TEST REPORT

Test Report No. :	HK241217001-1ER	2025/01/07
		Date of issue

Product Name : WPD-900

Product Model : VS20455

Serial Model : WPD-900-TX

Applicant : ViewSonic Corporation

Address : 10 Pointe Dr. Suite 200. Brea, CA 92821, USA

Manufacturer : Actions Microelectronics Co., Ltd.

Address : 201, No.9 Building, Software Park, KeJiZhongEr Road, GaoXinQu, NanShan, Shenzhen, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



**** Modified History ****

Revision	Description	Issued Data	Remark
Revision 1.0	Initial Test Report Release	2025/01/07	Jason Zhou



Contents

1.	<u>TEST STANDARDS</u>	<u>5</u>
2.	<u>SUMMARY</u>	<u>6</u>
2.1.	General Remarks	6
2.2.	Product Description	6
2.3.	Equipment Under Test	6
2.4.	EUT configuration	7
2.5.	Test summary	8
2.6.	Modifications	8
3.	<u>TEST ENVIRONMENT</u>	<u>9</u>
3.1.	Information of the Test Laboratory	9
3.2.	Environmental conditions	9
3.3.	Test Channels:	10
3.4.	Statement of the measurement uncertainty	10
3.5.	Equipments Used during the Test	11
4.	<u>TEST CONDITIONS AND RESULTS</u>	<u>12</u>
4.1.	Centre frequencies	12
4.2.	Nominal Channel Bandwidth and Occupied Channel Bandwidth	14
4.3.	RF output power, Transmit Power Control (TPC) and power density	17
4.3.1.	RF output power at the highest power - PH	18
4.3.2.	RF output power at the lowest power level of the TPC range - PL	20
4.4.	Power density	21
4.5.	Transmitter unwanted emissions	24
4.5.1.	Transmitter unwanted emissions outside the 5 GHz RLAN bands	24
4.5.2.	Transmitter unwanted emissions within the 5 GHz RLAN bands	27
4.6.	Receiver spurious emissions	29
4.7.	Dynamic Frequency Selection (DFS)	32
4.8.	Adaptivity	36
4.9.	Receiver Blocking	49
4.10.	Adjacent channel selectivity	51
4.11.	User Access Restrictions	53
4.12.	Geo-location capability	54
5.	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>55</u>
6.	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>56</u>



TEST STANDARDS

The tests were performed according to following standards:

[ETSI EN 301 893 V2.2.1 \(2024-11\)](#)–5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU



SUMMARY

1.1. General Remarks

Date of receipt of test sample	:	2024/12/24
Testing commenced on	:	2024/12/24
Testing concluded on	:	2025/01/07

1.2. Product Description

Product Name:	WPD-900
Model/Type reference:	VS20455
List Model:	WPD-900-TX
Difference description	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: VS20455.
Power supply:	DC 5V From Type-C
Adapter information:	N/A
Antenna Type	PCB Antenna
Antenna Gain	1dBi
WLAN	Supported 802.11a/802.11n HT20
Operation frequency	IEEE 802.11a:5180MHz-5240MHz IEEE 802.11n HT20:5180MHz-5240MHz
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Remark: The products are identical in interior structure, electrical circuits and components, just model names are different.	
Note:Antenna gain Refer to the antenna specifications. The cable loss data is obtained from the supplier. The test results in the report only apply to the tested sample.	

1.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 5V From Type-C



Channel list:

Channel	Frequency (MHz)
36	5180
38	2190
40	5200
44	5220
46	5230
48	5240

1.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○ /	M/N: /
	Manufacturer: /



1.5. Test summary

Test Item	Test Requirement ESTI EN301983	Verdict
Centre frequencies	Section 4.2.1	Pass
Nominal Channel Bandwidth and Occupied Channel Bandwidth	Section 4.2.2	Pass
RF output power, Transmit Power Control (TPC) and power density	Section 4.2.3	Pass
Transmitter unwanted emissions	Section 4.2.4	Pass
Receiver spurious emissions	Section 4.2.5	Pass
Dynamic Frequency Selection (DFS)	Section 4.2.6	N/A
Adaptivity (Channel Access Mechanism) 4.8.1 Applicability	Section 4.2.7	Pass
Receiver Blocking	Section 4.2.8	Pass
User Access Restrictions	Section 4.2.9	Pass
Geo-location capability	Section 4.2.10	N/A
Geo-location capability	B.2.2.11	N/A
Note:N./A Stands for "Not applicable"		

1.6. Modifications

No modifications were implemented to meet testing criteria.



TEST ENVIRONMENT

1.7. Information of the Test Laboratory

Shenzhen HUAK Testing Technology Co., Ltd.

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Testing Laboratory Authorization:

A2LA Accreditation Code is 4781.01.

FCC Designation Number is CN1229.

Canada IC CAB identifier is CN0045.

CNAS Registration Number is L9589.

1.8. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature: 25 °C

High Temperature: 40 °C

Low Temperature: -10 °C

Normal Voltage : DC 5V

High Voltage:DC 5.5V

Low Voltage:DC 4.5V

Relative Humidity: 55 %

Air Pressure: 989 hPa



1.9. Test Channels:

Test	Clause	Test channels		
		Lower sub-band (5 150 MHz to 5 350 MHz)		Higher sub-band 5 725 MHz to 5 850 MHz
		5 150 MHz to 5 250 MHz	5 250 MHz to 5 350 MHz	
Centre frequencies	5.3.2	C7 (see note 1)		C8 (see note 1)
Occupied Channel Bandwidth	5.3.3	C7		C8
Power, power density	5.3.4	C1	C2	C3, C4
Transmitter unwanted emissions outside the 5 GHz RLAN bands	5.3.5	C7 (see note 1)		C8 (see note 1)
Transmitter unwanted emissions within the 5 GHz RLAN bands	5.3.6	C1	C2	C3, C4
Receiver spurious emissions	5.3.7	C7 (see note 1)		C8 (see note 1)
Transmit Power Control (TPC)	5.3.4	n.a. (see note 2)	C2 (see note 1)	C3, C4 (see note 1)
Dynamic Frequency Selection (DFS)	5.3.8	n.a. (see note 2)	C5	C6 (see note 3)
Adaptivity	5.3.9	C7		C8
C1, C3: The lowest declared channel for every declared nominal channel bandwidth within this band. For the power density testing, it is sufficient to only perform this test using the lowest nominal channel bandwidth. C2, C4: The highest declared channel for every declared nominal channel bandwidth within this band. For the power density testing, it is sufficient to only perform this test using the lowest nominal channel bandwidth. C5, C6: One channel out of the declared channels for this frequency range. If more than one nominal channel bandwidth has been declared for this sub-band, testing shall be performed using the lowest and highest nominal channel bandwidth. C7, C8: One channel out of the declared channels for this sub-band. For Occupied Channel Bandwidth, testing shall be repeated for every declared nominal channel bandwidth within this sub-band. For Adaptivity, testing shall be performed using the highest nominal channel bandwidth.				
NOTE 1: In case of more than one channel plan has been declared, testing of these specific requirements need only be performed using one of the declared channel plans.				
NOTE 2: Testing is not required for nominal channel bandwidths that fall completely within the frequency range 5 150 MHz to 5 250 MHz.				
NOTE 3: Where the declared channel plan includes channels whose nominal channel bandwidth falls completely or partly within the 5 600 MHz to 5 650 MHz band, the tests for the <i>Channel Availability Check</i> (and where implemented, for the <i>Off-Channel CAC</i>) shall be performed on one of these channels in addition to a channel within the band 5 470 MHz to 5 600 MHz or within the band 5 650 MHz to 5 725 MHz.				

1.10. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 2 " and is documented in the Shenzhen HUAKE Testing Technology Co., Ltd. quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen HUAKE Testing Technology Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Frequency error	25 Hz	(1)
Transmitter power conducted	0.57 Db	(1)
Transmitter power Radiated	2.20 Db	(1)
Conducted spurious emission	1.60 Db	(1)
Radiated spurious emission	2.20 Db	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.



1.11. Equipments Used during the Test

Centre frequencies & RF output power & Power density & OCB & TPC						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	Spectrum analyzer	Agilent	N9020A	HKE-048	2024/02/20	2025/02/19
2	Signal generator	Agilent	N5182A	HKE-029	2024/02/20	2025/02/19
3	Signal generator	Agilent	83630A	HKE-028	2024/02/20	2025/02/19
4	RF automatic control unit	Tonscend	JS0806-2	HKE-060	2024/02/20	2025/02/19
5	Power Sensor	Agilent	E9300A	HKE-086	2024/02/20	2025/02/19
6	Temperature and humidity meter	Boyang	HTR-2	HKE-075	2024/02/20	2025/02/19
7	RF test software	Tonscend	V3.5.39	HKE-083	/	/

Adaptively & Receiver Blocking						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	Spectrum analyzer	R&S	FSP40	HKE-025	2024/02/20	2025/02/19
2	Wireless Communication Test Set	R&S	CMU200	HKE-026	2024/02/20	2025/02/19
3	Wireless Communication Test Set	R&S	CMW500	HKE-027	2024/02/20	2025/02/19
4	RF automatic control unit	Tonscend	JS0806-2	HKE-060	2024/02/20	2025/02/19
5	RF test software	Tonscend	V3.5.39	HKE-083	/	/

Transmitter spurious emissions & Receiver spurious emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	2024/02/21	2026/02/20
2	Horn antenna	Schwarzbeck	9120D	HKE-013	2024/02/21	2026/02/20
3	Receiver	R&S	ESR-7	HKE-010	2024/02/20	2025/02/19
4	Position controller	Taiwan MF	MF7802	HKE-011	2024/02/20	2025/02/19
5	Preamplifier	EMCI	EMC05184 5SE	HKE-015	2024/02/20	2025/02/19
6	Preamplifier	Agilent	83051A	HKE-016	2024/02/20	2025/02/19
7	High pass filter unit	Tonscend	JS0806-F	HKE-055	2024/02/20	2025/02/19
8	Spectrum analyzer	Agilent	N9020A	HKE-048	2024/02/20	2025/02/19
9	RSE Test Software	Tonscend	JS36-RSE 5.0.0	HKE -184	/	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



TEST CONDITIONS AND RESULTS

1.12. Centre frequencies

Limit

The actual centre frequency for any given channel declared by the manufacturer shall be maintained within the range $f_c \pm 20$ ppm.

Test Procedure

1. For equipment can operating without modulation
 - a Connected The UUT to the spectrum and operated in an unmodulated mode.
 - b Set the centre frequency of spectrum to the frequency which UUT operated.
 - c Max Hold and waiting the trace stabilized.
 - d Search the peak value of the power envelope and noted.
2. For equipment operating with modulation
 - a Connected The UUT to the spectrum.
 - b Set the centre frequency of spectrum to the frequency which UUT operated.
 - c Max Hold and waiting the trace stabilized.
 - d Search the peak value of the power envelope and noted.
 - e Move the marker in a positive frequency increment until the upper, (relative to the centre frequency), -10 dBc point is reached, note this point as f1.
 - f Move the marker in a negative frequency increment until the lower, (relative to the centre frequency), -10 dBc point is reached, note this point as VS20455 WPD-900-TX.
 - g The centre frequency is calculated as $(f1 + VS20455 WPD-900-TX) / 2$.
3. These measurements shall be performed under both normal and extreme test conditions.
4. One channel out of the declared channels for each sub-band shall be tested.



Test Results

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 a	CH36/ 5180MHz	5179.914354	16.53
5.5	-10			5179.973841	5.05
	+40			5179.965015	6.75
4.5	-10			5179.970434	5.71
	+40			5179.961276	7.48
Limit				20 ppm	
Result				PASS	

Test conditions		Mode	Test Channel / Frequency	Measured Result (MHz)	Frequency Deviation (ppm)
Voltage (V)	Temperature (°C)				
5.0	+25	802.11 n HT 20	CH36/ 5180MHz	5179.964308	6.89
5.5	-10			5179.970856	5.63
	+40			5179.968963	5.99
4.5	-10			5179.961726	7.39
	+40			5179.951505	9.36
Limit				20 ppm	
Result				PASS	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



1.13. Nominal Channel Bandwidth and Occupied Channel Bandwidth

LIMIT

The Nominal Channel Bandwidth for a single Operating Channel shall be 20 MHz

Alternatively, equipment may implement a lower Nominal Channel Bandwidth with a minimum of 5 MHz, providing they still comply with the Nominal Centre Frequencies defined in clause 4.2.1 (20 MHz raster).

The Occupied Channel Bandwidth shall be between 80 % and 100 % of the Nominal Channel Bandwidth. In case of smart antenna systems (devices with multiple transmit chains) each of the transmit chains shall meet this requirement.

The Occupied Channel Bandwidth might change with time/payload.

During a Channel Occupancy Time (COT), equipment may operate temporarily with an Occupied Channel Bandwidth of less than 80 % of its Nominal Channel Bandwidth with a minimum of 2 MHz

Test Procedure

1. Connect the UUT to the spectrum analyser and use the following settings:

Centre Frequency:	The centre frequency of the channel under test
Resolution Bandwidth:	100 kHz
Video Bandwidth:	300 kHz
Frequency Span:	2 × Nominal Bandwidth (e.g. 40 MHz for a 20 MHz channel)
Detector Mode:	Peak
Trace Mode:	Max Hold

2. When the trace is complete, capture the trace.
3. Find the peak value of the trace and place the analyser marker on this peak.
4. Use the 99 % bandwidth function of the spectrum analyser to measure the Occupied Channel Bandwidth of the UUT. This value shall be recorded.
5. Repeated steps 1 to 3 above in case of simultaneous transmissions in non-adjacent channels.
6. These measurements shall be performed only under normal operating conditions.
7. One channel out of the declared channels for each sub-band shall be tested.




TEST RESULTS

Mode	Channel	Frequency (MHz)	99% bandwidth (MHz)	Result
802.11 a	CH36	5180	16.255	Pass
802.11 n HT 20	CH36	5180	17.419	Pass


Note: Only the worst channel is reported for each modulation.



802.11a-5180MHz



802.11n HT20-5180MHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



1.14. RF output power, Transmit Power Control (TPC) and power density

LIMIT

The limits below are applicable to the system as a whole and in any possible configuration. Includes smart antenna systems (devices with multiple transmit chains).

In case of multiple (adjacent or non-adjacent) channels within the same sub-band, the total RF output power of all channels in that sub-band shall not exceed the limits defined below.

In case of multiple, non-adjacent channels operating in separate sub-bands, the total RF output power in each of the sub-bands shall not exceed the limits defined below.

TPC is not required for channels whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz.

For devices with TPC, the RF output power and the power density when configured to operate at the highest stated power level of the TPC range shall not exceed the levels given in table 1.

Devices are allowed to operate without TPC. See table 1 for the applicable limits in this case.

Table 1: Mean e.i.r.p. limits for RF output power and power density at the highest power level

Frequency range [MHz]	Mean e.i.r.p. limit [dBm]		Mean e.i.r.p. density limit [dBm/MHz]	
	with TPC	without TPC	with TPC	without TPC
5 150 to 5 350	23	20/23 (see note 1)	10	7/10 (see note 2)
5 470 to 5 725	30 (see note 3)	27 (see note 3)	17 (see note 3)	14 (see note 3)

NOTE 1: The applicable limit is 20 dBm, except for transmissions whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz, in which case the applicable limit is 23 dBm.

NOTE 2: The applicable limit is 7 dBm/MHz, except for transmissions whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz, in which case the applicable limit is 10 dBm/MHz.

NOTE 3: Slave devices without a Radar Interference Detection function shall comply with the limits for the band 5 250 MHz to 5 350 MHz.

For devices using TPC, the RF output power during a transmission burst when configured to operate at the lowest stated power level of the TPC range shall not exceed the levels given in table 2.

For devices without TPC, the limits in table 2 do not apply.

Table 2: Mean e.i.r.p. limits for RF output power at the lowest power level of the TPC range

Frequency range	Mean e.i.r.p. [dBm]
5 250 MHz to 5 350 MHz	17
5 470 MHz to 5 725 MHz	24 (see note)

NOTE: Slave devices without a Radar Interference Detection function shall comply with the limits for the band 5 250 MHz to 5 350 MHz.



1.14.1. RF output power at the highest power - PH

Test Procedure

1. The UUT shall be configured to operate at:
 - The highest stated transmitter output power level of the TPC range; or
 - The maximum transmitter output power level in case the equipment has no TPC feature.
2. For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle reference clause 5.4.4.2.1.1.2 ETSI EN 301 893 V2.2.1 (2024-11)
3. For equipment without continuous transmission capability and operating (or with the capability to operate) in only one sub-band reference clause 5.4.4.2.1.1.3 ETSI EN 301 893 V2.2.1 (2024-11)
4. For equipment without continuous transmission capability and having simultaneous transmissions in both sub-bands reference clause 5.4.4.2.1.1.4 ETSI EN 301 893 V2.2.1 (2024-11)
5. These measurements shall be performed under both normal and extreme test conditions.



Test Results

802.11a							
Test conditions		Channel/ Frequency	Measur power (dBm)	Antenna Gain (dBi)	e.i.r.p (dBm)	Limit (dBm)	Result
Temperature (°C)	Voltage (V)						
+25°C	5.0	36/5180	12.87	1	13.87	23	PASS
-10°C	5.5		12.34	1	13.34		
	4.5		11.55	1	12.55		
+40°C	5.5		11.67	1	12.67		
	4.5		12.52	1	13.52		

802.11 n HT 20							
Test conditions		Channel/ Frequency	Measur power (dBm)	Antenna Gain (dBi)	e.i.r.p (dBm)	Limit (dBm)	Result
Temperature (°C)	Voltage (V)						
+25°C	5.0	36/5180	12.44	1	13.44	23	PASS
-10°C	5.5		11.53	1	12.53		
	4.5		11.64	1	12.64		
+40°C	5.5		11.15	1	12.15		
	4.5		11.23	1	12.23		

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



1.14.2. RF output power at the lowest power level of the TPC range - PL

Test Procedure

1. The UUT shall be configured to operate at the lowest stated transmitter output power level of the TPC range.
2. For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle (e.g. Frame Based equipment) reference clause 5.4.4.2.1.2.2 ETSI EN 301 893 V2.2.1 (2024-11)
3. For equipment without continuous transmission capability and operating (or with the capability to operate) in only one sub-band reference clause 5.4.4.2.1.2.3 ETSI EN 301 893 V2.2.1 (2024-11)
4. For equipment without continuous transmission capability and having simultaneous transmissions in both sub-bands reference clause 5.4.4.2.1.2.4 ETSI EN 301 893 V2.2.1 (2024-11)
5. These measurements shall be performed under both normal and extreme test conditions.
6. This test is only required for equipment with a TPC feature.

Test Results

This test item is not applicable for the EUT without TPC featur.



1.15. Power density

Test Procedure

1. The UUT shall be configured to operate at:
 - The highest stated transmitter output power level of the TPC range; or
 - The maximum transmitter output power level in case the equipment has no TPC feature.
2. For equipment with continuous transmission capability or for equipment operating (or with the capability to operate) with a constant duty cycle (e.g. Frame Based equipment) reference clause 5.4.4.2.1.3.2 ETSI EN 301 893 V2.2.1 (2024-11).
3. For equipment without continuous transmission capability and without the capability to transmit with a constant duty cycle reference clause 5.4.4.2.1.3.3 ETSI EN 301 893 V2.2.1 (2024-11).
4. These measurements shall only be performed at normal test conditions.

Test Results

Mode	Channel/ Frequency (MHz)	Measured value (dBm/MHz)	Antenna Gain (dBi)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
802.11a	36/5180	0.19	1	1.19	10	Pass
802.11n HT 20	36/5180	-2.25	1	-1.25	10	Pass

Note: Only the worst channel is reported for each modulation.



802.11a-5180MHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11n HT20-5180MHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

1.16. Transmitter unwanted emissions

1.16.1. Transmitter unwanted emissions outside the 5 GHz RLAN bands

Limit

The level of unwanted emission shall not exceed the limits given in table 3.

Table 3: Transmitter unwanted emission limits outside the 5 GHz RLAN bands


Frequency range	Maximum power	Bandwidth
30 MHz to 47 MHz	-36 dBm	100 kHz
47 MHz to 74 MHz	-54 dBm	100 kHz
74 MHz to 87,5 MHz	-36 dBm	100 kHz
87,5 MHz to 118 MHz	-54 dBm	100 kHz
118 MHz to 174 MHz	-36 dBm	100 kHz
174 MHz to 230 MHz	-54 dBm	100 kHz
230 MHz to 470 MHz	-36 dBm	100 kHz
470 MHz to 862 MHz	-54 dBm	100 kHz
862 MHz to 1 GHz	-36 dBm	100 kHz
1 GHz to 5,15 GHz	-30 dBm	1 MHz
5,35 GHz to 5,47 GHz	-30 dBm	1 MHz
5,725 GHz to 26 GHz	-30 dBm	1 MHz

Test Procedure

1. The measurement procedure follows ETSI EN 301 893 V2.2.1 Sub-clause 5.4.5.2.2
2. The measurement shall only be performed at normal test conditions.
One channel out of the declared channels for each sub-band shall be tested.

Test Configuration

Effective Radiated Power measurement (30 MHz to 26 GHz)





TEST RESULTS

Remark: We tested at 802.11a/802.11n HT20 mode at the antenna single transmitting mode, and recorded the worst case 802.11n HT 20 mode at the single transmitting mode. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

802.11n HT 20, CH 36, Horizontal/Vertical


Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Below 1GHz:					
220.96	V	-76.93	-54	-22.93	PASS
229.48	V	-70.91	-54	-16.91	PASS
308.09	V	-77.00	-36	-41.00	PASS
445.25	V	-74.80	-36	-38.80	PASS
553.46	V	-77.32	-54	-23.32	PASS
836.38	V	-79.80	-54	-25.80	PASS
258.75	H	-78.91	-36	-42.91	PASS
275.60	H	-75.05	-36	-39.05	PASS
317.25	H	-78.63	-36	-42.63	PASS
449.16	H	-84.42	-36	-48.42	PASS
634.14	H	-73.81	-54	-19.81	PASS
870.89	H	-78.93	-54	-24.93	PASS
Note: 1.Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					



Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Above 1GHz:					
2037.27	V	-51.34	-30	-21.34	PASS
2242.77	V	-59.81	-30	-29.81	PASS
3499.16	V	-62.32	-30	-32.32	PASS
4378.30	V	-57.43	-30	-27.43	PASS
5278.28	V	-48.42	-30	-18.42	PASS
6166.79	V	-53.14	-30	-23.14	PASS
2257.08	H	-50.12	-30	-20.12	PASS
2691.08	H	-54.41	-30	-24.41	PASS
2935.56	H	-50.52	-30	-20.52	PASS
3855.34	H	-57.03	-30	-27.03	PASS
4753.68	H	-54.51	-30	-24.51	PASS
6675.24	H	-46.22	-30	-16.22	PASS
Note: 1. Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					

1.16.2. Transmitter unwanted emissions within the 5 GHz RLAN bands

LIMIT



NOTE: dBc is the spectral density relative to the maximum spectral power density of the transmitted signal.

Figure 1: Transmit spectral power mask

Test Procedure

1. The measurement procedure follows ETSI EN 301 893 V2.2.1 Sub-clause .4.6.2.1.
2. The measurement shall only be performed at normal test conditions.

Test Result

The test plots as follow:



802.11a



CH36



CH36

802.11n HT 20



CH36



CH36

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAJ, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

1.17. Receiver spurious emissions

The spurious emissions of the receiver shall not exceed the limits given in table 4.

Table 4: Spurious radiated emission limits


Frequency range	Maximum power	Measurement bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 26 GHz	-47 dBm	1 MHz

Test Procedure

1. The measurement procedure follows ETSI EN 301 893 V2.2.1 Sub-clause 5.4.7.2.2
2. The measurement shall only be performed at normal test conditions.
3. One channel out of the declared channels for each sub-band shall be tested.

Test Configuration

Effective Radiated Power measurement (30 MHz to 26 GHz)





TEST RESULTS

Remark: We tested at 802.11a/802.11n HT20 mode at the antenna single transmitting mode, and recorded the worst case 802.11n HT 20 mode at the single transmitting mode. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

802.11n HT 20, CH 36, Horizontal/Vertical

Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Below 1GHz:					
206.60	V	-79.01	-57	-22.01	PASS
256.06	V	-70.71	-57	-13.71	PASS
307.99	V	-78.52	-57	-21.52	PASS
435.95	V	-75.44	-57	-18.44	PASS
537.45	V	-73.22	-57	-16.22	PASS
828.65	V	-78.46	-57	-21.46	PASS
251.14	V	-76.33	-57	-19.33	PASS
279.74	H	-82.44	-57	-25.44	PASS
314.69	H	-80.11	-57	-23.11	PASS
443.40	H	-77.35	-57	-20.35	PASS
642.50	H	-74.62	-57	-17.62	PASS
850.65	H	-74.03	-57	-17.03	PASS
Note: 1. Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					



Fre. (MHz)	ANT. Pol.	Result (dBm)	Limit	Margin	Conclusion
Above 1GHz:					
2001.15	V	-78.06	-47	-31.06	PASS
2515.27	V	-77.80	-47	-30.80	PASS
3645.00	V	-68.41	-47	-21.41	PASS
4166.90	V	-76.02	-47	-29.02	PASS
5452.98	V	-68.56	-47	-21.56	PASS
5969.67	V	-70.56	-47	-23.56	PASS
2036.40	H	-72.42	-47	-25.42	PASS
2514.79	H	-78.84	-47	-31.84	PASS
3221.47	H	-76.12	-47	-29.12	PASS
4160.64	H	-77.63	-47	-30.63	PASS
4907.34	H	-77.21	-47	-30.21	PASS
6596.05	H	-79.53	-47	-32.53	PASS
Note: 1.Cable loss and antenna gain was combined in the calculated result. 2. Other point of the measurements are below 20dB from the limit.					



1.18. Dynamic Frequency Selection (DFS)

DFS parameters

Table D.1: DFS requirement values

Parameter	Value
Channel Availability Check Time	60 s (see note 1)
Minimum Off-Channel CAC Time	6 minutes (see note 2)
Maximum Off-Channel CAC Time	4 hours (see note 2)
Channel Move Time	10 s
Channel Closing Transmission Time	1 s
Non-Occupancy Period	30 minutes
NOTE 1: For channels whose nominal bandwidth falls completely or partly within the band 5 600 MHz to 5 650 MHz, the <i>Channel Availability Check Time</i> shall be 10 minutes.	
NOTE 2: For channels whose nominal bandwidth falls completely or partly within the band 5 600 MHz to 5 650 MHz, the <i>Off-Channel CAC Time</i> shall be within the range 1 to 24 hours.	

Table D.2: Interference threshold values

e.i.r.p. Spectral Density dBm/MHz	Value (see notes 1 and 2)
10	-62 dBm
NOTE 1: This is the level at the input of the receiver of an RLAN device with a maximum e.i.r.p. density of 10 dBm/MHz and assuming a 0 dBi receive antenna. For devices employing different e.i.r.p. spectral density and/or a different receive antenna gain G (dBi) the DFS threshold level at the receiver input follows the following relationship: DFS Detection Threshold (dBm) = -62 + 10 * e.i.r.p. Spectral Density (dBm/MHz) + G (dBi), however the DFS threshold level shall not be lower than -64 dBm assuming a 0 dBi receive antenna gain.	
NOTE 2: Slave devices with a maximum e.i.r.p. of less than 23 dBm do not have to implement radar detection.	

Table D.3: Parameters of the reference DFS test signal

Pulse width W [μs]	Pulse repetition frequency PRF [PPS]	Pulses per burst [PPB]
1	700	18




Table D.4: Parameters of radar test signals

Radar test signal # (see notes 1 to 3)	Pulse width W [μs]		Pulse repetition frequency PRF (PPS)		Number of different PRFs	Pulses per burst for each PRF (PPB) (see note 5)
	Min	Max	Min	Max		
1	0,5	5	200	1 000	1	10 (see note 6)
2	0,5	15	200	1 600	1	15 (see note 6)
3	0,5	15	2 300	4 000	1	25
4	20	30	2 000	4 000	1	20
5	0,5	2	300	400	2/3	10 (see note 6)
6	0,5	2	400	1 200	2/3	15 (see note 6)

NOTE 1: Radar test signals 1 to 4 are constant PRF based signals. See figure D.1. These radar test signals are intended to simulate also radars using a packet based Staggered PRF. See figure D.2.

NOTE 2: Radar test signal 4 is a modulated radar test signal. The modulation to be used is a chirp modulation with a ±2,5 MHz frequency deviation which is described below.



NOTE 3: Radar test signals 5 and 6 are single pulse based Staggered PRF radar test signals using 2 or 3 different PRF values. For radar test signal 5, the difference between the PRF values chosen shall be between 20 PPS and 50 PPS. For radar test signal 6, the difference between the PRF values chosen shall be between 80 PPS and 400 PPS. See figure D.3.

NOTE 4: Apart for the Off-Channel CAC testing, the radar test signals above shall only contain a single burst of pulses. See figures D.1, D.3 and D.4. For the Off-Channel CAC testing, repetitive bursts shall be used for the total duration of the test. See figures D.2 and D.5. See also clauses 4.7.2.2, 5.3.8.2.1.3.1 and 5.3.8.2.1.3.2.

NOTE 5: The total number of pulses in a burst is equal to the number of pulses for a single PRF multiplied by the number of different PRFs used.

NOTE 6: For the CAC and Off-Channel CAC requirements, the minimum number of pulses (for each PRF) for any of the radar test signals to be detected in the band 5 600 MHz to 5 650 MHz shall be 18.


Table D.5: Detection probability

Parameter	Detection Probability (P _d)	
	Channels whose nominal bandwidth falls partly or completely within the 5 600 MHz to 5 650 MHz band	Other channels
CAC, Off-Channel CAC	99,99 %	60 %
In-Service Monitoring	60 %	60 %


NOTE: P_d gives the probability of detection per simulated radar burst and represents a minimum level of detection performance under defined conditions. Therefore P_d does not represent the overall detection probability for any particular radar under real life conditions.

Test set-ups**Set-up A**


Set-up A is a set-up whereby the UUT is an RLAN device operating in master mode. Radar test signals are injected into the UUT. This set-up also contains an RLAN device operating in slave mode which is associated with the UUT.

**Figure 4: Set-up A****Set-up B**

Set-up B is a set-up whereby the UUT is an RLAN device operating in slave mode, with or without Radar Interference Detection function. This set-up also contains an RLAN device operating in master mode. The radar test signals are injected into the master device. The UUT (slave device) is associated with the master device.

**Figure 5: Set-up B****Set-up C**

The UUT is an RLAN device operating in slave mode with Radar Interference Detection function. Radar test signals are injected into the slave device. This set-up also contains an RLAN device operating in master mode. The UUT (slave device) is associated with the master device.

**Figure 6: Set-up C**



DFS technical requirements specifications

Follow table lists the DFS related technical requirements and their applicability for every operational mode. If the RLAN device is capable of operating in more than one operational mode then every operating mode shall be assessed separately.

Applicability of DFS requirements

Requirement	DFS Operational mode		
	Master	Slave without radar detection	Slave with radar detection (see table D.2, note 2)
Channel Availability Check	✓	Not required	✓ (see note 2)
Off-Channel CAC (see note 1)	✓	Not required	✓ (see note 2)
In-Service Monitoring	✓	Not required	✓
Channel Shutdown	✓	✓	✓
Non-Occupancy Period	✓	Not required	✓
Uniform Spreading	✓	Not required	Not required
NOTE 1: Where implemented by the manufacturer.			
NOTE 2: A slave with radar detection is not required to perform a CAC or Off-Channel CAC at initial use of the channel but only after the slave has detected a radar signal on the Operating Channel by In-Service Monitoring.			

TEST RESULTS

Testing is not required for nominal channel bandwidths that fall completely within the frequency range 5 150 MHz to 5 250 MHz. So this test item is not applicable for the EUT.





1.19. Adaptivity


Requirements and limits

When interference signal detected by relevant channel access mechanism UUT used. The UUT should stops transmissions on the current operating channel, apart from Short Control Signaling Transmissions with a maximum duty cycle of 5 % within an observation period of 50 ms,


Test Procedure

1. The measurement procedure follows the clause 5.3.9.2.1 of the ETSI EN 301 893 V2.2.1 (2024-11).
2. The inference signal used shall be a band limited noise signal with a 100 % duty cycle.
3. Testing shall be performed at one channel out of the declared channels for each sub-band and the highest nominal channel bandwidth.

Test Configuration



Adaptivity Test schematic graphic



Test Step 2 :We add the Additive white Gaussian noise (AWGN) as interference Signal



Test step 3 and Test step 3_2nd : We Repeat Test Step 2 and Test Step 2_2nd ,but We add the OFDM test signal as interference Signal

Test step 4 and Test step 4_2nd : We Repeat Test Step 2 and Test Step 2_2nd ,but We add LTE test signal as interference Signal

TEST RESULTS

Adaptivity 1

Test Mode	Test Channel	Priority Class	COT Num[n]	Max.COT [ms]	Limit [ms]	Min. Idel Time [ms]	Limit [ms]
802.11a	5180	2	868	1.912	<=6	0.037	>0.027
802.11n HT 20	5180	2	932	1.831	<=6	0.074	>0.027



Test Mode	Test Channel	Interference signal Type	Add interference signal Time[ms]	Interference signal Level [dBm/MHz]	Max.Short Control number[n]	Limit [n]	Max.Short Control Time [ms]	Limit [ms]
802.11a	5180	LTE	2000	-75	5	<=50	1.14	<2.5
802.11a	5180	OFDM	2000	-75	5	<=50	1.01	<2.5
802.11a	5180	AWGN	2000	-75	5	<=50	0.80	<2.5
802.11n HT 20	5180	LTE	2000	-75	5	<=50	1.06	<2.5
802.11n HT 20	5180	OFDM	2000	-75	5	<=50	0.67	<2.5
802.11n HT 20	5180	AWGN	2000	-75	5	<=50	0.76	<2.5



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11 a





n	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
B[n]	0	0	51	26	11	197	60	31	10	16	14	8	17	66	139	114	8720
P[n]	0	0	0.54	0.81	0.93	3.01	3.64	3.97	4.07	4.24	4.39	4.47	4.65	5.35	6.81	8.02	100
Limit	5	12	18.25	24.5	30.75	37	43.25	49.5	55.75	62	68.25	74.5	80.75	87	93.25	99.5	100

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Address: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11n HT20





n	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
B[n]	0	0	51	26	11	197	60	31	10	16	14	8	17	66	139	114	8720
P[n]	0	0	0.54	0.81	0.93	3.01	3.64	3.97	4.07	4.24	4.39	4.47	4.65	5.35	6.81	8.02	100
Limit	5	12	18.25	24.5	30.75	37	43.25	49.5	55.75	62	68.25	74.5	80.75	87	93.25	99.5	100

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Address: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



1.20. Receiver Blocking

Limits

ETSI EN 301 893 Sub-4.2.8.4

While maintaining the minimum performance criteria as defined in clause 4.2.8.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined in table 9.


Table 9: Receiver Blocking parameters

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)		Type of blocking signal
		Master or Slave with radar detection (see table D.2, note 2)	Slave without radar detection (see table D.2, note 2)	
P _{min} + 6 dB	5 100	-53	-59	Continuous Wave
P _{min} + 6 dB	4 900 5 000 5 975	-47	-53	Continuous Wave

NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined clause 4.2.8.3 in the absence of any blocking signal.

NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the same levels should be used at the antenna connector irrespective of antenna gain.

TEST CONFIGURATION:



TEST PROCEDURE

Please refer to ETSI EN 301 893 Sub-clause 4.2.8.2 for the measurement method..



TEST RESULTS

For 11a

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-59	10%	5%	PASS
	4900	-53	10%	4%	PASS
	5000	-53	10%	4%	PASS
	5975	-53	10%	6%	PASS

Pmin = -81dB

For 11n HT20

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5100	-59	10%	4%	PASS
	4900	-53	10%	5%	PASS
	5000	-53	10%	4%	PASS
	5975	-53	10%	6%	PASS

Pmin = -81dB

1.21. Adjacent channel selectivity

Limits

The limits defined in this clause apply when the equipment receives the wanted signal on a single channel and the occupied bandwidth of the interfering signal falls completely within a channel adjacent to this channel. Both channels have a nominal channel bandwidth as defined in clause 4.2.2.

Table 9: Adjacent channel selectivity parameters

Wanted signal mean power from companion device (dBm)	Interferer signal frequency offset range (MHz)	Interferer signal power (dBm) (see note 2)	Type of interferer signal
$P_{min} + 10$ dB	$20 \pm 0,2$	$P_{min} + 26$ dB	Same as the wanted signal with an equivalent occupied bandwidth
NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined clause 4.2.9.3 in the absence of any interfering signal.			
NOTE 2: The level specified for the interferer signal applies at the lowest data rate.			

TEST CONFIGURATION:




Figure 22: Test setup for receiver adjacent channel selectivity

TEST PROCEDURE

Please refer to ETSI EN 301 893 Sub-clause 5.4.11.2 for the measurement method..



TEST RESULTS

For 11a

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Interferer signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 10dB	5159.8	Pmin + 26dB	10%	6%	PASS
	5160.2		10%	5%	PASS
	5198.8		10%	4%	PASS
	5200.2		10%	3%	PASS

For 11n HT20

5180MHz

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm)	Limit(PER)	test value(PER)	Result
Pmin + 6dB	5159.8	-53	10%	4%	PASS
	5160.2	-47	10%	5%	PASS
	5199.8	-47	10%	6%	PASS
	5200.2	-47	10%	5%	PASS



1.22. User Access Restrictions

Requirement

The equipment shall be so constructed that settings (hardware and/or software) related to DFS shall not be accessible to the user if changing those settings result in the equipment no longer being compliant with the DFS requirements in EN301893 (clause 4.7) The above requirement includes the prevention of indirect access to any setting that impacts DFS.

Result

The EUT do not use the DFS Band and The customers will not obtain the information to set hardware and/ software related to DFS, if the product is on sales. So The EUT meets this requirement.



1.23. Geo-location capability

Requirement

Geo-location capability is a feature of the RLAN device to determine its geographical location with the purpose to configure itself according to the regulatory requirements applicable at the geographical location where it operates. The geo-location capability may be present in the equipment or in an external device (temporary) associated with the equipment operating at the same geographical location during the initial power up of the equipment. The geographical location may also be available in equipment already installed and operating at the same geographical location.



The geographical location determined by the equipment as defined in the above shall not be accessible to the user.

Result

This requirement only applies to equipment with geo-location capability, and the EUT do not support this function. So this requirement is not applicable for the EUT.



Test Setup Photos of the EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Addr: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




External and Internal Photos of the EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Address: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Address: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com



Address: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Addr: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



.....End of Report.....