

TEST REPORT N°: KSK-ESH-P24071264B-3

EN 300 328 RF Test Report

Applicant:	K-tronics (Suzhou) Technology Co., Ltd.
Address:	No.1088, Dajing Road, Economic and Technological Development Zone, Wujiang District, Suzhou, Jiangsu Province, 215200, P.R. China
Manufacturer:	i3-TECHNOLOGIES NV
Address:	Nijverheidslaan 60, 8540 Deerlijk, BELGIUM
This document includes : 74 pages	

Product Name:	Interactive Flat Panel	
Model Number:	i3TOUCH V-ONE 86, i3TOUCH V-ONE 86xxxxxxxx (x=0-9, A-Z, a-z, +, - (hyphen), /, \ or blank)	
Brand:	i3TOUCH	
Rated Voltage/Power	100-240V~, 50/60Hz, 4.8A	
Received Date:	Jul.15, 2024	
Test Date:	Jul.15 to Sep.03, 2024	
Applicable Standards:	EN 300 328 V2.2.2(2019-07)	
Clause Examined :	All Clauses Relevant	

Test Location: Building C, No. 829, Xin Zhuan Road, Shanghai, CHINA

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Test done by:	Approved by:
Name: Yuan ZHANG	Name: Sean YU
Title: Project Engineer	Title: RF Supervisor
Date: Sep.06, 2024	Date: Sep.06, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 1 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

Table of Contents

Release Control Record	4
1 Summary of Test Results	5
1.1 Test Instruments	6
1.2 Measurement Uncertainty	7
1.3 Maximum Measurement Uncertainty	7
1.4 Modification Record	7
2 General Information	8
2.1 General Description of EUT	8
2.2 Description of Test Modes	8
2.2.1 Test Mode Applicability:	10
2.2.2 Test Condition:	10
2.3 Description of Support Units	11
2.4 General Description of Applied Standards	11
3 Test Procedure and Results	12
3.1 RF Output Power	12
3.1.1 Limits of RF Output Power	12
3.1.2 Test Procedures	12
3.1.3 Deviation from Test Standard	12
3.1.4 Test Setup	12
3.1.5 Test Results	13
3.2 Hopping Frequency Separation, Accumulated Transmit time, Frequency Occupation and Hopping Sequence	14
3.2.1 Limit	17
3.2.2 Test Procedures	18
3.2.3 Deviation of Test Standard	18
3.2.4 Test Setup	18
3.2.5 Test Results	19
3.3 Adaptivity (Adaptive Frequency Hopping)	41
3.3.1 Limit of Adaptive	42
3.3.2 Test Procedure	45
3.3.3 Deviation from Test Standard	45
3.3.4 Test Setup Configuration	45
3.3.5 List of Measurements	46
3.3.6 Test Result	46
3.4 Occupied Channel Bandwidth	47
3.4.1 Limit of Occupied Channel Bandwidth	47
3.4.2 Test Procedure	47
3.4.3 Deviation from Test Standard	47
3.4.4 Test Setup	48
3.4.5 Test Results	49
3.5 Transmitter Unwanted Emissions in the Out-of-band Domain	49
3.5.1 Limits of Transmitter Unwanted Emissions in the Out-of-band Domain	53
3.5.2 Test Procedure	53
3.5.3 Deviation from Test Standard	53
3.5.4 Test Setup	54
3.5.5 Test Results	55
3.6 Transmitter Spurious Emissions in the spurious domain	56
3.6.1 Limits of Transmitter Spurious Emissions	58



TEST REPORT N°: KSK-ESH-P24071264B-3

3.6.2	Test Procedure	58
3.6.3	Deviation from Test Standard	59
3.6.4	Test Setup	59
3.6.5	Test Results	60
3.7	Receiver Spurious Emissions	63
3.7.1	Limit of Receiver Spurious Radiation	63
3.7.2	Test Procedure	63
3.7.3	Deviation from Test Standard	63
3.7.4	Test Setup	64
3.7.5	Test Results	65
3.8	Receiver Blocking	66
3.8.1	Limit of Receiver Blocking	66
3.8.2	Test Procedure	68
3.8.3	Deviation from Test Standard	68
3.8.4	Test Setup Configuration	68
3.8.5	Test Results	69
4	Photographs of the Test Configuration	71
5	Photographs of the EUT	71
APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB		74



TEST REPORT N°: KSK-ESH-P24071264B-3

Release Control Record

Issue No.	Description	Date Issued
KSK-ESH-P24071264B-3	Original release	Sep.06, 2024

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 4 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

1 Summary of Test Results

The EUT has been tested according to the following specifications:

EN 300 328 V2.2.2		
Clause	Test Parameter	Results
4.3.2.2	RF Output Power	Pass
4.3.2.4	Hopping Frequency Separation	Pass
4.3.2.5	Accumulated Transmit time, Frequency Occupation and Hopping Sequence	Pass
4.3.2.6	Adaptivity (Adaptive Equipment using modulation other than FHSS)	Not Applicable (Note 1)
4.3.2.7	Occupied Channel Bandwidth	Pass
4.3.2.8	Transmitter Unwanted Emissions in the out-of-band Domain	Pass
4.3.2.9	Transmitter Unwanted Emissions in the Spurious Domain	Pass
4.3.2.10	Receiver Spurious Emissions	Pass
4.3.2.11	Receiver Blocking	Pass
4.3.2.12	Geo-location capability	Not Applicable (Note 2)

Note1: These requirements do not apply for equipment with a maximum declared RF Output power of less than 10 dBm EIRP or for equipment when operating in a mode where the RF Output power is less than 10 dBm EIRP.

Note2: This product has no Geo-location capability, so the test is not applicable.

Special Comments: None.

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 5 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

1.1 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Double Ridged Broadband Horn (30MHz-1.5GHz)	Schwarzbeck	VULB9168	E1A1012	Aug.17,23	Aug.16,25
Horn Antenna (1GHz -18GHz)	Schwarzbeck	BBHA9120D	E1A1041	Apr.11,23	Apr.10,25
Pre-Amplifier(9kHz-1GHz)	Tonscend	TAP9K3G40	E1A2012	Apr.19,23	Apr.18,25
Pre-Amplifier(1GHz-18GHz)	Tonscend	TAP01018050	E1A2013	Mar.01,24	Feb.28,25
Pre-Amplifier(18GHz-40GHz)	Tonscend	TAP18040048	E1A2014	May.24,24	May.23,25
Pre-Amplifier(9kHz-1GHz)	SONOMA	11909A(310)	E1A2007	Feb.18,24	Feb.17,25
Pre-Amplifier(1GHz-26.5GHz)	Agilent	8449B	E1A2002	Feb.18,24	Feb.17,25
Signal Generator	Keysight	N5171B	E1S9016	Feb.19,24	Feb.18,25
Signal Generator	Keysight	N5182B	E1S9017	Feb.19,24	Feb.18,25
Wireless Connectivity Tester	R&S	CMW270	E1S9021	Oct.28,22	Oct.26,24
Spectrum Analyzer	R&S	FSQ	E1S1005	Aug.12,24	Aug.11,25
Spectrum Analyzer	Keysight	N9030B	E1S1003	Sep.14,23	Sep.13,24
Spectrum Analyzer	Keysight	N9020A	E1S1004	Mar.01,24	Feb.28,25
RF Control Unit	Toscend	JS0806-2	E1C5003	NCR	NCR
DC Power supply	Chroma	62024p-80-60	S1S1009	Mar.21,24	Mar.20,25
Humidity&Temp Programmable Tester	ESPEC	SE TH-Z-042U	C1TH002	Jun.06,24	Jun.05,25
Test Software	Toscend	JS1120-3	N/A	N/A	N/A
Test Software	Toscend	JS36-RSE	N/A	N/A	N/A



TEST REPORT N°: KSK-ESH-P24071264B-3

1.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 1.132 \times 10^{-4} \%$
RF output power, conducted	$\pm 1.017 \text{ dB}$
Power Spectral Density, conducted	$\pm 1.017 \text{ dB}$
Unwanted Emissions, conducted	$\pm 2.855 \text{ dB}$
All emissions, radiated	$\pm 2.855 \text{ dB}$
Temperature	$\pm 0.7^\circ \text{C}$
Supply voltages	$\pm 0.04 \%$
Time	$\pm 5 \%$

1.3 Maximum Measurement Uncertainty

For the test methods, according to EN 300 328 standard, the measurement uncertainty figures shall be calculated in accordance with ETR 100 028-1 [4] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Maximum measurement uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 5 \%$
RF output power, conducted	$\pm 1,5 \text{ dB}$
Power Spectral Density, conducted	$\pm 3 \text{ dB}$
Unwanted Emissions, conducted	$\pm 3 \text{ dB}$
All emissions, radiated	$\pm 6 \text{ dB}$
Temperature	$\pm 1^\circ \text{C}$
Supply voltages	$\pm 3 \%$
Time	$\pm 5 \%$

1.4 Modification Record

There were no modifications required for compliance.

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 7 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

2 General Information

2.1 General Description of EUT

Product	Interactive Flat Panel
Brand	i3TOUCH
Model	i3TOUCH V-ONE 86, i3TOUCH V-ONE 86xxxxxxxx (x=0-9, A-Z, a-z, +, - (hyphen), /, \ or blank)
Model difference	All models are identical to each other except for different model name.
Nominal Voltage	100-240V~, 50/60Hz, 4.8A
Temperature Operating Range	+0deg.c to +40deg.c
Modulation Type	Bluetooth BR+EDR
Modulation Technology	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Adaptive/Non-Adaptive	☐ non-adaptive Equipment ☒ adaptive Equipment without the possibility to switch to a non-adaptive mode ☐ adaptive Equipment which can also operate in a non-adaptive mode
EIRP Power (Measured Max. Average)	8.33dBm
Antenna Type	External Antenna
Antenna Gain	2.80dBi
Data Cable Supplied	NA

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
2. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
3. The EUT contains two wireless modules.
The wireless module of model WCT1DR2201D supports BT/WIFI function.
The wireless module of model WC0NR2201 supports WIFI function.
The two wireless modules can work at the same time.



TEST REPORT N°: KSK-ESH-P24071264B-3

2.2 Description of Test Modes

79 channels are provided for Bluetooth.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
0	2402 MHz	27	2429 MHz	54	2456 MHz
1	2403 MHz	28	2430 MHz	55	2457 MHz
2	2404 MHz	29	2431 MHz	56	2458 MHz
3	2405 MHz	30	2432 MHz	57	2459 MHz
4	2406 MHz	31	2433 MHz	58	2460 MHz
5	2407 MHz	32	2434 MHz	59	2461 MHz
6	2408 MHz	33	2435 MHz	60	2462 MHz
7	2409 MHz	34	2436 MHz	61	2463 MHz
8	2410 MHz	35	2437 MHz	62	2464 MHz
9	2411 MHz	36	2438 MHz	63	2465 MHz
10	2412 MHz	37	2439 MHz	64	2466 MHz
11	2413 MHz	38	2440 MHz	65	2467 MHz
12	2414 MHz	39	2441 MHz	66	2468 MHz
13	2415 MHz	40	2442 MHz	67	2469 MHz
14	2416 MHz	41	2443 MHz	68	2470 MHz
15	2417 MHz	42	2444 MHz	69	2471 MHz
16	2418 MHz	43	2445 MHz	70	2472 MHz
17	2419 MHz	44	2446 MHz	71	2473 MHz
18	2420 MHz	45	2447 MHz	72	2474 MHz
19	2421 MHz	46	2448 MHz	73	2475 MHz
20	2422 MHz	47	2449 MHz	74	2476 MHz
21	2423 MHz	48	2450 MHz	75	2477 MHz
22	2424 MHz	49	2451 MHz	76	2478 MHz
23	2425 MHz	50	2452 MHz	77	2479 MHz
24	2426 MHz	51	2453 MHz	78	2480 MHz
25	2427 MHz	52	2454 MHz	-	-
26	2428 MHz	53	2455 MHz	-	-



TEST REPORT N°: KSK-ESH-P24071264B-3

2.2.1 Test Mode Applicability:

EUT Configure Mode	Applicable to									Description
	ROP	FHS	ATT/HO/FS	AD	OCB	EOB	SE<1G	SE>1G	RB	
-	√	√	√	--	√	√	√	√	√	-

Where **ROP**: RF Output Power

ATT/HO/FS: Accumulated Transmit Time, Frequency Occupation and Hopping Sequence

FHS: Hopping Frequency Separation

OCB: Occupied Channel Bandwidth

AD: Adaptivity (Channel Access Mechanism)

EOB: Transmitter unwanted emissions in the out-of-band domain

SE<1G: Unwanted Emissions in the Spurious Domain below 1 GHz

SE>1G: Unwanted Emissions in the Spurious Domain above 1 GHz

RB: Receiver Blocking

NOTE: The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **X-plane(Above 1GHz) & . Y-plane(Below 1GH**

2.2.2 Test Condition:

Applicable to	Normal Environmental Conditions	Normal Input Power	Extreme Temperature conditions
ROP	25deg. C, 60%RH	AC 230V	√
FHS	25deg. C, 60%RH	AC 230V	-
ATT/HO/FS	25deg. C, 60%RH	AC 230V	-
AD	25deg. C, 60%RH	-	-
OCB	25deg. C, 60%RH	AC 230V	-
EOB	25deg. C, 60%RH	AC 230V	-
SE<1G	23deg. C, 65%RH	AC 230V	-
SE>1G	21deg. C, 65%RH	AC 230V	-
RB	25deg. C, 60%RH	AC 230V	-

Extreme Temperature conditions	
Tmin	0deg. C
Tmax	+40deg. C

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 10 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

2.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND/Manufacturer	MODEL NO.
1	PC	ThinkPad	L470

2.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

EN 300 328 V2.2.2 (2019-07)

All related test items have been performed and recorded as per the above standard.

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 11 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

3 Test Procedure and Results

3.1 RF Output Power

3.1.1 Limits of RF Output Power

Condition	Frequency Band	Limit (e.i.r.p)
Under all test conditions	2400 ~ 2483.5 MHz	AV: 20dBm

3.1.2 Test Procedures

Refer to chapter 5.4.2.2 of EN 300 328 V2.2.2.


Measurement Method	
☒ Conducted measurement	☐ Radiated measurement

3.1.3 Deviation from Test Standard

No deviation.

3.1.4 Test Setup

The measurements for RF output power was performed at both normal environmental conditions and at the extremes of the operating temperature. The measurement was performed at the lowest, the middle, and the highest channel.





TEST REPORT N°: KSK-ESH-P24071264B-3

3.1.5 Test Results


Test Condition	Test Mode	Antenna	Channel [MHz]	EIRP [dBm]	Limit [dBm]	Verdict
NTNV	DH5	Ant1	Hop	7.01	20	PASS
	2DH5	Ant1	Hop	8.21	20	PASS
	3DH5	Ant1	Hop	8.33	20	PASS
LTVN	DH5	Ant1	Hop	7.03	20	PASS
	2DH5	Ant1	Hop	8.13	20	PASS
	3DH5	Ant1	Hop	8.33	20	PASS
HTNV	DH5	Ant1	Hop	7.05	20	PASS
	2DH5	Ant1	Hop	8.23	20	PASS
	3DH5	Ant1	Hop	8.21	20	PASS




TEST REPORT N°: KSK-ESH-P24071264B-3

3.1.6 Test Graphs


NTNV_DH5_Ant1_Hop



NTNV_2DH5_Ant1_Hop



NTNV_3DH5_Ant1_Hop



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


LTNV_DH5_Ant1_Hop



LTNV_2DH5_Ant1_Hop



LTNV_3DH5_Ant1_Hop



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


HTNV_DH5_Ant1_Hop



HTNV_2DH5_Ant1_Hop



HTNV_3DH5_Ant1_Hop



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3

3.2 Hopping Frequency Separation, Accumulated Transmit time, Frequency Occupation and Hopping Sequence

3.2.1 Limit

Accumulated Transmit time	
☐	Non adaptive frequency hopping systems(Non-AFH): Accumulated Transmit time · 15 ms in (15 ms × N min. number of hopping frequencies)
☒	Adaptive frequency hopping systems(AFH): Accumulated Transmit time · 400 ms in (400 ms × N min. number of hopping frequencies)

Frequency Occupation	
☐	Non adaptive frequency hopping systems(Non-AFH): Option 1: Frequency Occupation · one in (4 × dwell time per hop ×N actual number of hopping frequencies in use) Option 2: Occupation probability for each frequency shall be between ((1 / U) × 25 %) and 77 % where U is the number of hopping frequencies in use.
☒	Adaptive frequency hopping systems(AFH): Option 1: Frequency Occupation · one in (4 × dwell time per hop ×N actual number of hopping frequencies in use) Option 2: Occupation probability for each frequency shall be between ((1 / U) × 25 %) and 77 % where U is the number of hopping frequencies in use.

Hopping Sequence	
☐	Non adaptive frequency hopping systems(Non-AFH): Hopping sequence · N hopping frequencies N · Max (15, 15/min. hopping frequency separation (MHz))
☒	Adaptive frequency hopping systems(AFH): Hopping sequence · N hopping frequencies N · Max (15, 15/min. hopping frequency separation (MHz)) Operating over a minimum of 70% of the frequency band 2.400 - 2.4835 GHz.

Hopping Frequency Separation	
☐	Non adaptive frequency hopping systems(Non-AFH): · max (Occupied channel Bandwidth, 100 kHz)
☒	Adaptive frequency hopping systems(AFH): · 100 kHz



TEST REPORT N°: KSK-ESH-P24071264B-3

3.2.2 Test Procedures

Refer to chapter 5.4.4.2 and 5.4.5.2 of EN 300 328 V2.2.2.

Measurement Method	
☒ Conducted measurement	☐ Radiated measurement

3.2.3 Deviation of Test Standard

No deviation.

3.2.4 Test Setup

The test setup has been constructed as the normal test condition. The measurement was performed at the lowest, the middle, and the highest channel.





TEST REPORT N°: KSK-ESH-P24071264B-3

3.2.5 Test Results

Accumulated Transmit Time

Test Mode	Antenna	Channel [MHz]	Accumulated Transmit Time [ms]	Limit[ms]	Verdict
DH1	Ant1	Hop_2402	116	400	PASS
		Hop_2480	112	400	PASS
DH3	Ant1	Hop_2402	290	400	PASS
		Hop_2480	242	400	PASS
DH5	Ant1	Hop_2402	202	400	PASS
		Hop_2480	376	400	PASS
2DH1	Ant1	Hop_2402	122	400	PASS
		Hop_2480	122	400	PASS
2DH3	Ant1	Hop_2402	190	400	PASS
		Hop_2480	321	400	PASS
2DH5	Ant1	Hop_2402	347	400	PASS
		Hop_2480	346	400	PASS
3DH1	Ant1	Hop_2402	66	400	PASS
		Hop_2480	68	400	PASS
3DH3	Ant1	Hop_2402	243	400	PASS
		Hop_2480	264	400	PASS
3DH5	Ant1	Hop_2402	289	400	PASS
		Hop_2480	378	400	PASS



TEST REPORT N°: KSK-ESH-P24071264B-3

Frequency Occupation

Test Mode	Antenna	Channel [MHz]	Frequency Occupation times [N]	Limit [N.]	Verdict
DH1	Ant1	Hop_2402	1	1	PASS
		Hop_2480	2	1	PASS
DH3	Ant1	Hop_2402	1	1	PASS
		Hop_2480	1	1	PASS
DH5	Ant1	Hop_2402	4	1	PASS
		Hop_2480	1	1	PASS
2DH1	Ant1	Hop_2402	2	1	PASS
		Hop_2480	1	1	PASS
2DH3	Ant1	Hop_2402	2	1	PASS
		Hop_2480	2	1	PASS
2DH5	Ant1	Hop_2402	3	1	PASS
		Hop_2480	1	1	PASS
3DH1	Ant1	Hop_2402	1	1	PASS
		Hop_2480	1	1	PASS
3DH3	Ant1	Hop_2402	2	1	PASS
		Hop_2480	1	1	PASS
3DH5	Ant1	Hop_2402	1	1	PASS
		Hop_2480	1	1	PASS



TEST REPORT N°: KSK-ESH-P24071264B-3

Hopping Sequence

Test Mode	Antenna	Channel	Hop. [Num.]	Limit [Num.]	Band Use [%]	Limit [%]	Verdict
DH5	Ant1	Hop	79	15	95.43	70	PASS
2DH5	Ant1	Hop	79	15	95.98	70	PASS
3DH5	Ant1	Hop	79	15	95.97	70	PASS

Hopping Frequency Separation


Test Mode	Antenna	Channel [MHz]	Channel Separation [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	0.976	0.100	PASS
2DH5	Ant1	Hop	1.130	0.100	PASS
3DH5	Ant1	Hop	1.022	0.100	PASS




TEST REPORT N°: KSK-ESH-P24071264B-3

3.2.6 Test Graphs Accumulated Transmit Time


DH1_Ant1_Hop_2402



DH1_Ant1_Hop_2480



DH3_Ant1_Hop_2402



Bureau Veritas ADT (Shanghai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


2DH1_Ant1_Hop_2402



2DH1_Ant1_Hop_2480



2DH3_Ant1_Hop_2402



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


3DH1_Ant1_Hop_2402



3DH1_Ant1_Hop_2480



3DH3_Ant1_Hop_2402



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


3DH3_Ant1_Hop_2480



3DH5_Ant1_Hop_2402



3DH5_Ant1_Hop_2480




Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China



Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



DH3_Ant1_Hop_2402



DH3_Ant1_Hop_2480



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China


Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



DH5_Ant1_Hop_2402




Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China



Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



DH5_Ant1_Hop_2480



2DH1_Ant1_Hop_2402



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China


Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



2DH1_Ant1_Hop_2480




Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China



Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



2DH3_Ant1_Hop_2402



2DH3_Ant1_Hop_2480



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China


Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



2DH5_Ant1_Hop_2402




Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China



Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



2DH5_Ant1_Hop_2480



3DH1_Ant1_Hop_2402



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China


Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



3DH1_Ant1_Hop_2480




Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China



Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



3DH3_Ant1_Hop_2402



3DH3_Ant1_Hop_2480


Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China



Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3



3DH5_Ant1_Hop_2480



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China


Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3

Hopping Sequence


DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3

Hopping Frequency Separation


DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



TEST REPORT N°: KSK-ESH-P24071264B-3

3.3 Adaptivity (Adaptive Frequency Hopping)

This requirement does not apply to non-adaptive equipment or adaptive equipment operating in a non-adaptive mode providing the equipment complies with the requirements and/or restrictions applicable to non-adaptive equipment.

In addition, this requirement does not apply for equipment with a maximum declared RF Output power level of less than 10 dBm e.i.r.p. or for equipment when operating in a mode where the RF Output power is less than 10 dBm e.i.r.p.

3.3.1 Limit of Adaptive

Applicability of adaptive requirements and limit for wide band modulation techniques Interference threshold level

Requirement	Operational Mode			
	Non-LBT based Detect and Avoid	LBT based Detect and Avoid		
		Frame Based Equipment	Load Based Equipment (Base on 'Spectrum Sharing' mechanisms)	Load Based Equipment (Not using any of the mechanisms referenced)
Minimum Clear Channel Assessment (CCA) Time	NA	18 us (see note 1)	(see note 2)	18 us (see note 1)
Maximum Channel Occupancy (COT) Time	40 ms	1 ms to 10 ms	(see note 2)	13ms
Minimum Idle Period	5us	5% of COT	(see note 2)	18us (see note 3)
Extended CCA check	NA	NA	(see note 2)	18us~160us
Short Control Signalling Transmissions	Maximum duty cycle of 10 % within an observation period of 50 ms (see note 4)			

NOTE 1: The CCA time used by the equipment shall be declared by the supplier.

NOTE 2: Load Based Equipment may implement an LBT based spectrum sharing mechanism based on the Clear Channel Assessment (CCA) mode using energy detect, as described in IEEE 802.11™-2012 clause 9, clause 10, clause 16, clause 17, clause 19 and clause 20, or in IEEE 802.15.4™-2011 [i.4], clause 4, clause 5 and clause 8

NOTE 3: The Idle Period in between transmissions is considered to be the CCA or the Extended CCA check as there are no transmissions during this period.

NOTE 4: Adaptive equipment may or may not have Short Control Signalling Transmissions



TEST REPORT N°: KSK-ESH-P24071264B-3

Threshold Level for Non-LBT based Detect and Avoid	
Maximum transmit power (P _H) EIRP dBm	Threshold level (TL) (see notes 1 and 2)
20	-70 dBm / MHz
NOTE 1: For a 20 dBm e.i.r.p. transmitter the detection threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G)	
NOTE 2: For power levels less than 20 dBm e.i.r.p., the detection threshold level may be relaxed to: $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW} / P_{out})$; (Pout in mW e.i.r.p.)	

Unwanted signal parameters for Non-LBT based Detect and Avoid		
Wanted signal mean power from companion device (dBm)	Unwanted signal frequency (MHz)	Unwanted CW signal power (dBm)
-30	2 395 or 2 488,5 (see note 1)	-35 (see note 2)
NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz.		
NOTE 2: The level specified is the level in front of the UUT antenna. In case of conducted measurements, this level has to be corrected by the actual antenna assembly gain.		

Threshold Level for LBT based Detect and Avoid (Frame Based Equipment)	
Maximum transmit power (P _H) EIRP dBm	Threshold level (TL) (see notes 1 and 2)
20	-70 dBm / MHz
NOTE 1: For a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G)	
NOTE 2: For power levels less than 20 dBm e.i.r.p. the CCA threshold level may be relaxed to: $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW} / P_{out})$; (Pout in mW e.i.r.p.)	



TEST REPORT N°: KSK-ESH-P24071264B-3

Unwanted signal parameters for LBT based Detect and Avoid (Frame Based Equipment)		
Wanted signal mean power from companion device	Unwanted signal frequency (MHz)	Unwanted signal power (dBm)
sufficient to maintain the link (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 3)
NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.		
NOTE 2: A typical value which can be used in most cases is -50 dBm/MHz.		
NOTE 3: The level specified is the level in front of the UUT antenna. In case of conducted measurements, this level has to be corrected by the actual antenna assembly gain.		

Threshold Level for LBT based Detect and Avoid (Load Based Equipment)	
Maximum transmit power (P _H) EIRP dBm	Threshold level (TL) (see notes 1 and 2)
20	-70 dBm / MHz
NOTE 1: For a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G)	
NOTE 2: For power levels less than 20 dBm e.i.r.p. the CCA threshold level may be relaxed to: $TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW} / P_{out}) ; (P_{out} \text{ in mW e.i.r.p.})$	

Unwanted signal parameters for LBT based Detect and Avoid (Load Based Equipment)		
Wanted signal mean power from companion device	Unwanted signal frequency (MHz)	Unwanted signal power (dBm)
sufficient to maintain the link (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 3)
NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.		
NOTE 2: A typical value which can be used in most cases is -50 dBm/MHz.		
NOTE 3: The level specified is the level in front of the UUT antenna. In case of conducted measurements, this level has to be corrected by the actual antenna assembly gain.		

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 44 of 74		
TEST REPORT EN 300 328 Ver1.0		

TEST REPORT N°: KSK-ESH-P24071264B-3

3.3.2 Test Procedure


Refer to chapter 5.4.6.2 of EN 300 328 V2.2.2.

Measurement Method	
☒ Conducted measurement	☐ Radiated measurement

3.3.3 Deviation from Test Standard

No deviation.

3.3.4 Test Setup Configuration





TEST REPORT N°: KSK-ESH-P24071264B-3

3.3.5 List of Measurements

Clause	Test Parameter	Remarks	Pass/Fail
4.3.2.6.3.2.2	Adaptive (Frame Based Equipment)	Not Applicable	NA
4.3.2.6.3.2.3	Adaptive (Load Based Equipment)	Not Applicable	NA
4.3.2.6.4	Short Control Signalling Transmissions	Not Applicable	NA

3.3.6 Test Result

☐ Not applicable to non-adaptive equipment or adaptive equipment operating in a non-adaptive mode
☒ Not applicable to equipment with RF output power is less than 10 dBm e.i.r.p.
☐ Refer to below test result

3.3.6.1 Adaptive Result

☐ Not applicable to non-adaptive equipment or adaptive equipment operating in a non-adaptive mode
☒ Not applicable to equipment with RF output power is less than 10 dBm e.i.r.p.
☐ Refer to below test result



TEST REPORT N°: KSK-ESH-P24071264B-3

3.4 Occupied Channel Bandwidth

3.4.1 Limit of Occupied Channel Bandwidth

Condition		Limit
All types of equipment		Shall fall completely within the band 2400 to 2483.5 MHz.
Additional requirement	For non-adaptive using wide band modulations other than FHSS system and e.i.r.p > 10dBm.	Less than 20MHz
	For non-adaptive Frequency Hopping system and e.i.r.p > 10dBm.	Less than 5MHz

3.4.2 Test Procedure

1. Refer to chapter 5.4.7.2 of EN 300 328 V2.2.2.
2. The measurement shall be performed only on the lowest and the highest frequency within the stated frequency range.
3. The test procedure shall be as follows:

Step 1:

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	: Channel under test
Resolution BW	: 1 % of the span
Video BW	: 3 × RBW
Frequency Span	: 2 × Nominal Channel Bandwidth
Detector	: RMS
Trace Mode	: Max Hold
Sweep Time	: 1 s

Step 2:

Save the trace data to a file for further analysis by a computing device using an appropriate software application or program.

Step 3:

Use the 99 % bandwidth function of the spectrum analyzer to measure the Occupied Channel Bandwidth of the EUT.

Measurement	
☒ Conducted measurement	☐ Radiated measurement

3.4.3 Deviation from Test Standard

No deviation.



TEST REPORT N°: KSK-ESH-P24071264B-3

3.4.4 Test Setup

These measurements only were performed at normal test conditions. The measurement shall be performed only on the lowest and the highest frequency within the stated frequency range. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator.





TEST REPORT N°: KSK-ESH-P24071264B-3

3.4.5 Test Results

Test Mode	Antenna	Channel [MHz]	OCB[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.87849	2401.5665	2402.4450	2400 to 2483.5	PASS
		2441	0.87852	2440.5648	2441.4434	2400 to 2483.5	PASS
		2480	0.87801	2479.5652	2480.4432	2400 to 2483.5	PASS
2DH5	Ant1	2402	1.1810	2401.4145	2402.5955	2400 to 2483.5	PASS
		2441	1.1807	2440.4142	2441.5949	2400 to 2483.5	PASS
		2480	1.1824	2479.4137	2480.5961	2400 to 2483.5	PASS
3DH5	Ant1	2402	1.1941	2401.4298	2402.6239	2400 to 2483.5	PASS
		2441	1.1939	2440.4293	2441.6232	2400 to 2483.5	PASS
		2480	1.1943	2479.4294	2480.6237	2400 to 2483.5	PASS

Note:FL is the lowest frequency of the 99% occupied bandwidth of power envelope.

FH is the highest frequency of the 99% occupied bandwidth of power envelope.


Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 49 of 74		
TEST REPORT EN 300 328 Ver1.0		




TEST REPORT N°: KSK-ESH-P24071264B-3

3.4.1 Test Graphs


DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司

No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3

3.5 Transmitter Unwanted Emissions in the Out-of-band Domain

3.5.1 Limits of Transmitter Unwanted Emissions in the Out-of-band Domain

Condition	Limit
Under all test conditions	The transmitter unwanted emissions in the out-of-band domain but outside the allocated band, shall not exceed the values provided by the mask in below figure.



3.5.2 Test Procedure

1. Refer to chapter 5.4.8.2 of EN 300 328 V2.2.2.
2. These measurements shall only be performed at normal test conditions.
3. For conducted measurements on devices with multiple transmit chains using the results for each of the transmit chains for the corresponding 1 MHz segments shall be added and compared with the transmit mask limit.
4. These measurements shall only be performed at normal test conditions.
5. For conducted measurements on devices with multiple transmit chains using the results for each of the transmit chains for the corresponding 1 MHz segments shall be added and compared with the transmit mask limit.

Measurement Method	
☒ Conducted measurement	☐ Radiated measurement

3.5.3 Deviation from Test Standard

No deviation

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 53 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

3.5.4 Test Setup

The measurements were performed at normal environmental conditions and shall be repeated at the extremes of the operating temperature. The measurement was performed at the lowest and the highest channel on which the equipment can operate. The equipment was configured to operate under its worst case situation with respect to output power. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator. The frequency has to be recorded for the right and left end above threshold of highest and lowest channel respectively.



Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 54 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

3.5.5 Test Results


Test Mode	Antenna	Channel [MHz]	Freq [MHz]	Result [dBm/MHz]	Limit [dBm/MHz]	Verdict
DH5	Ant1	Hop	2398.5	-48.24	-20.00	PASS
			2399.5	-52.93	-10.00	PASS
			2484	-54.03	-10.00	PASS
			2485	-51.33	-20.00	PASS
2DH5	Ant1	Hop	2398.32	-52.19	-20.00	PASS
			2399.5	-46.7	-10.00	PASS
			2484	-48.28	-10.00	PASS
			2485.36	-55.77	-20.00	PASS
3DH5	Ant1	Hop	2395.77	-55.61	-20.00	PASS
			2399.5	-46.61	-10.00	PASS
			2484	-48.67	-10.00	PASS
			2487.73	-54.51	-20.00	PASS




TEST REPORT N°: KSK-ESH-P24071264B-3

3.5.6 Test Graphs


DH5_Ant1_Hop_2400MHz-2BW to 2400MHz



DH5_Ant1_Hop_2483.5MHz to 2483.5MHz+2BW



2DH5_Ant1_Hop_2400MHz-2BW to 2400MHz



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司


No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com




TEST REPORT N°: KSK-ESH-P24071264B-3


2DH5_Ant1_Hop_2483.5MHz to 2483.5MHz+2BW



3DH5_Ant1_Hop_2400MHz-2BW to 2400MHz



3DH5_Ant1_Hop_2483.5MHz to 2483.5MHz+2BW





TEST REPORT N°: KSK-ESH-P24071264B-3

3.6 Transmitter Spurious Emissions in the spurious domain

3.6.1 Limits of Transmitter Spurious Emissions

Frequency Range	Maximum Power Limit	Bandwidth
30 MHz to 47 MHz	-36dBm	100kHz
47 MHz to 74 MHz	-54dBm	100kHz
74 MHz to 87,5 MHz	-36dBm	100kHz
87,5 MHz to 118 MHz	-54dBm	100kHz
118 MHz to 174 MHz	-36dBm	100kHz
174 MHz to 230 MHz	-54dBm	100kHz
230 MHz to 470 MHz	-36dBm	100kHz
470 MHz to 862 MHz	-54dBm	100kHz
862 MHz to 1 GHz	-36dBm	100kHz
1GHz ~ 12.75GHz	-30dBm	1MHz

Note: These limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

3.6.2 Test Procedure

1. Refer to chapter 5.4.9 of EN 300 328 V2.2.2.
2. The EUT was placed on a turntable with 1.5m height.
3. The test distance between the receiving antenna and the EUT is 3meter below 1GHz frequency range, and 3 meter which is in far field test condition for measured frequency above 1GHz, while the receiving (test) antenna is kept at 1.5 meter height.
4. Set EUT in continuous transmitting with maximum output power.
5. The table was rotated from 0 to 360 degree to search the highest radiated emission.

Measurement Method	
☐ Conducted measurement	☒ Radiated measurement
<u>For Conducted measurement:</u> The level of unwanted emissions shall be measured as their power in a specified load (conducted spurious emissions) and their effective radiated power when radiated by the cabinet or structure of the equipment with the antenna connector(s) terminated by a specified load (cabinet radiation).	
<u>Conducted measurement (For equipment with multiple transmit chains):</u> ☐ Option 1: The results for each of the transmit chains for the corresponding 1MHz segments shall be added and compared with the limits. ☐ Option 2: The results for each of the transmit chains shall be individually compared with the limits after these limits have been reduced by 10 x log (N) (number of active transmit chains)	

TEST REPORT N°: KSK-ESH-P24071264B-3


3.6.3 Deviation from Test Standard

No deviation.


3.6.4 Test Setup

1. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration).
2. The equipment was configured to operate under its worst case situation with respect to output power.
3. The test setup has been constructed as the normal use condition.

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



4.



TEST REPORT N°: KSK-ESH-P24071264B-3

3.6.5 Test Results

Below 1GHz Worst-case Data (DH5-2402MHz)

Frequency Range	30 MHz ~ 1 GHz
-----------------	----------------

Spurious Emission Level				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
48.46	H	-56.35	-54.00	2.35
67.65	H	-56.82	-54.00	2.82
98.48	H	-56.11	-54.00	2.11
201.18	H	-57.68	-54.00	3.68
525.56	H	-60.72	-54.00	6.72
600.04	H	-72.65	-54.00	18.65
53.28	V	-58.46	-54.00	4.46
89.15	V	-61.32	-54.00	7.32
101.84	V	-63.86	-54.00	9.86
499.68	V	-62.79	-54.00	8.79
569.26	V	-66.68	-54.00	12.68
624.95	V	-71.53	-54.00	17.53



TEST REPORT N°: KSK-ESH-P24071264B-3

Above 1GHz Worst-case Data

DH5

Frequency Range	1GHz ~ 12.75GHz	Operating Channel	0 and 78
-----------------	-----------------	-------------------	----------

Spurious Emission Level					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
0	4804.00	H	-64.64	-30.00	34.64
	7206.00	H	-59.08	-30.00	29.08
	4804.00	V	-63.95	-30.00	33.95
	7206.00	V	-60.14	-30.00	30.14
78	4960.00	H	-64.72	-30.00	34.72
	7440.00	H	-58.54	-30.00	28.54
	4960.00	V	-64.38	-30.00	34.38
	7440.00	V	-59.24	-30.00	29.24

2DH5

Frequency Range	1GHz ~ 12.75GHz	Operating Channel	0 and 78
-----------------	-----------------	-------------------	----------

Spurious Emission Level					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
0	4804.00	H	-64.24	-30.00	34.24
	7206.00	H	-59.13	-30.00	29.13
	4804.00	V	-63.38	-30.00	33.38
	7206.00	V	-60.46	-30.00	30.46
78	4960.00	H	-64.72	-30.00	34.72
	7440.00	H	-59.41	-30.00	29.41
	4960.00	V	-64.68	-30.00	34.68
	7440.00	V	-64.23	-30.00	34.23



TEST REPORT N°: KSK-ESH-P24071264B-3

3DH5

Frequency Range	1GHz ~ 12.75GHz	Operating Channel	0 and 78
-----------------	-----------------	-------------------	----------

Spurious Emission Level					
Channel	Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
0	4804.00	H	-65.12	-30.00	35.12
	7206.00	H	-58.64	-30.00	28.64
	4804.00	V	-63.43	-30.00	33.43
	7206.00	V	-60.72	-30.00	30.72
78	4960.00	H	-65.18	-30.00	35.18
	7440.00	H	-59.04	-30.00	29.04
	4960.00	V	-64.25	-30.00	34.25
	7440.00	V	-59.54	-30.00	29.54

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 62 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

3.7 Receiver Spurious Emissions

3.7.1 Limit of Receiver Spurious Radiation

Frequency Range	Maximum Power Limit	Bandwidth
30 MHz ~ 1 GHz	-57dBm	100 kHz
1 GHz ~ 12.75 GHz	-47dBm	1 MHz

Note: These limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

3.7.2 Test Procedure

1. Refer to chapter 5.4.10 of EN 300 328 V2.2.2.
2. The test distance between the receiving antenna and the EUT is 3meter below 1GHz frequency range, and 3 meter which is in far field test condition for measured frequency above 1GHz, while the receiving (test) antenna is kept at 1.5 meter height.
3. Set EUT in receiving mode.
4. The table was rotated from 0 to 360 degree to search the highest radiated emission.

Measurement Method	
☐ Conducted measurement	☒ Radiated measurement
<u>For Conducted measurement:</u> The level of unwanted emissions shall be measured as their power in a specified load (conducted spurious emissions) and their effective radiated power when radiated by the cabinet or structure of the equipment with the antenna connector(s) terminated by a specified load (cabinet radiation).	
<u>Conducted measurement (For equipment with multiple transmit chains):</u> ☐ Option 1: The results for each of the transmit chains for the corresponding 1MHz segments shall be added and compared with the limits. ☐ Option 2: The results for each of the transmit chains shall be individually compared with the limits after these limits have been reduced by 10 x log (N) (number of active transmit chains)	

3.7.3 Deviation from Test Standard


No deviation.

TEST REPORT N°: KSK-ESH-P24071264B-3

3.7.4 Test Setup


1. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration).
2. Testing was performed when the equipment was in a receive-only mode.
3. The test setup has been constructed as the normal use condition.

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>

4.





TEST REPORT N°: KSK-ESH-P24071264B-3

3.7.5 Test Results

RX Worst-case Data

Frequency Range	30 MHz ~ 1 GHz
-----------------	----------------

Spurious Emission Level				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
31.82	H	-58.24	-57.00	1.24
149.25	H	-62.15	-57.00	5.15
172.34	H	-58.87	-57.00	1.87
228.68	H	-59.54	-57.00	2.54
296.11	H	-65.39	-57.00	8.39
499.96	H	-63.55	-57.00	6.55
75.24	V	-63.12	-57.00	6.12
85.55	V	-63.64	-57.00	6.64
100.23	V	-64.57	-57.00	7.57
118.97	V	-65.38	-57.00	8.38
402.65	V	-62.69	-57.00	5.69
499.89	V	-62.57	-57.00	5.57

RX above 1GHz Worst-case Data

Frequency Range	1 GHz ~ 12.75 GHz
-----------------	-------------------

Spurious Emission Level				
Frequency (MHz)	Antenna Polarization	Level (dBm)	Limit (dBm)	Margin (dB)
1765.57	H	-59.11	-47.00	12.11
2348.52	H	-61.24	-47.00	14.24
3525.30	H	-59.35	-47.00	12.35
4362.08	H	-64.17	-47.00	17.17
4962.58	H	-59.62	-47.00	12.62
9914.78	H	-54.57	-47.00	7.57
1265.75	V	-56.41	-47.00	9.41
1535.57	V	-57.27	-47.00	10.27
4702.64	V	-60.35	-47.00	13.35
5865.11	V	-59.12	-47.00	12.12
7500.15	V	-56.59	-47.00	9.59
9900.87	V	-54.47	-47.00	7.47



TEST REPORT N°: KSK-ESH-P24071264B-3

3.8 Receiver Blocking

3.8.1 Limit of Receiver Blocking

This requirement applies to all receiver categories.

Receiver Category		
☐ Category 1	☒ Category 2	☐ Category 3
Minimum performance criterion	☒ PER $\leq 10\%$	
	☐ Alternative performance criteria (See note)	
Note: The manufacturer was declared performance criteria is x% for the intended use of the equipment.		

Receiver Category 1 Equipment			
Wanted signal mean power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (See note 2)	Type of blocking signal
(-133 dBm + 10 × log10(OCBW)) or -68 dBm whichever is less (see note 2)	2 380 2 504	-34	CW
(-139 dBm + 10 × log10(OCBW)) or -74 dBm whichever is less (see note 3)	2 300 2 330 2 360 2 524 2 584 2 674		

NOTE 1: OCBW is in Hz.

NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 26 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.

NOTE 3: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 20 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.

NOTE 4: The level specified is the level at the UUT receiver input assuming a 0dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.



TEST REPORT N°: KSK-ESH-P24071264B-3

Receiver Category 2 Equipment			
Wanted signal mean power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (See note 2)	Type of blocking signal
(-139 dBm + 10 × log ₁₀ (OCBW) + 10 dB) or (-74 dBm + 10 dB) whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
NOTE 1: OCBW is in Hz. NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 26 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.			

Receiver Category 3 Equipment			
Wanted signal mean power from companion device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (See note 2)	Type of blocking signal
(-139 dBm + 10 × log ₁₀ (OCBW) + 20 dB) or (-74 dBm + 20 dB) whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
NOTE 1: OCBW is in Hz. NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative the test may be performed using a wanted signal up to P_{min} + 30 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. NOTE 3: The level specified is the level at the UUT receiver input assuming a 0dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna			

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 67 of 74		
TEST REPORT EN 300 328 Ver1.0		



TEST REPORT N°: KSK-ESH-P24071264B-3

3.8.2 Test Procedure


1. Refer to chapter 5.4.11.2 of EN 300 328 V2.2.2.
2. For systems using multiple receive chains only one chain (antenna port) need to be tested.

Measurement Method	
☐ Conducted measurement	☒ Radiated measurement

3.8.3 Deviation from Test Standard

No deviation.

3.8.4 Test Setup Configuration





TEST REPORT N°: KSK-ESH-P24071264B-3

3.8.5 Test Results

Receiver Category 2 Equipment


Receiver blocking performance when operating at the lowest operating channel	
The actual blocking signal power(Note1)	antenna gain(G) :2.8dBi
	☒ at the antenna connector
	☐ in front of the antenna
Note1: For the conducted measurements , the level shall be corrected as follows: the actual blocking signal power = blocking signal power + G	

Test Mode	Antenna	Channel [MHz]	Wanted signal [dBm]	Freq. [MHz]	CW [dBm]	PER [%]	Limit [%]	Verdict
DH5	Ant1	Hop	-66.76	2300	-31.2	1.94	≤10	PASS
			-66.76	2380	-31.2	3.25	≤10	PASS
			-66.76	2504	-31.2	2.60	≤10	PASS
			-66.76	2584	-31.2	2.51	≤10	PASS



TEST REPORT N°: KSK-ESH-P24071264B-3

3.8.6 Test Graphs



Bureau Veritas ADT (ShangHai) Corporation
必维诚硕科技(上海)有限公司



No.829,Xin Zhuan Road,Song Jiang
District,Shanghai,China

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com

TEST REPORT N°: KSK-ESH-P24071264B-3


4 Photographs of the Test Configuration

TX / RX SPURIOUS EMISSION TEST




TEST REPORT N°: KSK-ESH-P24071264B-3

5 Photographs of the EUT



TEST REPORT N°: KSK-ESH-P24071264B-3





TEST REPORT N°: KSK-ESH-P24071264B-3

APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

--- END ---

Bureau Veritas ADT (ShangHai) Corporation 必维诚硕科技(上海)有限公司	No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China	Tel: +86 21 6195 7000 Fax: +86 21 6195 7001 Email: contact@cn.bureauveritas.com
Page 74 of 74		
TEST REPORT EN 300 328 Ver1.0		