

ETSI EN300 328 RADIO TEST REPORT

For

i3-Technologies NV

Interactive Flat Panel Display

Model Number: A4-75


Addition Model: A4-NT-75

Applicant:	i3-Technologies NV
Address:	Kleine Schaluinweg 7, 3290 Diest, Belgium
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2507219
Date of Test:	Jun. 20, 2025~ Aug. 28, 2025
Date of Report:	Aug. 29, 2025

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION	3
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Antenna Information	5
1.3. Antenna Information	5
1.4. Information of RF Cable	6
2. SUMMARY OF MEASUREMENTS AND RESULTS.....	7
2.1. Test Facilities.....	8
2.2. Measurement Uncertainty	9
2.3. Assistant Equipment Used For Test	9
2.4. Block Diagram of Test Setup	9
2.5. Test Mode	10
2.6. Channel List.....	10
2.7. Test Equipment List.....	11
3. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN	12
3.1. Applicability	12
3.2. Limit.....	12
3.3. Test Setup.....	12
3.4. Test Procedure	12
3.5. Test Result.....	13
4. RECEIVER SPURIOUS EMISSIONS	25
4.1. Applicability	25
4.2. Limit.....	25
4.3. Test Setup.....	25
4.4. Test Procedure	25
4.5. Test Result.....	26
5. PHOTOGRAPHS OF TEST SETUP	34
5.1. Setup for Transmitter & Receiver Spurious Emissions	34
6. EUT PHOTO.....	35

Applicant: Address:	i3-Technologies NV Kleine Schaluinweg 7, 3290 Diest, Belgium		
Manufacturer: Address:	i3-Technologies NV Kleine Schaluinweg 7, 3290 Diest, Belgium		
E.U.T:	Interactive Flat Panel Display		
Model Number:	A4-75		
Addition Model:	A4-NT-75 Note: They are identical except model name.		
Power Supply:	100-240V~, 50/60Hz, 7.5A		
Trade Name:	i3	Serial No.:	-----
Date of Receipt:	Jun. 20, 2025	Date of Test:	Jun. 20, 2025 ~ Aug. 28, 2025
Test Specification:	ETSI EN 300 328 V2.2.2: 2019-07		
Test Result:	The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co.,Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the ETSI EN 300 328 requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:		Reviewed by:	
 Zephyr Zhu/ Assistant		 Seven Wang/ Engineer	
		Date: Aug. 29, 2025 Approved by:  Iceman Hu / Manager	
Other Aspects: N/A			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1.GENERAL INFORMATION

1.1.Description of Device (EUT)

Product Name	:	Interactive Flat Panel Display
Model Number	:	A4-75
Module Model Number	:	WCT2GM2511; WXT52M2511
Software Version	:	N/A
Hardware Version	:	N/A
Operation frequency	:	IEEE 802.11b/g/n HT20/ax HE20:2412MHz~2472MHz IEEE 802.11n HT40/ax HE40:2422MHz~2462MHz
Modulation	:	IEEE 802.11b mode: DSSS IEEE 802.11g/n mode: OFDM IEEE 802.11ax mode: OFDMA
Operating Temperature Range	:	0℃~+45℃
Sample Type	:	Prototype production

Module Model Number: WCT2GM2511

1.2. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Internal	-	3
2	-	-	Internal	-	3

Note:

1. The EUT support smart antenna systems(multiple antennas without beamforming).
2. The EUT support 2TX2RX,the antennas can support SISO function in 802.11b and 802.11g,and can support MIMO function in 802.11n.
3. After pre-test all antenna configurations, the worst case configuration as list below.
4. The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
5. The test results of this report only apply to the sample as received.

ANT No. TX Mode	SISO Configuration	MIMO Configuration
IEEE 802.11b	Ant 1 and Ant 2	/
IEEE 802.11g	Ant 1 and Ant 2	/
IEEE 802.11n HT20	/	Ant 1+Ant 2
IEEE 802.11n HT40	/	Ant 1+Ant 2

Module Model Number: WXT52M2511

1.3. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Internal	-	2.80
2	-	-	Internal	-	2.78

Note:

6. The EUT support smart antenna systems(multiple antennas without beamforming).
7. The EUT support 2TX2RX,the antennas can support SISO function in 802.11b and 802.11g,and can support MIMO function in 802.11n/802.11ax.
8. After pre-test all antenna configurations, the worst case configuration as list below.
9. The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
10. The test results of this report only apply to the sample as received.

ANT No. TX Mode	SISO Configuration	MIMO Configuration
IEEE 802.11b	Ant 1 and Ant 2	/
IEEE 802.11g	Ant 1 and Ant 2	/
IEEE 802.11n HT20	/	Ant 1+Ant 2
IEEE 802.11n HT40	/	Ant 1+Ant 2
IEEE 802.11ax HE20	/	Ant 1+Ant 2
IEEE 802.11ax HE40	/	Ant 1+Ant 2

1.4.Information of RF Cable

Cable Loss(dB)	Provided by
1.0	i3-Technologies NV
1.The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received.	
2.The laboratory is not responsible for the accuracy of the cable loss.	

2.SUMMARY OF MEASUREMENTS AND RESULTS

Harmonized Standard ETSI EN300 328				
The following essential requirements and test specifications are relevant to the presumption of conformity under Article 3.2 of the Radio Equipment Directive 2014/53/EU				
No	Test Parameter	Clause No	Condition	Results
1	RF Output Power	4.3.1.2 or 4.3.2.2	Apply all equipment	N/A
2	Power Spectral Density	4.3.2.3	Only for non-FHSS equipment	N/A
3	Duty Cycle ,Tx-Sequence, Tx-gap	4.3.1.3 or 4.3.2.4	Only for non-Adaptive equipment	N/A
4	Accumulated Transmit Time, Frequency Occupation & Hopping Sequence	4.3.1.4	Only for FHSS equipment	N/A
5	Hopping Frequency Separation	4.3.1.5	Only for FHSS equipment	N/A
6	Medium Utilization	4.3.1.6 or 4.3.2.5	Only for non-Adaptive equipment	N/A
7	Adaptivity	4.3.1.7 or 4.3.2.6	Only for Adaptive equipment	N/A
8	Occupied Channel Bandwidth	4.3.1.8 or 4.3.2.7	Apply all equipment	N/A
9	Transmitter unwanted emissions in the OOB domain	4.3.1.9 or 4.3.2.8	Apply all equipment	N/A
10	Transmitter unwanted emissions in the spurious domain	4.3.1.10 or 4.3.2.9	Apply all equipment	PASS
11	Receiver spurious emissions	4.3.1.11 or 4.3.2.10	Apply all equipment	PASS
12	Receiver Blocking	4.3.1.12 or 4.3.2.11	Apply all equipment	N/A
13	Geo-location capability	4.3.1.13 or 4.3.2.12	Only for equipment with geo-location capability	N/A
Note: 1.N/A is an abbreviation for Not Applicable and means this test item is not applicable for this device according to the technology characteristic of device. 2. The wireless module WCT2GM2511, WXT52M2511 included in the device passed the RED certification, when applied to the host, Re-test RSE of 2.4G Wi-Fi function, all other test data refer to module test report 4790119556.2-8 & 4791023025-1-RF-3.				

2.1. Test Facilities

EMC Lab : Accredited by CNAS, CHINA
Registration No.: L5288
This Accreditation is valid until: November 12, 2029

Recognized by FCC, USA
Designation Number: CN1215
This Recognition is valid until: January 31, 2026

Accredited by A2LA, USA
Registration No.: 4366.01
This Accreditation is valid until: January 31, 2026

Recognized by Industry Canada
CAB identifier No.: CN0035
This Recognition is valid until: January 31, 2026

Recognized by VCCI, Japan
Registration No.: C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2020
This Recognition is valid until: Apr. 19, 2026

Recognized by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Recognized by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
Guangdong, China

2.2.Measurement Uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 18GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


2.3.Assistant Equipment Used For Test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.5m	AC Cable

2.4.Block Diagram of Test Setup

For radiated emissions test: EUT was placed on a turntable, which is 1.5 meters high above ground. The EUT was set into 2.4G Wi-Fi test mode by software prior to testing.



(EUT: Interactive Flat Panel Display)

2.5. Test Mode

The test mode was selected for the final test as listed below.

Test Item	Test Mode	Data Rate	Test Channel
Transmitter unwanted emissions in the spurious domain	IEEE 802.11b	1Mbps	Low/ High
	IEEE 802.11g	6Mbps	Low/ High
	IEEE 802.11n HT20	MCS0	Low/ High
	IEEE 802.11n HT40	MCS0	Low/ High
	IEEE 802.11ax HE20	MCS0	Low/ High
	IEEE 802.11ax HE40	MCS0	Low/ High
Receiver Spurious Emissions	Receive	-	-

Note: In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.6. Channel List

IEEE 802.11b/802.11g/802.11n HT20/802.11ax HE20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442	12	2467
3	2422	8	2447	13	2472
4	2427	9	2452		
5	2432	10	2457		
IEEE 802.11n HT40/802.11ax HE40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452
4	2427	7	2442	10	2457
5	2432	8	2447	11	2462

2.7. Test Equipment List

For Radiated Emissions Test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 11,25	June 10,26
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For Radiated Emission Test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA9120D	EST-E144	LISAI	June 11,25	June 10,26
Horn Antenna	Com-Power	AHA-840	EST-E133	LISAI	June 11,25	June 10,26
Low Noise Amplifier	RF	TRLA-010180 G45N	EST-E142	LISAI	June 11,25	June 10,26
Spectrum Analyzer	Rohde &Schwarz	FSV40	EST-E069	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

3. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

3.1. Applicability


This requirement applies to all types of non-FHSS equipment.

3.2. Limit

Frequency Range	Maximum Power	Bandwidth
30MHz to 47MHz	-36dBm	100kHz
47MHz to 74MHz	-54dBm	100kHz
74MHz to 87,5MHz	-36dBm	100kHz
87,5MHz to 118MHz	-54dBm	100kHz
118MHz to 174MHz	-36dBm	100kHz
174MHz to 230MHz	-54dBm	100kHz
230MHz to 470MHz	-36dBm	100kHz
470MHz to 694MHz	-54dBm	100kHz
694MHz to 1GHz	-36dBm	100kHz
1GHz to 12,75GHz	-30dBm	1MHz

Note: These limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

3.3. Test Setup



3.4. Test Procedure

- EUT was placed on a turn table, which is 1.5 meter high above ground.
- Test Antenna is set 3 meters away from the EUT, which is connect to a spectrum analyzer.
- Set the EUT transmit continuously with maximum output power.
- The measurement procedure refer to clause 5.4.9.2.2 of ETSI EN300 328 V2.2.2.
- Repeat step a to step c until all modes and channels were measured.
- Record the results in the test report.

3.5. Test Result

30MHz to 1GHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 131

File: \\EMC-966-1\test data\2025\RF\TTC\王牌A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 131
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 TX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : TX Mode
WCT2GM2511

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBm)	Correction Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Type
1	163.86	10.73	1.89	-95.45	9.70	-73.13	-36.00	37.13	erp
2	191.99	9.28	2.06	-95.80	9.70	-74.76	-54.00	20.76	erp
3	344.28	13.92	2.86	-101.05	9.70	-74.57	-36.00	38.57	erp
4	389.87	15.60	3.07	-101.38	9.70	-73.01	-36.00	37.01	erp
5	479.11	17.75	3.47	-100.98	9.70	-70.06	-54.00	16.06	erp
6	721.61	20.95	4.36	-102.83	9.70	-67.82	-36.00	31.82	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 132

File: \\EMC-966-1\test data\2025\RF\TTC\王牌A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 132
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : EN300328_V2.2.2 TX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : TX Mode
WCT2GM2511

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBm)	Correction Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Type
1	231.76	10.46	2.28	-92.69	9.70	-70.25	-36.00	34.25	erp
2	385.99	15.44	3.05	-92.21	9.70	-64.02	-36.00	28.02	erp
3	488.81	17.80	3.51	-100.83	9.70	-69.82	-54.00	15.82	erp
4	617.82	19.92	4.00	-103.81	9.70	-70.19	-54.00	16.19	erp
5	782.72	22.05	4.58	-102.84	9.70	-66.51	-36.00	30.51	erp
6	858.38	22.90	4.84	-99.54	9.70	-62.10	-36.00	26.10	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 147

File: \\EMC-966-1\test data\2025\RF\TTC\王牌A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 147
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 TX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : TX Mode
WXT52M2511

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBm)	Correction Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Type
1	191.99	9.28	2.06	-95.51	9.70	-74.47	-54.00	20.47	erp
2	355.92	14.51	2.92	-98.71	9.70	-71.58	-36.00	35.58	erp
3	373.38	14.92	3.00	-98.62	9.70	-71.00	-36.00	35.00	erp
4	478.14	17.69	3.47	-100.45	9.70	-69.59	-54.00	15.59	erp
5	642.07	20.38	4.09	-107.52	9.70	-73.35	-54.00	19.35	erp
6	724.52	21.10	4.37	-102.48	9.70	-67.31	-36.00	31.31	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 148

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 148
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : EN300328_V2.2.2 TX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : TX Mode
WXT52M2511


	Freq.	Ant.	Cable		Correction	Emission			
	(MHz)	Factor	Loss	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	385.02	15.40	3.05	-92.08	9.70	-63.93	-36.00	27.93	erp
2	473.29	17.42	3.44	-99.09	9.70	-68.53	-54.00	14.53	erp
3	689.60	20.60	4.26	-103.76	9.70	-69.20	-54.00	15.20	erp
4	719.67	20.88	4.36	-101.82	9.70	-66.88	-36.00	30.88	erp
5	784.66	22.09	4.59	-102.24	9.70	-65.86	-36.00	29.86	erp
6	859.35	22.90	4.84	-98.37	9.70	-60.93	-36.00	24.93	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Above 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 91
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 TX
Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
Engineer : Aron Zhang
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : IEEE 802.11g TX 2412MHz
WCT2GM2511

	Freq.	Ant.	Cable	Amp	Correction	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2974.00	27.93	4.01	43.44	-54.25	11.80	-53.95	-30.00	23.95	eirp
2	4818.75	31.80	5.30	43.23	-61.42	11.80	-55.75	-30.00	25.75	eirp
3	5946.75	33.40	5.86	43.39	-57.34	11.80	-49.67	-30.00	19.67	eirp
4	7204.00	37.10	6.70	43.36	-75.09	11.80	-62.85	-30.00	32.85	eirp
5	8978.25	38.53	7.06	43.01	-67.85	11.80	-53.47	-30.00	23.47	eirp
6	10940.50	39.41	8.74	42.04	-72.44	11.80	-54.53	-30.00	24.53	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 92

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-16



Site no. : 1# 966 Chamber Data no. : 92
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : EN300328_V2.2.2 TX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : IEEE 802.11g TX 2412MHz
 WCT2GM2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2962.25	28.00	3.99	43.46	-52.93	11.80	-52.60	-30.00	22.60	eirp
2	4818.75	31.80	5.30	43.23	-61.39	11.80	-55.72	-30.00	25.72	eirp
3	5946.75	33.40	5.86	43.39	-60.61	11.80	-52.94	-30.00	22.94	eirp
4	7204.00	37.10	6.70	43.36	-71.56	11.80	-59.32	-30.00	29.32	eirp
5	8978.25	38.53	7.06	43.01	-64.99	11.80	-50.61	-30.00	20.61	eirp
6	11880.50	40.02	8.90	41.12	-73.93	11.80	-54.33	-30.00	24.33	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 93

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-16



Site no. : 1# 966 Chamber Data no. : 93
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : EN300328_V2.2.2 TX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : IEEE 802.11g TX 2472MHz
 WCT2GM2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2974.00	27.93	4.01	43.44	-56.82	11.80	-56.52	-30.00	26.52	eirp
2	4936.25	31.75	5.36	43.21	-59.63	11.80	-53.93	-30.00	23.93	eirp
3	5935.00	33.40	5.85	43.39	-61.09	11.80	-53.43	-30.00	23.43	eirp
4	7004.25	35.90	6.64	43.40	-70.34	11.80	-59.40	-30.00	29.40	eirp
5	8990.00	38.42	7.06	43.00	-66.73	11.80	-52.45	-30.00	22.45	eirp
6	11939.25	40.05	8.91	41.07	-73.91	11.80	-54.22	-30.00	24.22	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 94

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-16



Site no. : 1# 966 Chamber Data no. : 94
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : EN300328_V2.2.2 TX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : IEEE 802.11g TX 2472MHz
 WCT2GM2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2974.00	27.93	4.01	43.44	-55.91	11.80	-55.61	-30.00	25.61	eirp
2	4948.00	31.75	5.36	43.21	-64.75	11.80	-59.05	-30.00	29.05	eirp
3	5935.00	33.40	5.85	43.39	-59.15	11.80	-51.49	-30.00	21.49	eirp
4	7168.75	36.97	6.69	43.37	-74.82	11.80	-62.73	-30.00	32.73	eirp
5	8990.00	38.42	7.06	43.00	-69.38	11.80	-55.10	-30.00	25.10	eirp
6	10999.25	39.40	8.77	42.00	-73.04	11.80	-55.07	-30.00	25.07	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 75

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-12



Site no. : 1# 966 Chamber Data no. : 75
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 TX
Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
Engineer : Aron Zhang
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : IEEE 802.11ax HE20 TX 2412MHz
WXT52M2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2962.25	28.00	3.99	43.46	-51.69	11.80	-51.36	-30.00	21.36	eirp
2	4818.75	31.80	5.30	43.23	-66.04	11.80	-60.37	-30.00	30.37	eirp
3	5946.75	33.40	5.86	43.39	-55.17	11.80	-47.50	-30.00	17.50	eirp
4	7239.25	36.80	6.71	43.35	-75.13	11.80	-63.17	-30.00	33.17	eirp
5	8990.00	38.42	7.06	43.00	-70.41	11.80	-56.13	-30.00	26.13	eirp
6	10999.25	39.40	8.77	42.00	-72.76	11.80	-54.79	-30.00	24.79	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 76

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.E6 (154)

Date: 2025-07-12



Site no. : 1# 966 Chamber Data no. : 76
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : EN300328_V2.2.2 TX
Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
Engineer : Aron Zhang
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : IEEE 802.11ax HE20 TX 2412MHz
WXT52M2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2974.00	27.93	4.01	43.44	-53.70	11.80	-53.40	-30.00	23.40	eirp
2	4818.75	31.80	5.30	43.23	-69.21	11.80	-63.54	-30.00	33.54	eirp
3	5946.75	33.40	5.86	43.39	-57.08	11.80	-49.41	-30.00	19.41	eirp
4	7133.50	36.83	6.68	43.37	-72.18	11.80	-60.24	-30.00	30.24	eirp
5	8990.00	38.42	7.06	43.00	-66.70	11.80	-52.42	-30.00	22.42	eirp
6	11974.50	40.09	8.92	41.02	-75.12	11.80	-55.33	-30.00	25.33	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 77

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-12



Site no. : 1# 966 Chamber Data no. : 77
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : EN300328_V2.2.2 TX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : IEEE 802.11ax HE20 TX 2472MHz
 WXT52M2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2985.75	27.87	4.02	43.42	-55.07	11.80	-54.80	-30.00	24.80	eirp
2	4948.00	31.75	5.36	43.21	-68.74	11.80	-63.04	-30.00	33.04	eirp
3	5946.75	33.40	5.86	43.39	-56.27	11.80	-48.60	-30.00	18.60	eirp
4	7227.50	36.95	6.71	43.36	-71.86	11.80	-59.76	-30.00	29.76	eirp
5	8990.00	38.42	7.06	43.00	-67.35	11.80	-53.07	-30.00	23.07	eirp
6	11610.25	39.83	8.86	41.39	-74.12	11.80	-55.02	-30.00	25.02	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 78

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-12



Site no. : 1# 966 Chamber Data no. : 78
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 TX
Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
Engineer : Aron Zhang
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : IEEE 802.11ax HE20 TX 2472MHz
WXT52M2511

	Freq.	Ant.	Cable	Amp		Correction	Emission			
	(MHz)	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	2962.25	28.00	3.99	43.46	-54.75	11.80	-54.42	-30.00	24.42	eirp
2	4936.25	31.75	5.36	43.21	-68.05	11.80	-62.35	-30.00	32.35	eirp
3	5935.00	33.40	5.85	43.39	-55.71	11.80	-48.05	-30.00	18.05	eirp
4	7450.75	36.85	6.77	43.31	-76.57	11.80	-64.46	-30.00	34.46	eirp
5	8990.00	38.42	7.06	43.00	-68.52	11.80	-54.24	-30.00	24.24	eirp
6	11363.50	39.66	8.83	41.63	-74.39	11.80	-55.73	-30.00	25.73	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

4.RECEIVER SPURIOUS EMISSIONS

4.1.Applicability


This requirement applies to all types of non-FHSS equipment.

4.2.Limit

Frequency Range	Maximum Power	Bandwidth
30MHz to 1GHz	-57dBm	100kHz
1GHz to 12,75GHz	-47dBm	1MHz

Note: These limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

4.3.Test Setup



4.4.Test Procedure

- EUT was placed on a turn table, which is 1.5 meter high above ground.
- Test Antenna is set 3 meters away from the EUT, which is connected to a spectrum analyzer.
- Set the EUT transmit to receive mode.
- The measurement procedure refers to clause 5.4.10.2.2 of ETSI EN300 328 V2.2.2.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

4.5. Test Result

30MHz to 1GHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 133

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 133
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : EN300328_V2.2.2 RX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : RX Mode
WCT2GM2511

	Freq.	Ant.	Cable		Correction	Emission			
	(MHz)	Factor	Loss	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	392.78	15.68	3.08	-90.37	9.70	-61.91	-57.00	4.91	erp
2	714.82	20.80	4.34	-101.19	9.70	-66.35	-57.00	9.35	erp
3	782.72	22.05	4.58	-101.23	9.70	-64.90	-57.00	7.90	erp
4	859.35	22.90	4.84	-99.04	9.70	-61.60	-57.00	4.60	erp
5	902.03	22.95	4.99	-101.96	9.70	-64.32	-57.00	7.32	erp
6	974.78	24.25	5.22	-104.37	9.70	-65.20	-57.00	8.20	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 134

File: \\EMC-966-1\test data\2025\RF\TTC\王牌A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 134
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 RX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : RX Mode
WCT2GM2511

	Freq.	Ant.	Cable		Correction	Emission			
	(MHz)	Factor	Loss	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	163.86	10.73	1.89	-94.80	9.70	-72.48	-57.00	15.48	erp
2	373.38	14.92	3.00	-98.82	9.70	-71.20	-57.00	14.20	erp
3	387.93	15.52	3.06	-99.22	9.70	-70.94	-57.00	13.94	erp
4	481.05	17.80	3.48	-100.57	9.70	-69.59	-57.00	12.59	erp
5	719.67	20.88	4.36	-101.92	9.70	-66.98	-57.00	9.98	erp
6	898.15	22.88	4.98	-105.69	9.70	-68.13	-57.00	11.13	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 149

File: \\EMC-966-1\test data\2025\RF\TTC\王牌A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 149
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : EN300328_V2.2.2 RX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : RX Mode
WXT52M2511

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBm)	Correction Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Type
1	390.84	15.63	3.08	-91.82	9.70	-63.41	-57.00	6.41	erp
2	473.29	17.42	3.44	-99.91	9.70	-69.35	-57.00	12.35	erp
3	784.66	22.09	4.59	-103.13	9.70	-66.75	-57.00	9.75	erp
4	851.59	22.90	4.82	-97.99	9.70	-60.57	-57.00	3.57	erp
5	902.03	22.95	4.99	-101.99	9.70	-64.35	-57.00	7.35	erp
6	976.72	24.23	5.23	-103.58	9.70	-64.42	-57.00	7.42	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 150

File: \\EMC-966-1\test data\2025\RF\TTC\王牌\A4-75.EM6 (154)

Date: 2025-08-28



Site no. : 1# 966 Chamber Data no. : 150
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : EN300328_V2.2.2 RX(3)
Env. / Ins. : Temp:22.6°C;Humi:51.5%;Press:101.55kPa
Engineer : ZQL
EUT : Interactive Flat Panel Display
Power : AC 230V/50Hz
M/N : A4-75
Test Mode : RX Mode
WXT52M2511

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBm)	Correction Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Type
1	161.92	10.97	1.88	-94.35	9.70	-71.80	-57.00	14.80	erp
2	373.38	14.92	3.00	-98.59	9.70	-70.97	-57.00	13.97	erp
3	479.11	17.75	3.47	-99.20	9.70	-68.28	-57.00	11.28	erp
4	719.67	20.88	4.36	-102.67	9.70	-67.73	-57.00	10.73	erp
5	867.11	22.90	4.87	-106.47	9.70	-69.00	-57.00	12.00	erp
6	946.65	23.99	5.13	-106.40	9.70	-67.58	-57.00	10.58	erp

Remarks: 1. Emission Level = Reading+Antenna Factor+Cable Loss+Correction Factor
2. Margin = Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Above 1GHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 107

File: \\EMC-966-1\test data\2025\RF\TTC\王牌A4-75.EM6 (154)

Date: 2025-07-16



Site no. : 1# 966 Chamber Data no. : 107
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : EN300328_V2.2.2 RX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : RX Mode
 WCT2GM2511

		Ant.	Cable	Amp		Correction	Emission			
	Freq.	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
	(MHz)	(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	1305.50	26.00	2.51	45.50	-53.36	11.80	-58.55	-47.00	11.55	eirp
2	1458.25	25.90	2.65	45.31	-52.33	11.80	-57.29	-47.00	10.29	eirp
3	2974.00	27.93	4.01	43.44	-50.54	11.80	-50.24	-47.00	3.24	eirp
4	5935.00	33.40	5.85	43.39	-57.79	11.80	-50.13	-47.00	3.13	eirp
5	8907.75	39.00	7.05	43.02	-65.09	11.80	-50.26	-47.00	3.26	eirp
6	11892.25	40.03	8.90	41.10	-73.59	11.80	-53.96	-47.00	6.96	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 108

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-16



Site no. : 1# 966 Chamber Data no. : 108
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : EN300328_V2.2.2 RX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : RX Mode
 WCT2GM2511

	Freq.	Ant.	Cable	Amp	Correction	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	1458.25	25.90	2.65	45.31	-58.95	11.80	-63.91	-47.00	16.91	eirp
2	2950.50	28.00	3.99	43.46	-50.46	11.80	-50.13	-47.00	3.13	eirp
3	5935.00	33.40	5.85	43.39	-57.95	11.80	-50.29	-47.00	3.29	eirp
4	8896.00	38.90	7.05	43.02	-65.00	11.80	-50.27	-47.00	3.27	eirp
5	9683.25	40.25	7.78	42.79	-72.71	11.80	-55.67	-47.00	8.67	eirp
6	11328.25	39.64	8.82	41.66	-74.16	11.80	-55.56	-47.00	8.56	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 61

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-12



Site no. : 1# 966 Chamber Data no. : 61
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : EN300328_V2.2.2 RX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : RX Mode
 WXT52M2511

	Freq.	Ant.	Cable	Amp	Correction	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	1199.75	25.10	2.42	45.64	-51.78	11.80	-58.10	-47.00	11.10	eirp
2	2997.50	27.80	4.04	43.40	-57.73	11.80	-57.49	-47.00	10.49	eirp
3	5946.75	33.40	5.86	43.39	-58.26	11.80	-50.59	-47.00	3.59	eirp
4	7145.25	36.83	6.68	43.37	-72.80	11.80	-60.86	-47.00	13.86	eirp
5	9001.75	38.30	7.06	43.00	-66.26	11.80	-52.10	-47.00	5.10	eirp
6	11880.50	40.02	8.90	41.12	-76.39	11.80	-56.79	-47.00	9.79	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 62

File: \\EMC-966-1\test data\2025\RF\TCL王牌\A4-75.EM6 (154)

Date: 2025-07-12



Site no. : 1# 966 Chamber Data no. : 62
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : EN300328_V2.2.2 RX
 Env. / Ins. : Temp:20.5°C;Humi:50%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : Interactive Flat Panel Display
 Power : AC 230V/50Hz
 M/N : A4-75
 Test Mode : RX Mode
 WXT52M2511

	Freq.	Ant.	Cable	Amp	Correction	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Factor	Level	Limits	Margin	Type
		(dB/m)	(dB)	(dB)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1	1399.50	25.60	2.61	45.37	-52.39	11.80	-57.75	-47.00	10.75	eirp
2	2962.25	28.00	3.99	43.46	-57.30	11.80	-56.97	-47.00	9.97	eirp
3	5946.75	33.40	5.86	43.39	-58.48	11.80	-50.81	-47.00	3.81	eirp
4	6510.75	36.10	6.27	43.40	-74.07	11.80	-63.30	-47.00	16.30	eirp
5	8919.50	38.88	7.05	43.02	-70.22	11.80	-55.51	-47.00	8.51	eirp
6	11892.25	40.03	8.90	41.10	-75.94	11.80	-56.31	-47.00	9.31	eirp

Remarks: 1. Emission Level= Reading+Antenna Factor+Cable Loss-Amp Factor+Correction Factor
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

5. PHOTOGRAPHS OF TEST SETUP

5.1. Setup for Transmitter & Receiver Spurious Emissions

Below 1GHz



Above 1GHz



6.EUT PHOTO

Refer to report no. ESTE-R2507216

End of Test Report