Certificate #7130.01

CE Radio Test Report

Project No.	:	2502C138
Equipment	:	AX1500 Whole Home Mesh Wi-Fi 6 System
Brand Name	:	Cudy
Test Model	:	M1500
Series Model	:	N/A
Applicant	:	Shenzhen Cudy Technology Co., Ltd.
Address	:	7/F, Lepu Tower (West), 66 Xingke Rd, Nanshan, Shenzhen, China
Manufacturer	:	Shenzhen Cudy Technology Co., Ltd.
Address	:	7/F, Lepu Tower (West), 66 Xingke Rd, Nanshan, Shenzhen, China
Factory	:	Shenzhen Cudy Technology Co., Ltd.
Address	:	7/F, Lepu Tower (West), 66 Xingke Rd, Nanshan, Shenzhen, China
Date of Receipt	:	Feb. 19, 2025
Date of Test	:	Feb. 20, 2025 ~ Mar. 11, 2025
Issued Date	:	Mar. 20, 2025
Report Version	:	R00
Test Sample	:	Engineering Sample No.: DG2025021962
Standard(s)	:	ETSI EN 301 893 V2.1.1 (2017-05)

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Chella Zheng

Approved by : Welly Zhou

Room 108-116, 309-310, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong, People's Republic of China.
Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. BTL assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by BTL.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the ISO/IEC 17025: 2017 requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.
Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents Page

REPORT ISSUED HISTORY 7

1 . RF EMISSIONS MEASUREMENT 8

1.1 TEST FACILITY 8

1.2 MEASUREMENT UNCERTAINTY 8

1.3 TEST ENVIRONMENT CONDITIONS 8

1.4 TEST CHANNEL 9

1.5 TEST METHODOLOGY AND RESULTS 10

2 . GENERAL INFORMATION 11

2.1 GENERAL DESCRIPTION OF EUT 11

2.2 DESCRIPTION OF TEST MODES 13

2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING 14

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 15

2.5 DESCRIPTION OF SUPPORT UNITS 15

2.6 EUT OPERATING CONDITIONS 15

2.7 CUSTOMER INFORMATION DESCRIPTION 15

3 . CENTRE FREQUENCIES 16

3.1 LIMIT 16

3.2 TEST PROCEDURES 16

3.3 TEST SETUP LAYOUT 16

3.4 TEST DEVIATION 16

3.5 EUT OPERATION DURING TEST 16

3.6 TEST RESULTS 16

4 . NOMINAL / OCCUPIED CHANNEL BANDWIDTH 17

4.1 LIMIT 17

4.2 TEST PROCEDURES 17

4.3 TEST SETUP LAYOUT 17

4.4 TEST DEVIATION 17

4.5 EUT OPERATION DURING TEST 17

4.6 TEST RESULTS 17

5 . RF OUTPUT POWER 18

5.1 LIMIT 18

5.2 TEST PROCEDURES 18

Table of Contents Page

5.3 TEST SETUP LAYOUT 18
5.4 TEST DEVIATION 18
5.5 EUT OPERATION DURING TEST 18
5.6 TEST RESULTS 18
6 . POWER DENSITY 19
6.1 LIMIT 19
6.2 TEST PROCEDURES 19
6.3 TEST SETUP LAYOUT 19
6.4 TEST DEVIATION 19
6.5 EUT OPERATION DURING TEST 19
6.6 TEST RESULTS 19
7 . TRANSMITTER UNWANTED EMISSIONS (OUTSIDE THE 5 GHZ RLAN BANDS) 20
7.1 LIMIT 20
7.2 TEST PROCEDURES 20
7.3 TEST SETUP LAYOUT 20
7.4 TEST DEVIATION 21
7.5 EUT OPERATION DURING TEST 21
7.6 TEST RESULTS (30MHZ TO 1000MHZ) 21
7.7 TEST RESULTS (ABOVE 1000MHZ) 21
8 . TRANSMITTER UNWANTED EMISSIONS(WITHIN THE 5 GHZ RLAN BANDS) 22
8.1 LIMIT 22
8.2 TEST PROCEDURES 22
8.3 TEST SETUP LAYOUT 22
8.4 TEST DEVIATION 22
8.5 EUT OPERATION DURING TEST 22
8.6 TEST RESULTS 22
9 . RECEIVER SPURIOUS EMISSIONS 23
9.1 LIMIT 23
9.2 TEST PROCEDURES 23
9.3 TEST SETUP LAYOUT 23
9.4 TEST DEVIATION 23
9.5 EUT OPERATION DURING TEST 23

Table of Contents Page

9.6 TEST RESULTS (30 MHZ TO 1000 MHZ) 23
9.7 TEST RESULTS (ABOVE 1000 MHZ) 23
10 . ADAPTIVITY (CHANNEL ACCESS MECHANISM) 24
10.1 LIMIT 24
10.2 TEST PROCEDURES 24
10.3 TEST SETUP 24
10.4 TEST DEVIATION 24
10.5 EUT OPERATION DURING TEST 24
10.6 TEST RESULTS 24
11 . RECEIVER BLOCKING 25
11.1 LIMIT 25
11.2 TEST PROCEDURES 25
11.3 TEST SETUP 25
11.4 TEST DEVIATION 25
11.5 EUT OPERATION DURING TEST 25
11.6 TEST RESULTS 25
12 . MEASUREMENT INSTRUMENTS LIST 26
13 . EUT TEST PHOTO 29
APPENDIX A - CENTRE FREQUENCIES 31
APPENDIX B - NOMINAL / OCCUPIED CHANNEL BANDWIDTH 33
APPENDIX C - RF OUTPUT POWER 35
APPENDIX D - POWER DENSITY 38
APPENDIX E - TRANSMITTER UNWANTED EMISSIONS 40
OUTSIDE THE 5 GHZ RLAN BANDS (30MHZ TO 1000MHZ) 40
APPENDIX F - TRANSMITTER UNWANTED EMISSIONS 43
OUTSIDE THE 5 GHZ RLAN BANDS (ABOVE 1000MHZ) 43
APPENDIX G - TRANSMITTER UNWANTED EMISSIONS 54
WITHIN THE 5 GHZ RLAN BANDS 54
APPENDIX H - RECEIVER SPURIOUS EMISSIONS (30MHZ TO 1000MHZ) 59
APPENDIX I - RECEIVER SPURIOUS EMISSIONS (ABOVE 1000MHZ) 62

Table of Contents Page

APPENDIX J - ADAPTIVITY **67**

APPENDIX K - RECEIVER BLOCKING **77**

APPENDIX L - INFORMATION AS REQUIRED BY EN 301 893 V2.1.1, CLAUSE 5.4.1 **79**

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-ETSP-2-2502C138	R00	Original Report.	Mar. 20, 2025	Valid

1. RF EMISSIONS MEASUREMENT

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is **SSL-CB05/SSL-TR08/SSL-TR19** at the location of Room 108-116, 309-310, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong, People's Republic of China.

1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor) k=1.96 or k=2(which provide confidence levels of respectively 95% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).
Measurement Uncertainty for a Level of Confidence of 95.45%, $U=2\times u_c(y)$.

The BTL measurement uncertainty as below table:

Item	**Uncertainty**
Radio Frequency	53.46 Hz
RF Power, Conducted	0.95 dB
Power Density	0.86 dB
Temperature	0.46 °C
Humidity	1.3 %
Time	0.566 %
Spurious Emissions, Conducted	2.71 dB
Spurious Emissions, Radiated f ≤ 1GHz	3.76 dB
Spurious Emissions, Radiated 1GHz < f ≤ 18GHz	3.76 dB
Spurious Emissions, Radiated 18GHz < f ≤ 26.5GHz	4.02 dB

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By	Test Date
Centre frequencies	Normal & Extreme	52%	AC 230V/50Hz	Hagan He	Mar. 05, 2025
Occupied Channel Bandwidth	22°C	52%	AC 230V/50Hz	Hagan He	Mar. 05, 2025
RF output power	Normal & Extreme	52%	AC 230V/50Hz	Evan Fang	Feb. 28, 2025-Mar. 10, 2025
Power Density	22°C	52%	AC 230V/50Hz	Hagan He	Mar. 05, 2025
Transmitter unwanted emissions outside the 5 GHz RLAN bands	21°C	57%	AC 230V/50Hz	Gavin Ge	Mar. 04, 2025-Mar. 05, 2025
Transmitter unwanted emissions within the 5 GHz RLAN bands	22°C	52%	AC 230V/50Hz	Hagan He	Mar. 05, 2025
Receiver spurious emissions	21°C	57%	AC 230V/50Hz	Gavin Ge	Mar. 04, 2025-Mar. 05, 2025
Adaptivity	21°C	51%	AC 230V/50Hz	Hagan He	Mar. 03, 2025
Receiver Blocking	23°C	61%	AC 230V/50Hz	Hagan He	Mar. 04, 2025

1.4 TEST CHANNEL

IEEE 802.11a / IEEE 802.11ax(HE20)		
Test Channel	EUT Channel	Test Frequency
Low	CH36	5180 MHz
High	CH48	5240 MHz

IEEE 802.11ax(HE40)		
Test Channel	EUT Channel	Test Frequency
Low	CH38	5190 MHz
High	CH46	5230 MHz

IEEE 802.11ax(HE80)		
Test Channel	EUT Channel	Test Frequency
Low	CH42	5210 MHz

1.5 TEST METHODOLOGY AND RESULTS

Harmonised Standard ETSI EN 301 893					
Requirement			Requirement Conditionality		Observations
No	Description	Reference: Clause No	U/C	Condition	
1	Carrier frequencies	4.2.1	U	-	Pass
2	Nominal, and occupied channel bandwidth	4.2.2	U	-	Pass
3	RF output power	4.2.3	U	-	Pass
	Transmit Power Control (TPC)	4.2.3	C	1)Not required for channels whose nominal bandwidth falls completely within the band 5150 MHz to 5250 MHz. 2)Not required for devices that operate at a maximum mean e.i.r.p. of 20 dBm when operating in 5250 MHz to 5350 MHz or 27 dBm when operating in 5470 MHz to 5725 MHz.	N/A
	Power Density	4.2.3	U	-	Pass
4	Transmitter unwanted emissions outside the 5 GHz RLAN bands	4.2.4.1	U	-	Pass
5	Transmitter unwanted emissions within the 5 GHz RLAN bands	4.2.4.2	U	-	Pass
6	Receiver spurious emissions	4.2.5	U	-	Pass
7	Adaptivity	4.2.7	U	-	Pass
8	Receiver Blocking	4.2.8	U	-	Pass
9	User Access Restrictions	4.2.9	U	-	Pass **Note 1**
10	Geo-location capability	4.2.10	C	Where implemented by the manufacturer.	N/A

Note:

1. No related options for DFS functions will be provided in the software interfaces.
   DFS functions can be changed only by telnet command. Before the shipment of the product the telnet will be closed so that it will be inaccessible for the end user.
2. U/C Indicates whether the requirement is unconditionally applicable (U) or is conditional upon the manufacturer's claimed functionality of the equipment (C).
3. “N/A” indicates that it does not apply to this device.

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	AX1500 Whole Home Mesh Wi-Fi 6 System
Brand Name	Cudy
Test Model	M1500
Series Model	N/A
Model Difference(s)	N/A
Hardware Version	REV1.0
Software Version	2.3.0
Power Source	DC voltage supplied from AC adapter. Model: DSA-12PF11-12 FEU 120100
Power Rating	I/P: 100-240V~ 50/60Hz 0.5A O/P: +12.0V ⎓ 1.0A
Operation Frequency Band(s)	5150 MHz ~ 5250 MHz
Modulation Type	IEEE 802.11a/n/ac: OFDM IEEE 802.11ax: OFDMA
Bit Rate of Transmitter	IEEE 802.11a: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 300 Mbps IEEE 802.11ac: up to 866.7 Mbps IEEE 802.11ax: up to 1201 Mbps
Max. e.i.r.p.	IEEE 802.11a: 21.75 dBm (149.62 mW) IEEE 802.11ax(HE20): 22.47 dBm (176.60 mW) IEEE 802.11ax(HE40): 22.58 dBm (181.13 mW) IEEE 802.11ax(HE80): 22.63 dBm (183.23 mW)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20)		IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40)		IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80)	
Band 1		Band 1		Band 1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	South Star	N/A	PCB	N/A	5.85
2	South Star	N/A	PCB	N/A	5.56

Note:

1) The EUT supports CDD. Physically, the EUT provides two completed transmitters and receivers (2T2R).
2) Beamforming Gain: 3 dB.

4. The worst case for 2TX as follow:

Operating Mode / TX Mode	2TX
IEEE 802.11a	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT20)	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT20)	V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT80)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE80)	V (Ant. 1+Ant. 2)

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test	Clause	Test channels
		Lower sub-band (5150 MHz to 5350 MHz)
		5150 MHz to 5250 MHz
Centre frequencies	5.4.2	C7(see note 1)
Occupied Channel Bandwidth	5.4.3	C7
Power, power density	5.4.4	C1
Transmitter unwanted emissions outside the 5 GHz RLAN bands	5.4.5	C7(see note 1)
Transmitter unwanted emissions within the 5 GHz RLAN bands	5.4.6	C1
Receiver spurious emissions	5.4.7	C7(see note 1)
Transmit Power Control (TPC)	5.4.4	N/A(see note 2)
Adaptivity	5.4.9	C9
Receiver Blocking	5.4.10	C7

C1	The lowest declared channel for every declared Nominal Channel Bandwidth within this band. For the Power Density testing, it is sufficient to only perform this test using the lowest Nominal Channel Bandwidth.
C7	One channel out of the declared channels for this sub-band. For Occupied Channel Bandwidth, testing shall be repeated for every declared Nominal Channel Bandwidth within this sub-band.
C9	One channel (in case of single-channel testing) or a group of channels (in case of multi-channel testing) out of the declared channels.

Note :

(1) In case of more than 1 channel plan has been declared, testing of these specific requirements need only be performed using one of the declared channel plans.

(2) Testing is not required for nominal channel bandwidths that fall completely within the frequency range 5150 MHz to 5250 MHz.

(3) For radiated spurious emissions below 1 GHz and receiver spurious emissions above 1 GHz test, the IEEE 802.11ax(HE80) channel 42 is found to be the worst case and recorded.

(4) IEEE 802.11ax mode only supports full RU, so only the full RU is evaluated and measured inside report.

(5) The RF Output Power of the Beamforming mode will be lower than that of the Non Beamforming mode. Only Non Beamforming mode will be evaluated and recorded in the report.

(6) HE20/HE40/HE80 covers HT20/HT40 and VHT20/VHT40/VHT80, due to same modulation (in full RU). The power setting for 802.11n HT20/HT40 and 802.11ac VHT20/VHT40/VHT80 are the same or lower than 802.11ax HE20/HE40/HE80.


(7) For radiated spurious emissions above 18GHz test, only tested and recorded the worst case.

2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	MP_tool_8832b
Frequency (MHz)	5180
IEEE 802.11a	13
IEEE 802.11ac(VHT20)	14
IEEE 802.11ax(HE20)	14
Frequency (MHz)	5190
IEEE 802.11ac(VHT40)	14
IEEE 802.11ax(HE40)	14
Frequency (MHz)	5210
IEEE 802.11ac(VHT80)	14
IEEE 802.11ax(HE80)	14

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	Honor	14SER5 3500	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	DC Cable	NO	NO	1.5m
2	RJ45 Cable	NO	NO	10m

2.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

2.7 CUSTOMER INFORMATION DESCRIPTION

1) The antenna gain and beamforming gain are provided by the manufacturer.
2) Except for radiated spurious emissions, the results of all test items include cable losses. All cable losses are provided by the testing laboratory.

3. CENTRE FREQUENCIES

3.1 LIMIT

Clause	Test Item	Limit
4.2.1	Centre Frequencies	F(c) ±20ppm

3.2 TEST PROCEDURES


Refer to ETSI EN 301 893, clause 5.4.2.2.1.

3.3 TEST SETUP LAYOUT

Normal Condition



Extreme Condition



3.4 TEST DEVIATION

There is no deviation with the original standard.

3.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

3.6 TEST RESULTS

Please refer to the Appendix A.

4. NOMINAL / OCCUPIED CHANNEL BANDWIDTH

4.1 LIMIT

The Nominal Channel Bandwidth for a single Operating Channel shall be 20 MHz.

Alternatively, equipment may implement a lower Nominal Channel Bandwidth with a minimum of 5 MHz, providing they still comply with the Nominal Centre Frequencies defined in clause 4.2.1 of EN 301 893 (20 MHz raster).

The Occupied Channel Bandwidth shall be between 80 % and 100 % of the Nominal Channel Bandwidth. In case of smart antenna systems (devices with multiple transmit chains) each of the transmit chains shall meet this requirement. The Occupied Channel Bandwidth might change with time/payload.

During a Channel Occupancy Time (COT), equipment may operate temporarily with an Occupied Channel Bandwidth of less than 80 % of its Nominal Channel Bandwidth with a minimum of 2 MHz.

4.2 TEST PROCEDURES

Refer to ETSI EN 301 893, clause 5.4.3.2.1.

4.3 TEST SETUP LAYOUT



4.4 TEST DEVIATION

There is no deviation with the original standard.

4.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

4.6 TEST RESULTS

Please refer to the Appendix B.

5. RF OUTPUT POWER

5.1 LIMIT

Mean e.i.r.p. Limits for RF Output Power at the Highest Power Level		
Frequency Range (MHz)	Mean e.i.r.p. Limit for P_H (dBm)	
	With TPC	Without TPC
5150 to 5350	23	20/23 (see note1)

Note:	
(1)	The applicable limit is 20 dBm, except for transmissions whose nominal bandwidth falls completely within the band 5150 MHz to 5250 MHz, in which case the applicable limit is 23 dBm.

5.2 TEST PROCEDURES


Refer to ETSI EN 301 893, clause 5.4.4.2.1.

5.3 TEST SETUP LAYOUT

Normal Condition



Extreme Condition



5.4 TEST DEVIATION

There is no deviation with the original standard.

5.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

5.6 TEST RESULTS

Please refer to the Appendix C.

6. POWER DENSITY

6.1 LIMIT

Mean e.i.r.p. Limits for Power Density at the Highest Power Level		
Frequency Range (MHz)	Mean e.i.r.p. Density Limit (dBm/MHz)	
	With TPC	Without TPC
5150 to 5350	10	7/10 (see note1)

Note:	
(1)	The applicable limit is 7 dBm/MHz, except for transmissions whose nominal bandwidth falls completely within the band 5150 MHz to 5250 MHz, in which case the applicable limit is 10 dBm/MHz.

6.2 TEST PROCEDURES

Refer to ETSI EN 301 893, clause 5.4.4.2.1.

6.3 TEST SETUP LAYOUT



6.4 TEST DEVIATION

There is no deviation with the original standard.

6.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

6.6 TEST RESULTS

Please refer to the Appendix D.

7. TRANSMITTER UNWANTED EMISSIONS (OUTSIDE THE 5 GHZ RLAN BANDS)

7.1 LIMIT


Clause	Test Item	Frequency(MHz)	Limit (dBm)
4.2.4.1	Transmitter Unwanted Emissions (Outside The 5 GHz RLAN Bands)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	-54
		Other frequencies Below 1GHz	-36
		1GHz~26.5 GHz (Outside frequency ranges)	-30

7.2 TEST PROCEDURES


Refer to ETSI EN 301 893, clause 5.4.5.2.2.

7.3 TEST SETUP LAYOUT


Emission Radiated Measurement Test Set-Up Frequency Below 1 GHz



Emission Radiated Measurement Test Set-Up Frequency 1 GHz - 18 GHz



Emission Radiated Measurement Test Set-Up Frequency Above 18 GHz



7.4 TEST DEVIATION

There is no deviation with the original standard.

7.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

7.6 TEST RESULTS (30MHZ TO 1000MHZ)


Please refer to the Appendix E.

7.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix F.

8. TRANSMITTER UNWANTED EMISSIONS(WITHIN THE 5 GHZ RLAN BANDS)

8.1 LIMIT

Clause	Test Item	Limit
4.2.4.2	Transmitter Unwanted Emissions (Within the 5 GHz RLAN bands)	

8.2 TEST PROCEDURES

Refer to ETSI EN 301 893, clause 5.4.6.2.1.

8.3 TEST SETUP LAYOUT



8.4 TEST DEVIATION

There is no deviation with the original standard.

8.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

8.6 TEST RESULTS

Please refer to the Appendix G.

9. RECEIVER SPURIOUS EMISSIONS

9.1 LIMIT

Clause	Test Item	Frequency(MHz)	Limit
4.2.5	Receiver spurious emissions	30-1000	-57dBm
		1000~26500	-47dBm

9.2 TEST PROCEDURES

Refer to ETSI EN 301 893, clause 5.4.7.2.2.

9.3 TEST SETUP LAYOUT

Please refer to clause 7.3.

9.4 TEST DEVIATION

There is no deviation with the original standard.

9.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously receiving.

9.6 TEST RESULTS (30 MHZ TO 1000 MHZ)

Please refer to the Appendix H.

9.7 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Appendix I.

10. ADAPTIVITY (CHANNEL ACCESS MECHANISM)


10.1 LIMIT

Refer to ETSI EN 301 893, clause 4.2.7

10.2 TEST PROCEDURES

Refer to ETSI EN 301 893, clause 5.4.9.3.2.

10.3 TEST SETUP



10.4 TEST DEVIATION

There is no deviation with the original standard.

10.5 EUT OPERATION DURING TEST

The measurements shall be performed during normal operation.

10.6 TEST RESULTS

Please refer to the Appendix J.

11. RECEIVER BLOCKING

11.1 LIMIT


The minimum performance criterion shall be a PER of less than or equal to 10 %.

Wanted signal mean power from companion device (dBm)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 2)		Type of blocking signal
		Master or Slave with radar detection (see table D.2, note 2)	Slave without radar detection (see table D.2, note 2)	
Pmin + 6 dB	5 100	-53	-59	Continuous Wave
Pmin + 6 dB	4 900 5 000 5 975	-47	-53	Continuous Wave
NOTE 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria as defined clause 4.2.8.3 in the absence of any blocking signal. NOTE 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the same levels should be used at the antenna connector irrespective of antenna gain.				

11.2 TEST PROCEDURES

Refer to ETSI EN 301 893, clause 5.4.10.2.1.

11.3 TEST SETUP



11.4 TEST DEVIATION

There is no deviation with the original standard.

11.5 EUT OPERATION DURING TEST

The measurements shall be performed during normal receiving.

11.6 TEST RESULTS

Please refer to the Appendix K.

12. MEASUREMENT INSTRUMENTS LIST

Centre Frequency					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	BTL Test System	BTL	TestSoftware	N/A	N/A
2	MXA Signal Analyzer	Keysight	N9010A	MY56480543	Jan. 10, 2026
3	Temperature Chamber	ESPEC CORP	SU-242	93018736	Jun. 28, 2025
4	Cable	RegalWay	RWP50-402-SMSM-2M	N/A	N/A
5	Attenuator	RegalWay	RWA-201-S-10	N/A	Jun. 28, 2025
6	Attenuator	RegalWay	RWA-201-S-6	N/A	Jun. 28, 2025

Nominal / Occupied Channel Bandwidth & Power Density & Transmitter Unwanted Emissions Within The 5 GHz RLAN Bands					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	BTL Test System	BTL	TestSoftware	N/A	N/A
2	MXA Signal Analyzer	Keysight	N9010A	MY56480543	Jan. 10, 2026
3	Cable	RegalWay	RWP50-402-SMSM-1.5M	N/A	N/A
4	Attenuator	RegalWay	RWA-201-S-10	N/A	Jun. 28, 2025
5	Attenuator	RegalWay	RWA-201-S-6	N/A	Jun. 28, 2025

RF Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	X-series USB Peak and Average Power Sensor	Keysight	U2021XA	MY55190003	Jun. 20, 2025
2	X-series USB Peak and Average Power Sensor	Keysight	U2021XA	MY55190006	Jun. 20, 2025
3	Attenuator	RegalWay	RWA-201-S-10	N/A	Jun. 28, 2025
4	Attenuator	RegalWay	RWA-201-S-10	N/A	Jun. 28, 2025
5	Temperature Chamber	ESPEC CORP	SU-242	93018736	Jun. 28, 2025
6	Cable	RegalWay	SMA-SMA-1M	N/A	N/A
7	Cable	RegalWay	RWP50-402-SMSM-1M	N/A	N/A
8	BTL Test System	BTL	TestSoftware	N/A	N/A

Adaptivity					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	MXG Vector Signal Generator	Keysight	N5182B	MY57300318	Jan. 10, 2026
2	MXA Signal Analyzer	Keysight	N9010A	MY56480543	Jan. 10, 2026
3	date Acquisition Unit	Keysight	AD211	TW54033508	N/A
4	Shielding box	JiaChen	JC-PB2015	PB20132310378A	N/A
5	Cable	RegalWay	RWP50-402-SMSM-1M	N/A	N/A
6	Cable	RegalWay	RWP50-402-SMSM-1M	N/A	N/A
7	Cable	RegalWay	RWP50-402-SMSM-1.5M	N/A	N/A
8	Cable	RegalWay	RWP50-402-SMSM-1.5M	N/A	N/A
9	Cable	RegalWay	RWP50-402-SMSM-2M	N/A	N/A
10	Cable	RegalWay	RWP50-402-SMSM-2M	N/A	N/A
11	Power Divider	RegalWay	RW-PD2-0118SF30	N/A	Jun. 28, 2025
12	Power Divider	RegalWay	RW-PD2-0118SF30	N/A	Jun. 28, 2025
13	Power Divider	RegalWay	RW-PD2-0118SF30	N/A	Jun. 28, 2025
14	Power Divider	RegalWay	RWPD2-DC27-S	N/A	Jun. 28, 2025
15	BTL Test System	BTL	TestSoftware	N/A	N/A
16	Attenuator	RegalWay	RWPA-6000-110-MA	N/A	Jun. 28, 2025
17	Attenuator	RegalWay	RWA-201-S-20	N/A	Jun. 28, 2025
18	Notebook	Lenovo	ThinkBook14/16	N/A	N/A

Receiver Blocking					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wideband Radio Communication tester	R&S	CMW500	168838	Jun. 28, 2025
2	MXG Vector Signal Generator	Keysight	N5182B	MY57300318	Jan. 10, 2026
3	Power Divider	RegalWay	RW-PD2-0118SF30	N/A	Jun. 28, 2025
4	Shielding box	JiaChen	JC-PB2015	PB20132310378A	N/A
5	Cable	RegalWay	RWP50-402-SMSM-1M	N/A	N/A
6	Cable	RegalWay	RWP50-402-SMSM-1.5M	N/A	N/A
7	Cable	RegalWay	RWP50-402-SMSM-1.5M	N/A	N/A
8	Cable	RegalWay	RWP50-402-SMSM-2M	N/A	N/A


Transmitter and Receiver Spurious Emission (Radiated Measurement)_Below 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	01381	Sep. 26, 2025
2	Attenuator	EMC INSTRUMENT	EMCI-N-6-06	AT-06009	Sep. 26, 2025
3	Preamplifier	EMC INSTRUMENT	EMC330N	980855	Jun. 28, 2025
4	Cable	RegalWay	SW50T-CA038-3000	N/A	N/A
5	Cable	RegalWay	SW50T-CA038-4000	N/A	N/A
6	Cable	RegalWay	SW50T-CA038-4000	N/A	N/A
7	Signal & Spectrum Analyzer	R&S	FSV3004	101285	Jun. 28, 2025
8	Top precision	Pneumatic Mast Contorller	N/A	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A


Transmitter and Receiver Spurious Emission (Radiated Measurement)_Above 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Top precision	Pneumatic Mast Contorller	N/A	N/A	N/A
2	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
3	Signal & Spectrum Analyzer	R&S	FSV3044	101377	Jun. 28, 2025
4	Cable	RegalWay	SW50T-CA004-4000	N/A	N/A
5	Cable	RegalWay	SW50T-CA0037-2500	N/A	N/A
6	Cable	RegalWay	SW50T-CA004-3000	N/A	N/A
7	Double-Ridged Waveguide Horn Antennas	ETS-LINDGREN	3117-PA	00252542	Sep. 13, 2025
8	Preamplifier	ETS-LINDGREN	3117-PA	00252542	Jun. 28, 2025
9	Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	1137	Oct. 12, 2025
10	Pre-Amplifier	EMC INSTRUMENT	EMC184045SE	980911	Jun. 28, 2025
11	Cable	RegalWay	RWLP50-2.6A-2.92M2.92M-5M	N/A	N/A
12	Cable	RegalWay	RWLP50-2.6A-2.92M2.92M-1.5M	N/A	N/A
13	Band Reject Filter	COM-MW	ZHPF6-M6500-18000-547	07213124	Jun. 28, 2025

Remark: “N/A” denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.


13. EUT TEST PHOTO

Radiated Emissions Test Photos - Below 18 GHz





Radiated Emissions Test Photos - Above 18 GHz





APPENDIX A - CENTRE FREQUENCIES

Test Mode: IEEE 802.11a Mode		
Test Conditions		Measurement Frequency (MHz)
		5180MHz
T nom(°C)	22	5179.9620
T min(°C)	0	5179.9860
T max(°C)	40	5179.9400
Max. Deviation Frequency		-0.0600
Max. Frequency Error (ppm)		-11.58
Limit (ppm)		±20.00
Result		Pass

APPENDIX B - NOMINAL / OCCUPIED CHANNEL BANDWIDTH

Test Mode: IEEE 802.11a Mode		
Test Conditions		Occupied Channel Bandwidth (MHz)
		5180MHz
T nom (°C)	22	16.47
Limits		16~20
Result		Pass

Test Mode: IEEE 802.11ax(HE20) Mode		
Test Conditions		Occupied Channel Bandwidth (MHz)
		5180MHz
T nom (°C)	22	18.99
Limits		16~20
Result		Pass

Test Mode: IEEE 802.11ax(HE40) Mode		
Test Conditions		Occupied Channel Bandwidth (MHz)
		5190MHz
T nom (°C)	22	37.69
Limits		32~40
Result		Pass

Test Mode: IEEE 802.11ax(HE80) Mode		
Test Conditions		Occupied Channel Bandwidth (MHz)
		5210MHz
T nom (°C)	22	76.83
Limits		64~80
Result		Pass

APPENDIX C - RF OUTPUT POWER

Test Mode: IEEE 802.11a Mode at the Highest Power Level		
Test Conditions		e.i.r.p. (dBm)
		5180MHz
T nom (°C)	23	21.53
T min (°C)	0	21.75
T max (°C)	40	21.30
Max. e.i.r.p.		21.75
Limits		23
Result		Pass

Test Mode: IEEE 802.11ax(HE20) Mode at the Highest Power Level		
Test Conditions		e.i.r.p. (dBm)
		5180MHz
T nom (°C)	23	22.33
T min (°C)	0	22.47
T max (°C)	40	22.17
Max. e.i.r.p.		22.47
Limits		23
Result		Pass

Test Mode: IEEE 802.11ax(HE40) Mode at the Highest Power Level		
Test Conditions		e.i.r.p. (dBm)
		5190MHz
T nom (°C)	23	22.46
T min (°C)	0	22.58
T max (°C)	40	22.26
Max. e.i.r.p.		22.58
Limits		23
Result		Pass

Test Mode: IEEE 802.11ax(HE80) Mode at the Highest Power Level		
Test Conditions		e.i.r.p. (dBm)
		5210MHz
T nom (°C)	23	22.42
T min (°C)	0	22.63
T max (°C)	40	22.20
Max. e.i.r.p.		22.63
Limits		23
Result		Pass

Note:
1) e.i.r.p. = Conducted output power + G (Ant Gain)
2) Conducted output power = Measure result + Cable loss


APPENDIX D - POWER DENSITY

Test Mode: IEEE 802.11a Mode		
Test Conditions		Spectral Power Density e.i.r.p. (dBm / MHz)
		5180MHz
T nom (°C)	22	9.61
Limits		10
Result		Pass

Test Mode: IEEE 802.11ax(HE20) Mode		
Test Conditions		Spectral Power Density e.i.r.p. (dBm / MHz)
		5180MHz
T nom (°C)	22	9.98
Limits		10
Result		Pass


APPENDIX E - TRANSMITTER UNWANTED EMISSIONS OUTSIDE THE 5 GHZ RLAN BANDS (30MHZ TO 1000MHZ)

Test Mode	TX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	34.5590	-61.82	-0.22	-62.04	-36.00	-26.04	RMS	
2 *	90.3340	-52.39	-8.86	-61.25	-54.00	-7.25	RMS	
3	249.9960	-68.75	-3.20	-71.95	-36.00	-35.95	RMS	
4	374.9320	-70.37	-0.05	-70.42	-36.00	-34.42	RMS	
5	499.9650	-71.50	2.02	-69.48	-54.00	-15.48	RMS	
6	881.9510	-78.00	7.74	-70.26	-36.00	-34.26	RMS	


Test Mode	TX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	94.3110	-52.77	-8.02	-60.79	-54.00	-6.79	RMS	
2	139.2220	-64.87	-1.44	-66.31	-36.00	-30.31	RMS	
3	249.9960	-68.69	-3.40	-72.09	-36.00	-36.09	RMS	
4	374.9320	-69.04	-0.08	-69.12	-36.00	-33.12	RMS	
5	499.9650	-69.81	2.03	-67.78	-54.00	-13.78	RMS	
6	624.9980	-72.68	4.31	-68.37	-54.00	-14.37	RMS	


APPENDIX F - TRANSMITTER UNWANTED EMISSIONS OUTSIDE THE 5 GHZ RLAN BANDS (ABOVE 1000MHZ)

Test Mode	TX Mode IEEE 802.11a_5180MHz	Polarization	Vertical




No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	6906.6500	-58.66	8.75	-49.91	-30.00	-19.91	RMS	

Test Mode	TX Mode IEEE 802.11a_5180MHz	Polarization	Horizontal




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	6906.6500	-59.76	8.77	-50.99	-30.00	-20.99	RMS	
2	9687.8500	-57.98	10.08	-47.90	-30.00	-17.90	RMS	
3 *	15540.9500	-56.11	15.15	-40.96	-30.00	-10.96	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE20)_5180MHz	Polarization	Vertical




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	10358.5000	-61.96	10.74	-51.22	-30.00	-21.22	RMS	
2 *	15543.5000	-61.28	14.99	-46.29	-30.00	-16.29	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE20)_5180MHz	Polarization	Horizontal




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	9687.8500	-57.86	10.08	-47.78	-30.00	-17.78	RMS	
2 *	15549.4500	-58.22	15.19	-43.03	-30.00	-13.03	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE40)_5190MHz	Polarization	Vertical




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	9687.8500	-61.16	9.92	-51.24	-30.00	-21.24	RMS	
2 *	13840.1000	-61.83	13.14	-48.69	-30.00	-18.69	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE40)_5190MHz	Polarization	Horizontal




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	9687.8500	-58.73	10.08	-48.65	-30.00	-18.65	RMS	
2 *	15554.5500	-59.97	15.21	-44.76	-30.00	-14.76	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Vertical




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	9687.8500	-61.39	9.92	-51.47	-30.00	-21.47	RMS	
2 *	13893.6500	-62.90	13.15	-49.75	-30.00	-19.75	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Horizontal




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	9687.8500	-59.05	10.08	-48.97	-30.00	-18.97	RMS	
2 *	15668.4500	-62.23	15.71	-46.52	-30.00	-16.52	RMS	

Test Mode	TX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	22169.250	-61.43	3.05	-58.38	-30.00	-28.38	RMS	


Test Mode	TX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	22728.975	-61.77	4.42	-57.35	-30.00	-27.35	RMS	


APPENDIX G - TRANSMITTER UNWANTED EMISSIONS WITHIN THE 5 GHZ RLAN BANDS

Test Mode :	IEEE 802.11a_5180MHz



Note:
The MASK is only applicable within the 5150MHz to 5350MHz and 5470MHz to 5725MHz. 5350MHz to 5470MHz is applicable within the Radiation spurious,so the waveform is not displayed in the test data.

Test Mode :	IEEE 802.11ax(HE20)_5180MHz



Note:
The MASK is only applicable within the 5150MHz to 5350MHz and 5470MHz to 5725MHz. 5350MHz to 5470MHz is applicable within the Radiation spurious,so the waveform is not displayed in the test data.

Test Mode :	IEEE 802.11ax(HE40)_5190MHz



Note:
The MASK is only applicable within the 5150MHz to 5350MHz and 5470MHz to 5725MHz. 5350MHz to 5470MHz is applicable within the Radiation spurious,so the waveform is not displayed in the test data.


Test Mode :	IEEE 802.11ax(HE80)_5210MHz



Note:
The MASK is only applicable within the 5150MHz to 5350MHz and 5470MHz to 5725MHz. 5350MHz to 5470MHz is applicable within the Radiation spurious,so the waveform is not displayed in the test data.


APPENDIX H - RECEIVER SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)

Test Mode	RX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	34.5590	-61.13	-0.22	-61.35	-57.00	-4.35	RMS	
2	90.3340	-52.75	-8.86	-61.61	-57.00	-4.61	RMS	
3	249.9960	-68.46	-3.20	-71.66	-57.00	-14.66	RMS	
4	374.9320	-71.30	-0.05	-71.35	-57.00	-14.35	RMS	
5	499.9650	-71.73	2.02	-69.71	-57.00	-12.71	RMS	
6	877.1010	-77.47	7.64	-69.83	-57.00	-12.83	RMS	


Test Mode	RX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	94.3110	-55.89	-8.02	-63.91	-57.00	-6.91	RMS	
2	108.7640	-58.08	-6.24	-64.32	-57.00	-7.32	RMS	
3	249.9960	-70.67	-3.40	-74.07	-57.00	-17.07	RMS	
4	374.9320	-72.72	-0.08	-72.80	-57.00	-15.80	RMS	
5	499.9650	-72.91	2.03	-70.88	-57.00	-13.88	RMS	
6	971.0940	-79.06	8.99	-70.07	-57.00	-13.07	RMS	


APPENDIX I - RECEIVER SPURIOUS EMISSIONS (ABOVE 1000MHZ)

Test Mode	RX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Vertical




No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	6431.5000	-58.92	7.96	-50.96	-47.00	-3.96	RMS	
2	9687.8500	-62.45	9.92	-52.53	-47.00	-5.53	RMS	

Test Mode	RX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Horizontal




No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	9687.8500	-61.81	10.08	-51.73	-47.00	-4.73	RMS	

Test Mode	RX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	19201.475	-59.73	1.79	-57.94	-47.00	-10.94	RMS	

Test Mode	RX Mode IEEE 802.11ax(HE80)_5210MHz	Polarization	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	20538.525	-60.30	4.25	-56.05	-47.00	-9.05	RMS	

APPENDIX J - ADAPTIVITY

EUT Operational Mode	Frame Based Equipment	
	Load Based Equipment (CCA using 'energy detect')	√
	Load Based Equipment (CCA not using any of the mechanisms referenced)	

Clause	Test Parameter	Remark	Pass/Fail
4.2.7.3.1	Adaptive (Frame Based Equipment)	Not Applicable	N/A
4.2.7.3.2	Adaptive (Load Based Equipment)	Applicable	Pass
4.2.7.3.3	Short Control Signalling Transmissions	Applicable	Pass

Test Mode:	TX Mode_ IEEE 802.11ax(HE20)_5180MHz,IEEE 802.11ax(HE40)_5190MHz

Channel Occupancy Time and Priority Class Measured Results		
Freq.(MHz)	Channel Occupancy Time (ms)	Priority Class
5180	1.49	4
5190	0.558	4

Adaptivity Results				
Detection Threshold Level			-69.15 dBm/MHz	
Interference Signal	Freq.(MHz)		Short Control Signalling Transmissions (ms)	Number of Short Control Signalling Transmissions
AWGN	AX20	5180	0	0
OFDM		5180	0	0
LTE		5180	0	0
AWGN	AX40	5180	0	0
		5200	0	0
Limit			2.5	≤ 50
Result			Pass	


Note:
1. For an EUT with a non-zero dBi antenna gain, the final interference detection threshold level T_L at the port of the radio module in a conducted test setup shall be adjusted by the gain of the bypassed antenna and is calculated using below formulas:

Threshold Level =-75 dBm/MHz +EUT Antenna Gain.

2. Short Control Signalling Transmissions = 50 (ms) * Duty cycle (%)


Single Channel device test results

IEEE 802.11ax(HE20) Mode 5180 MHz




COT Number:10006	Idle Number:9912
Maximum COT(ms):1.49	Minimum Idle Time(us):27


IEEE 802.11ax(HE20) Mode 5180 MHz



Pn	Idle Num	Result(%)	Limit(%)	Status
0	0	0	5	Pass
1	12	0.121	30	Pass
2	12	0.242	55	Pass
3	35	0.595	80	Pass
4	9853	100	100	Pass


IEEE 802.11ax(HE20) Mode 5180 MHz
Interference Signal(AWGN)






Duty Cycle(%):0.00 Short Control Signalling Transmissions Time(ms):0.00
Test Result:Pass


IEEE 802.11ax(HE20) Mode 5180 MHz
Interference Signal(OFDM)






Duty Cycle(%):0.00 Short Control Signalling Transmissions Time(ms):0.00
Test Result:Pass

IEEE 802.11ax(HE20) Mode 5180 MHz
Interference Signal(LTE)






Duty Cycle(%):0.00 Short Control Signalling Transmissions Time(ms):0.00
Test Result:Pass

Multi-Channel device test results


Option 2:
The EUT is set to a channel bandwidth of 40MHz with the primary operating channel 5180MHz. One additional adjacent 20MHz operating channel that constructs the full 40 MHz channel bandwidth is located at 5200 MHz. Data traffic is started and then an interfering signal is injected into the EUT at 5200 MHz.

IEEE 802.11ax(HE40) Mode 5190 MHz




COT Number:10945	Idle Number:10212
Maximum COT(ms):0.558	Minimum Idle Time(us):27


IEEE 802.11ax(HE40) Mode 5190 MHz



Pn	Idle Num	Result(%)	Limit(%)	Status
0	0	0	5	Pass
1	1874	18.351	30	Pass
2	1430	32.354	55	Pass
3	678	38.993	80	Pass
4	6230	100	100	Pass


IEEE 802.11ax(HE40) Mode 5180 MHz
Interference Signal(AWGN)





Duty Cycle(%):0.00 Short Control Signalling Transmissions Time(ms):0.00
Test Result:Pass

IEEE 802.11ax(HE40) Mode 5200 MHz
Interference Signal(AWGN)



Duty Cycle(%):0.00 Short Control Signalling Transmissions Time(ms):0.00
Test Result:Pass

APPENDIX K - RECEIVER BLOCKING

Receiver Blocking Result						
P_{min}(dBm)	-90					
Modulation Mode	Operation Freq. (MHz)	Wanted Signal Mean Power from Companion Device (dBm) P_{min} + 6 dB	Blocking Signal Freq. (MHz)	Receiver Blocking Power (dBm)	PER (%)	Blocking Signal Level at which the Performance Criteria is no longer met(dBm) **(See Note)**
IEEE 802.11a 6 Mbps	5180	-84	5100	-53	2.00	-28
			4900	-47	1.60	-21
			5000	-47	1.20	-25
			5975	-47	2.40	-24
Limit	PER(Packet Error Rate) ≤ 10%					N/A
Result	Pass					Record Only

Receiver Blocking Result						
P_{min}(dBm)	-89					
Modulation Mode	Operation Freq. (MHz)	Wanted Signal Mean Power from Companion Device (dBm) P_{min} + 6 dB	Blocking Signal Freq. (MHz)	Receiver Blocking Power (dBm)	PER (%)	Blocking Signal Level at which the Performance Criteria is no longer met(dBm) **(See Note)**
IEEE 802.11a 6 Mbps	5240	-83	5100	-53	1.40	-26
			4900	-47	0.60	-23
			5000	-47	1.60	-24
			5975	-47	3.80	-22
Limit	PER(Packet Error Rate) ≤ 10%					N/A
Result	Pass					Record Only

Note:
The performance criteria had been met, the level of the blocking signal at the UUT were further increased in steps of 1 dB until the level whereby the performance criteria were no longer met.

APPENDIX L - INFORMATION AS REQUIRED BY EN 301 893 V2.1.1, CLAUSE 5.4.1

In accordance with ETSI EN 301 893, clause 5.4.1, the following information is provided by the manufacturer.

a) The Nominal Channel Bandwidth(s):

Nominal Channel Bandwidth 1: 20 MHz

Nominal Channel Bandwidth 2: 40 MHz

Nominal Channel Bandwidth 3: 80 MHz

The associated centre frequencies: in clause 1.4 of the test report.

b) For Load Based Equipment that supports multi-channel operation:

☐ The LBE equipment supports Option 1 as described in clause 4.2.7.3.2.3

☒ The LBE equipment supports Option 2 as described in clause 4.2.7.3.2.3

• The (maximum) number of channels used for multi-channel operation: 4

• These channels are adjacent channels: ☒ Yes ☐ No

• In case of non-adjacent channels, whether or not these channels are in different sub-bands:

☐ Yes ☐ No

• for LBE equipment implementing option 1 (see clause 4.2.7.3.2.3), the number of channels used for multi-channel operation when performing the test described in clause 5.4.9.3.2.3.1: N/A

In case of multi-channel operation, further information defining the channels used for these simultaneous transmissions may be required.

c) The different transmit operating modes (see clause 5.3.3.2) (tick all that apply):

☐ **Operating mode 1:** Single Antenna Equipment

- ☐ a) Equipment with only 1 antenna
- ☐ b) Equipment with diversity antennas but only 1 antenna active at any moment in time
- ☐ c) Smart Antenna Systems with 2 or more antennas, but operating in a (legacy) mode where only 1 antenna is used.

☐ **Operating mode 2:** Smart Antenna Systems - Multiple Antennas without beamforming

- ☐ a) Single spatial stream/Standard throughput
- ☐ b) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 1
- ☐ c) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 2
- ☐ d) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 3
- ☐ e) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 4

☒ **Operating mode 3:** Smart Antenna Systems - Multiple Antennas with beamforming

- ☒ a) Single spatial stream/Standard throughput
- ☒ b) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 1
- ☒ c) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 2
- ☒ d) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 3
- ☐ e) High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 4

d) In case of Smart Antenna Systems or multiple antenna systems:

• The number of Receive chains: 2

• The number of Transmit chains: 2

• Equal power distribution among the transmit chains: ☒ Yes ☐ No

• In case of beamforming, the maximum (additional) beamforming gain: 3 dB

NOTE: Beamforming gain does not include the basic gain of a single antenna (assembly).

e) TPC feature available: ☐ Yes ☒ No

h) The DFS related operating mode(s) of the equipment: N/A

☐Master

☐Slave with radar detection

☐Slave without radar detection

i) User access restrictions (please check box below to confirm):

☒the equipment is constructed to comply with the requirements contained in clause 4.2.9 in ETSI EN 301 893 V2.1.1.

j) For equipment with Off-Channel CAC functionality:

The equipment has an *"Off-Channel CAC"* function: ☐Yes ☒No

If yes, specify the *"Off-Channel CAC Time"*

• For channels outside the 5 600 MHz to 5 650 MHz range: _____hours

• If applicable, for channels (partially) within the 5 600 MHz to 5 650 MHz range: _____ hours

k) The equipment can operate in ad-hoc mode:

☒ no ad-hoc operation

☐ ad-hoc operation in the frequency range 5 150 MHz to 5 250 MHz without DFS

☐ ad-hoc operation with DFS

l) Operating Frequency Range(s):

Range 1: ☐5 150 MHz to 5 350 MHz and 5 470 MHz to 5 725 MHz

Range 2: ☐5 470 MHz to 5 725 MHz

Range 3: ☐5 150 MHz to 5 250 MHz (ad-hoc without DFS)

Range 4: ☒other, please specify: 5 150 MHz to 5 250 MHz

If the equipment has more than one Operating Frequency Range, tick all that apply.

m) The extreme operating temperature and supply voltage range that apply to the equipment:

☐-20 °C to +55 °C (Outdoor & Indoor usage)

☐0 °C to +35 °C (Indoor usage only)

☒Other: 0℃ to 40℃.

The supply voltages of the stand-alone radio equipment or the supply voltages of the combined (host) equipment or test jig in case of plug-in devices:

Details provided are for the:

☒stand-alone equipment

☐combined (or host) equipment

☐test jig

Supply Voltage ☒AC mains State AC voltage: Minimum: 100V Nominal: 230V Maximum: 240V

☐DC State DC voltage: Minimum: … Nominal: ... Maximum: ...

In case of DC, indicate the type of power source:

☐Internal Power Supply

☐External Power Supply or AC/DC adapter

☐Battery ☐Nickel Cadmium

☐Alkaline

☐Nickel-Metal Hydride

☐Lithium-Ion

☐Lead acid (Vehicle regulated)

☐Other

☐Other_____

n) The test sequence/test software used (see also ETSI EN 301 893 (V2.1.1), clause 5.3.1.2):

MP_tool_8832b

o) Type of Equipment:

☒Stand-alone

☐Combined Equipment (Equipment where the radio part is fully integrated within another type of equipment)

☐Plug-in radio device (Equipment intended for a variety of host systems)

☐Other____

p) Adaptivity (Channel Access Mechanism):

☐Frame Based Equipment

☒Load Based Equipment

r) With regards to Adaptivity for Load Based Equipment:

☒ The Load Based Equipment operates as a Supervising Device

☐ The Load Based Equipment operates as a Supervised Device

☐ The Load Based Equipment can operate as a Supervising and as a Supervised Device

☐ The Load Based Equipment makes use of note 1 in table 7 or note 1 in table 8 of ETSI EN 301 893 V2.1.1

The Priority Classes implemented by the Load Based Equipment

- When operating as a Supervising Device

☒ Priority Class 4 (Highest priority)

☐ Priority Class 3

☐ Priority Class 2

☐ Priority Class 1 (Lowest priority)

- When operating as a Supervised Device

☐ Priority Class 4 (Highest priority)

☐ Priority Class 3

☐ Priority Class 2

☐ Priority Class 1 (Lowest priority)

☒ The Load Based Equipment operates as an Initiating Device

☐ The Load Based Equipment operates as an Responding Device

☐ The Load Based Equipment can operate as an Initiating Device and as a Responding Device

With regard to Energy Detection Threshold, the Load Based Equipment has implemented either option 1 of clause 4.2.7.3.2.5 of ETSI EN 301 893 V2.1.1 or option 2 of clause 4.2.7.3.2.5 of ETSI EN 301 893 V2.1.1:

☒ Option 1

☐ Option 2

Specify which protocol has been implemented:

☒ IEEE 802.11™

☐ Other:____

s) The equipment supports a geo-location capability as defined in clause 4.2.10 of ETSI EN 301 893 V2.1.1:

☐ Yes

☒ No

End of Test Report